


Constructing a SWAT model of the St. Croix River basin, eastern Minnesota and western Wisconsin



Putting together pieces of the water-quality puzzle



Constructing a SWAT model of the St. Croix River basin, eastern Minnesota and western Wisconsin

James E. Almendinger

St. Croix Watershed Research Station, Science Museum of Minnesota, Marine on St. Croix, MN 55047

Deb Debjani

Spatial Science Laboratory, Texas A&M University, College Station, TX 77843

Mehdi Ahmadi

Spatial Science Laboratory, Texas A&M University, College Station, TX 77843

Xuesong Zhang

Spatial Science Laboratory, Texas A&M University, College Station, TX 77843

Raghavan Srinivasan

Spatial Science Laboratory, Texas A&M University, College Station, TX 77843

March 2014

Pursuant to the following project:

“Protect Water Quality of the St. Croix National Scenic Riverway”
National Park Service FY2008 Centennial Challenge Cost Share Program
Agreement J659005002C, Modification 0003
Direct funds provided by the National Park Service
Matching funds provided by the Metropolitan Council of Minnesota
and the Minnesota Pollution Control Agency

Contents

CONSTRUCTING A SWAT MODEL OF THE ST. CROIX RIVER BASIN, EASTERN MINNESOTA AND WESTERN WISCONSIN

ABSTRACT	1
INTRODUCTION	3
PROBLEM	3
STUDY AREA AND THE ORIGIN OF LAKE ST. CROIX	6
PURPOSE AND SCOPE	11
MODELING BASICS	11
MODEL TERMINOLOGY	11
SWAT MODELING PROGRAM	12
MODEL CONSTRUCTION	14
STREAM NETWORK AND SUBBASIN DELINEATION	14
LAKES: SWAT RESERVOIRS	17
LANDSCAPE DEPRESSIONS: SWAT PONDS AND WETLANDS	21
SOILS	22
LAND COVER: AGRICULTURAL LAND	24
<i>Cropland Area</i>	24
<i>General Crop Rotations in Basin Quadrants</i>	24
<i>Spatial Distribution of Rotations within Quadrants</i>	27
LAND COVER: DEVELOPED LAND	28
HYDROLOGIC RESPONSE UNIT (HRU) DETERMINATION	29
LAND USE: AGRICULTURAL PRACTICES	30
<i>Manure Quantities</i>	30
<i>Pasture</i>	36
<i>Specific Crop Rotations</i>	37
LAND USE: URBAN PRACTICES	38
LAND COVER: DIFFERENCES BETWEEN 1990s AND 2000s	40
POINT-SOURCE DATA	43
CLIMATE DATA	47
MODEL CONSTRUCTION SUMMARY	49
MODEL CALIBRATION AND VALIDATION	49
GOODNESS OF FIT MEASURES	49
HYDROLOGY	51
WATER QUALITY	56
SUMMARY AND CONCLUSIONS	63
ACKNOWLEDGEMENTS	65
REFERENCES	65
APPENDIX A: SPECIFIC CROP ROTATIONS	71

Constructing a SWAT model of the St. Croix River basin, eastern Minnesota and western Wisconsin

James E. Almendinger

St. Croix Watershed Research Station, Science Museum of Minnesota, Marine on St. Croix, MN 55047

Deb Debjani

Spatial Science Laboratory, Texas A&M University, College Station, TX 77843

Mehdi Ahmadi

Spatial Science Laboratory, Texas A&M University, College Station, TX 77843

Xuesong Zhang

Spatial Science Laboratory, Texas A&M University, College Station, TX 77843

Raghavan Srinivasan

Spatial Science Laboratory, Texas A&M University, College Station, TX 77843

Abstract

The biotic integrity and recreational value of the St. Croix National Scenic Riverway depends on its water quality. Both Minnesota and Wisconsin have declared Lake St. Croix, the lowermost 40 km of the riverway, as impaired due to excessive phosphorus and chlorophyll levels and have agreed to reduce phosphorus loads to the river by 27% over the next several decades. Most of these loads come from diffuse nonpoint sources, and so reducing them will require changing land use and management practices in the 20,000-km² contributing basin. A computerized watershed model that simulates rainfall-runoff, erosion, and nutrient-transport processes can help guide decisions about which best management practices are most effective and where to implement them. We here document the construction of such a watershed model for the St. Croix basin using the Soil and Water Assessment Tool (SWAT), a program developed by the USDA to predict nonpoint loads of sediment and nutrients from large basins over long periods of time. Available digital data sets of topography and hydrography were used to subdivide the basin into 419 subbasins. The 39 largest lakes intersecting the channel system were modeled explicitly; the many other lakes and wetlands were treated as aggregated surface-water storage in each subbasin. Lake St. Croix was modeled as four separate, sequential pools. Land cover in the model was set to either of two separate decades, the 1990s (1990-99) and the 2000s (2000-09). Agricultural practices were configured to account for crop rotations, tillage practices, livestock grazing, and applications of manure and inorganic fertilizer. Unique combinations of land-cover, soil type, slope, and subbasin resulted in a total of 3,010 hydrologic response units (HRUs), about seven per subbasin. The model was calibrated to observed data for 2000-07 and validated to

data for 1990-99. Calibration of monthly flows was based on data from two main-stem stations (Danbury and St. Croix Falls) and from three tributary stations (Kettle, Snake, and Apple rivers), with excellent model fits. Monthly loads of sediment and nutrients were calibrated based on data at a single main-stem station at Stillwater, MN, with acceptable model fits for both suspended sediment and total phosphorus. The St. Croix SWAT model offers the most comprehensive whole-basin tool available for identifying where problems exist on the landscape, what new problems may arise as land is developed and climate changes, and which best-management practices are most likely to be effective in reducing nonpoint-source pollution. In short, the model provides an integrated, whole-basin framework for making sound, science-based decisions in how best to restore and protect the St. Croix River, thus securing the nation's investment in the St. Croix National Scenic Riverway.

Introduction

Problem

For its scenic, recreational, biotic, and water-resource values, the upper St. Croix River (Figure 1) was included in the first group of only eight rivers nationwide to be federally designated as a National Scenic and Recreational Riverway by congressional act in 1968. Four years later in 1972, the riverway was expanded to include the lower St. Croix to its confluence with the Mississippi River (Waters, 1977). The riverway corridor harbors at least 60 state and federally listed endangered or threatened species (Holmberg et al., 1997), including two federally endangered mussel species, the winged mapleleaf and the pearly Higgins eye (Coffin and Pfanmuller, 1988). The river is adjacent to one of the largest population centers in the upper Midwest, the Minneapolis-St. Paul metropolitan area, and is consequently a heavily-used and highly-valued resource, with more than one million visitors annually (NPS, 1995).

However, despite its apparent high quality, the St. Croix River has been significantly impacted by inputs of sediment and nutrients and is far from its original pristine condition. Recent studies have demonstrated that the river receives about four times the natural loads of sediment and phosphorus from its tributaries (Triplett et al., 2009). The increase in loads accelerated after 1940 with the mechanization of agriculture and the widespread application of inorganic fertilizers. As a consequence, during the 1940s the algal community shifted from being benthic-dominated (bottom-dwelling) to planktonic-dominated (free-floating) (Edlund et al., 2009a). Such a shift at the bottom of the food chain has implications for nearly all other aquatic species. Dwindling populations of endangered species, notably mussels, indicates that there have been serious compromises to the health of the river.

Advances in waste-water treatment and soil conservation have held point and nonpoint phosphorus loads in check for the last few decades, but population increases and attendant land-use changes may overwhelm this relative success (Edlund et al., 2009b). The Minneapolis-St. Paul metropolitan area is expanding rapidly into the lower basin of the St. Croix, encouraged by enlarged transportation corridors, planned river crossings, and commercial developments. Higher prices for corn and soybeans will encourage farmers to expand row-crop acreage at the expense of grassland acreage enrolled in conservation reserve programs.

The lowermost 40 km of the riverway comprises Lake St. Croix, a riverine lake naturally impounded at its confluence with the Mississippi River (Zumberge, 1952; Wright et al., 1998; Blumentritt et al., 2009). Lower velocities, increased hydraulic residence time, and anaerobic hypolimnetic waters promote internal loading of phosphorus from the lake sediments, escalating the eutrophication from increased phosphorus loads. Whereas water-column total phosphorus concentrations increased by a factor of two or three since Euro-American settlement, the flux of biogenic silica (a measure of algal productivity) increased by a factor of 5.5. That is, because of internal recycling of nutrients in the lake, each unit increase in phosphorus resulted in about twice the unit increase in algal productivity (Edlund et al., 2009a).




Figure 1. The St. Croix River basin in eastern Minnesota and western Wisconsin.

In 2008-09, both Minnesota and Wisconsin declared Lake St. Croix to be impaired by eutrophication from excess phosphorus loads, according to section 303(d) of the Clean Water Act. This declaration triggered a total daily maximum load (TMDL) study, which aimed to reduce phosphorus loads by 27% to bring the lake into compliance with Minnesota and Wisconsin standards (MPCA and WDNR, 2012). By accounting for a margin of safety and reserve capacity, the TMDL updated the 20%-reduction goal set in 2004 by the interagency St. Croix Basin Water Resources Planning Team (SCBWRPT, 2004), which was based in part on aiming to return the lake to 1940s conditions, when the lake underwent the ecological transition from benthic- to planktonic-dominated algae (Edlund et al., 2009a). Multiple agencies have shared responsibility for management of land and water resources within the St. Croix basin, which extends over 19 counties in two states, comprising dozens of local units of government (Figure 1). The many players in the watershed emphasize the need for close cooperation between lead state and federal agencies, and for a whole-basin approach to achieve the TMDL recommendations. Local units of government can do their part, but they need to know how their efforts fit within the context of the whole basin.

Previous studies have shown that most of the phosphorus reaching Lake St. Croix comes from nonpoint sources. Based on data from 1988-99, Robertson and Lenz (2002) estimated that in wet years about 87% of the phosphorus load came from nonpoint sources and about 8% from point sources, and in dry years the split was 52% from nonpoint and 29% from point sources (the remainder coming from internal loading from lake sediments). Edlund et al. (2009b) combined historic flow and point-source data with lake-sediment data (from Triplett et al., 2009) to estimate decadal average phosphorus loads to Lake St. Croix and to partition those loads between point, nonpoint, anthropogenic, and natural sources. For the 1990s, they estimated about 12% of the phosphorus load was from point sources and 88% from nonpoint sources; furthermore, the nonpoint sources can be partitioned into about 40% from natural and 48% from anthropogenic sources. Internal loading would only add to these loads. Excluding the natural-source loads, fully 80% of the anthropogenic phosphorus loads were from nonpoint sources, and 20% from point sources. Clearly, to reduce total phosphorus loads to Lake St. Croix, strategies to reduce the nonpoint loads must be part of the solution.

Computer models of watersheds that simulate rainfall-runoff, erosion, and nutrient transport processes are extremely useful tools to help guide watershed managers in the implementation of remediation practices to reduce nonpoint-source pollution (Borah and Bera, 2004). Models can also enhance the value of monitoring data by extending the spatial and temporal scales to which the data apply. Spatially, models can identify subwatersheds and land-use practices within a watershed that may be the principal contributors of pollutant loads monitored at the watershed outlet. Temporally, models can be run for times and climatic conditions beyond the window of monitoring data, thereby providing a context by which the representativeness of the monitoring data can be evaluated. Furthermore, computer models create an objective framework for a whole-basin approach to management of land and water

resources. The model provides the overall context for each subunit, wherein the contributions of each unit can be evaluated against the whole. This report describes the construction of such a computer model of the St. Croix River basin to document data inputs and model configuration as a foundation for applying the model to specific management needs.

Study Area and the Origin of Lake St. Croix

The St. Croix River drains a basin of about 20,000 km² and extends 250 km from its headwaters to its confluence with the Mississippi River, over which distance it loses only 100 m in altitude (Figure 1). The federally designated St. Croix National Scenic and Recreational Riverway also includes the 158-km-long Namekagon River in Wisconsin, which joins the St. Croix just upstream of the Minnesota/Wisconsin border. At least 15 other major tributaries contribute to the St. Croix from the basin beyond the narrow riverway corridor. As noted earlier, the lower 40 km of the riverway, from Stillwater, MN, to Prescott, WI, is a natural impoundment called Lake St. Croix, dammed at its mouth by sediment from the Mississippi River. Because of the increased hydraulic residence time in Lake St. Croix, the lake suffers from eutrophication that is not always expressed in upstream contributing reaches.

The climate of the St. Croix basin is strongly continental, with cold dry winters and warm humid summers. In Grantsburg, WI, near the basin centroid, the 1971-2000 normal mean temperature is -12.9 deg C (9 deg F) for January and 20.6 deg C (69 deg F) for July. The normal annual precipitation is 808 mm (31.8 inches), 42% of which falls during summer (Jun-Jul-Aug) and only 10% during winter (Dec-Jan-Feb) (NCDC, 2011). Mean annual water yield (also called mean annual runoff) differs across the basin by more than a factor of two, from about 6.6 inches the southwest part of the basin to 13.7 inches in the northeast part, with an average of 9.75 inches (248 mm) over the basin (Figure 2; data from D. Lorenz, U.S. Geological Survey, personal communication, 2010, based on data compiled for Lorenz et al., 2010). This volume equates to a mean annual flow at the outlet of the basin of 157 cms (cubic meters per second; about 5500 cubic feet per second [cfs]). If the mean annual precipitation at Grantsburg is representative of the basin, then mean annual evapotranspiration (ET) would be the difference between precipitation and water yield, or about 560 mm (22 inches).

Most of the land cover in the basin is undeveloped (over 80%), with forest being the single largest category and predominate in the northern half of the basin (Table 1 and Figure 3). According to land use interpreted from satellite imagery, in the early 1990s forest occupied about 46% of the land area, and it appears to have expanded to about 55% by the mid-2000s (meaning 2000-09). Water and wetland areas occupy about 14-19% depending on the data set. While some undeveloped land such as pasture can yield elevated phosphorus loads, the principal sources of anthropogenic nonpoint loads of phosphorus are expected to be tilled cropland and developed urban areas (both residential and non-residential). Cropland is found mostly in the southern half of the basin and has (according to these data sets) declined from about 16% of the basin area in




Figure 2. Mean annual water yield in the St. Croix basin, inches per year, 1940-2008.

the early 1990s to about 9% in the mid-2000s. Conversely, over the same time period, developed lands have increased from about 2% of the basin area to about 5%. A visual comparison of Figures 3a and 3b will show a general decrease in cropland (yellow) and increase in forest (green), and an expansion of urban areas (red and pink).

However, a comparison of values in Table 1 demonstrates the imprecision among the spatial data sets due to different algorithms used to interpret satellite imagery. While the above trends in cropland and urban lands may be qualitatively correct, other data sets should be examined in trying to quantify the trends. In particular, we note that the tabular NASS data




Figure 3. Land cover in the St. Croix basin for (a) 1992 and (b) 2007.

sets of cropland area, available for each county for each year, indicated that the percentage area of tilled cropland in the basin went from 11.7% in the 1990s to 11.3% in the 2000s – a nearly insubstantial decline in contrast to the 7% (from 16% to 9%) decline indicated by the spatial data sets (see Land Cover section below).

The St. Croix River occupies its ancient bedrock valley, which is a remnant of the North American mid-continent rift system extending southward from Lake Superior. All but the southernmost tip of the basin was overrun by the last (Wisconsinan) glacial advance (Wright, 1972; Hobbs and Goebel, 1982). Consequently the surficial geology is dominated by sandy glacial drift, most of which was deposited by ice from the Superior lobe of the Laurentide ice sheet. This ice lobe retreated from the basin by about 20,000 years ago, leaving behind a hummocky landscape of moraines interspersed with sandy outwash and lacustrine plains, many of which are occupied by peatlands today (about 10-15% of the basin area). These peatlands deliver humic-stained water to the river, giving it a distinctive tea-color. Sometime near 18,000 years ago, an offshoot from the Des Moines ice lobe occupying the Mississippi River valley to the southwest spilled northeasterly into the basin and deposited a tongue of calcareous drift, much of which was outwash, extending to Grantsburg, WI. From these parent materials, soils in the basin tend to be sands to sandy-loams and generally well drained. However, the flat topography can result in poor drainage with shallow water tables despite the coarse soils. The hummocky landscape and fairly permeable surficial deposits result in substantial areas of closed surficial drainage and a strong influence of groundwater discharge on streamflow.

During glacial recession, the ice front retreated far enough north to create pro-glacial lakes Agassiz and Duluth, and meltwaters spilling from these lakes scoured the valleys of the three major rivers of the upper Midwest: the Minnesota (designated as Glacial River Warren when carrying meltwater), the Mississippi, and St. Croix rivers. When meltwater flows ceased, alluvial fans from tributaries dammed flow at points along these rivers, creating a series of riverine lakes. In particular, about 10,300 years ago the alluvial fan of the Chippewa River dammed the Mississippi River, about 100 km southeast of present-day Minneapolis-St. Paul. This created Lake Pepin, which at that time extended all the way north to St. Paul and up the St. Croix valley as well (Blumentritt et al., 2009). Hence the origin of Lake St. Croix is about contemporaneous with the origin of Lake Pepin, although similar alluvial-fan dams within the St. Croix valley may have created local pools prior to the formation of Lake Pepin. Gradually the delta of the Mississippi River at the head of Lake Pepin prograded downstream, thus shortening the lake. When the delta prograded past the confluence with the St. Croix River, the resulting sediment plug at the mouth of the St. Croix thereafter became the functional outlet threshold for Lake St. Croix. The scouring of the St. Croix valley by late-glacial meltwaters resulted in tributary outlets being abandoned high in the valley walls. Where these walls are bedrock, the tributaries now spill down rock gorges. Where the valley walls are glacial drift, however, tributaries may still be downcutting to achieve gradient equilibrium with the lowered base level of the St. Croix.

Purpose and Scope

The purpose of this report is to document the data sets and methods used to construct and calibrate a computer model of the St. Croix River basin in eastern Minnesota and western Wisconsin. The level of detail in this documentation is aimed principally to give technically trained agency personnel enough information to understand the strengths and weakness of the model. This understanding will help resource managers to interpret model output in realistic ways that are most useful to them. Some introductory material regarding watershed modeling is included to help those readers with less technical backgrounds and to standardize some of the modeling terminology as used in this report.

Modeling Basics

Model Terminology

A watershed model is a computer program that simulates selected hydrological processes within a study watershed. Watershed here refers to the directly contributing landscape surface with a continuous downward path to the stream channel, plus smaller areas of closed drainage embedded within or contiguous to the directly contributing area that would contribute runoff should they ever spill. Hydrological processes commonly include components of the hydrological cycle (evapotranspiration, infiltration, overland runoff), processes in channels and reservoirs, and transport of sediment and nutrients. Because these processes operate fundamentally the same in all watersheds, a watershed-modeling program can be written that includes equations describing each of these processes in a generic or default way. A watershed model is initially constructed, then, by providing a watershed-modeling program with spatially referenced geographic data specific to a study watershed, including topography, soils, and land cover. The model is further configured by providing specific characteristics of these geographic features. Such information includes the geometries of reservoirs and other landscape depressions that can modify runoff hydraulics and pollutant transport. Additionally, the model must be informed of the land-management practices for each land-cover type, in particular what crop rotations, fertilizer applications, and tillage practices should be applied to agricultural land cover.

Once constructed, a model is run by providing an input file of weather over a selected period of time. The model then calculates the following: how much water infiltrates, evapotranspires, or runs off to the receiving channel; the mass of sediment and nutrients transported to the channel; and the routing (amount and timing) of water, sediment, and nutrients down the channel network to the watershed outlet. The primary outputs from the model are streamflow and quantities of sediment and nutrients delivered to the watershed outlet or other selected points within the watershed. To test how well the model simulates reality, model

output is compared with actual data collected from the watershed. A newly constructed model must commonly be adjusted to obtain an acceptable fit between the model output and the actual data. This process of adjusting a model is called calibration (or parameterization) and is done by making small changes in the input data or in the coefficients (parameters) within the model equations. The calibrated model is then run over a second time period for which further monitoring data are available. If the model output acceptably fits this second data set, the model is said to be validated.

SWAT Modeling Program

The Soil and Water Assessment Tool (SWAT) is a watershed modeling program developed by the Agricultural Research Service (ARS) of the U.S. Department of Agriculture (USDA) (Arnold et al. 1998). SWAT's purpose is "to predict the impact of land management practices on water, sediment and agricultural chemical yields in large complex watersheds with varying soils, land use and management conditions over long periods of time" (Neitsch et al. 2011, p. 1). SWAT is a well-supported modeling program with a large user base that has grown over the past ten years. Although SWAT was originally developed for use in rural watersheds, routines to handle urban landscapes have been added and continually improved.

Model construction requires inputs of hydrography, topography, soils, land cover, and agricultural management practices. Data input is facilitated by the program ArcSWAT (Winchell et al., 2013), an interface with ArcGIS geographic information systems (GIS) software (ESRI, 2012). ArcSWAT uses the topographic data to delineate the watershed into subbasins and to characterize slopes. Within each subbasin, the interface calculates the total area for each unique combination of land cover, soil type, and slope class, which are three critical factors determining the hydrologic (rainfall-runoff) response of a landscape unit. Each unique combination is defined as a "hydrologic response unit" (HRU), whose aggregate area in each subbasin is modeled as a contiguous land area with uniform soil, land cover, and slope that drains to the subbasin's channel (Figure 4). Including all possible HRUs, many of which may be small and hydrologically insignificant, can add undue complexity to the model and make run-times inefficient. Consequently, the ArcSWAT interface helps the user select the principal land cover types, soil types, and slope categories to use in determining the HRUs to include in the model. Thresholds of percent of subbasin area can be set for each factor, below which data are ignored. For example, if a 10% threshold is selected for land cover, only land-cover categories with areas greater than 10% of the subbasin area will be considered. The modeler faces significant trade-offs in this step, balancing model complexity against efficiency.

Hence, the subbasin is the smallest unit with spatial meaning in SWAT; within a subbasin, the spatial relations among different land uses and soils are lost. The HRU concept simplifies the calculations of hydrological processes in the model; however, the loss of spatial information within the subbasin introduces a measure of unrealism and requires caution in interpreting model




Figure 4. Conceptualization of hydrological response units (HRUs) within subbasins in a SWAT model.

results. In other words, the SWAT program views the world as consisting of large fields (HRUs) of uniform soil and vegetation sloping directly to a stream channel, whereas in the real world the flow path from field to stream is usually quite a bit more complicated. For the St. Croix SWAT model, the watershed was divided into 419 subbasins (about 50 km² on average), with 3010 HRUs (about seven per subbasin on average).

SWAT runs on a daily time step, requiring input of daily precipitation and daily minimum and maximum temperatures. Missing weather data are created on the fly by a weather generator program embedded within SWAT that statistically mimics data from nearby weather stations. SWAT allows detailed agricultural management practices to be simulated, tracking planting, tillage, and fertilization operations and calculating resultant plant growth during the year. SWAT partitions daily rainfall into infiltration and runoff based on a modified curve-number method.

Evapotranspiration is calculated based on available soil water (which is tracked by SWAT) and climatic conditions. Infiltrated water beyond soil field capacity becomes groundwater recharge, which moves to the stream based on a user-supplied baseflow recession constant. Overland runoff transports sediment and nutrients to the channel based on soil erodibility, land cover, peak flow velocity, and solubility (partition coefficient) considerations. The model allows some runoff from each subbasin to be intercepted by depression storage, called ponds or wetlands in SWAT, where some sediment and nutrient loss can occur, before being delivered to the channel. Water and its load of suspended sediment and nutrients reaching the channel are routed downstream via a variable storage algorithm. The model allows channel sedimentation and erosion, as well as biological transformations of nutrients via algal growth, settling, and decomposition. All on-channel lakes, whether natural or human-made, are called reservoirs in the model; they greatly influence peak flows and can trap significant quantities of sediment and nutrients.

Model output consists of flows and transported constituents at selected spatial and temporal scales. Output is available for each HRU, subbasin, and reservoir and can be summarized as daily, monthly, or annual averages for selected years of the model run.

Model Construction

This section reviews the data sets used to construct the SWAT model of the St. Croix River basin, including spatial data and temporal data. Table 2a lists the spatial data sets required for model construction, which lay the geographic framework for the model. These include hydrography, topography, land cover, and soils. Most of these datasets were downloadable through the web from the listed agencies. Table 2b lists the temporal data sets, which include weather and point-source input data sets as well as monitoring data sets used later during the calibration process.

Stream Network and Subbasin Delineation

ArcSWAT can use the grid-based tools within ArcGIS to automatically delineate the stream network and subbasin boundaries based on a digital elevation model (DEM) of the area. We used the 30-m DEM data set available from the USGS, which would commonly be adequate for basins the size of the St. Croix (Figure 5a). However, automated watershed delineation routines are error-prone in landscapes like that of the St. Croix basin because the geologically young surface has a poorly developed drainage system, with many closed depressions and large flat areas where drainage direction is ambiguous.

To reduce delineation errors due to errors or ambiguities in the DEM, a known stream network can be “burned” into the DEM to force channels to be delineated in the correct positions, thereby increasing the accuracy of the subbasin boundaries between these channels. Fortunately,

Table 2. Principal datasets for constructing the St. Croix SWAT model.

Item	Agency	Reference	Dataset	Format
(a) SPATIAL DATASETS				
Watershed base	MDNR	(1)	Hydrologically corrected minor subwatershed delineations	Polygon shapefile
Stream channels	MDNR	(1)	Hydrologically corrected high-density flow network	Polyline shapefile
Open water	MDNR	(2)	Open Water (24K Hydrography)	Polygon shapefile
Lake geometry	MDNR	(2)	Lake basin morphology	Polygon shapefile
Topography	USGS	(3)	Digital Elevation Model (DEM), 30-m resolution	Grid
Soils	USDA/NRCS	(4)	STATSGO (State Soil Geographic Database)	Polygon shapefile
Soils	USDA/NRCS	(5)	SSURGO (Soil Survey Geographic Database)	Polygon shapefile
Land cover	USDA/NASS	(6)	Crop Data Layer (CDL), 2006-10	Grid
Land cover	USGS	(3)	National Land Cover Dataset (NLCD), 1992, 2001, 2006	Grid
Land cover	UM	(7)	Land cover classification, 2007	Grid
(b) TIME-SERIES DATASETS				
Precipitation	NCDC	(8)	Cooperative Network weather stations	Tabular, time series
Temperature	NCDC	(8)	Cooperative Network weather stations	Tabular, time series
Point sources	MPCA, WDNR	(9)	Various	Tabular, time series
Loads	MCES	(10)	St. Croix River at Stillwater	Tabular, time series
Flow and loads	USGS	(11)	St. Croix River at Danbury and at St. Croix Falls Major tributaries for WY1999	Tabular, time series
Flow and loads	MPCA	(12)	Major Minnesota tributaries	Tabular, time series
Loads	Chisago SWCD	(13)	Sunrise River at Sunrise, 2006-08	Tabular, time series
Flow and loads	MCES	(14)	Valley Creek, Browns Creek (Minnesota tributaries to Lake St. Croix)	Tabular, time series
Agricultural data	USDA/NASS	(15)	Crop yields and harvested acreages; livestock populations. Annual countywide data, for the 19 counties overlapped by the St. Croix basin.	Tabular

ABBREVIATIONS:

MCES, Metropolitan Council Environmental Services; MDNR, Minnesota Department of Natural Resources; MPCA, Minnesota Pollution Control Agency; NASS, National Agricultural Statistics Service; NCDC, National Climatic Data Center; NRCS, Natural Resources Conservation Service; SWCD, Soil and Water Conservation District; USACE, U.S. Army Corps of Engineers; USDA, U.S. Department of Agriculture; USGS, U.S. Geological Survey; WDNR, Wisconsin Department of Natural Resources

REFERENCES:

(1) Vaughn 2010 and S.R. Vaughn, MDNR, personal communication, 2010. (2) MDNR 2010. (3) USGS 2010. (4) NRCS 2008a. (5) NRCS 2008b. (6) NASS 2011. (7) Marv Bauer, Remote Sensing Laboratory, Department of Forestry, Univ. of Minnesota, personal communication 2010. (8) NCDC 2010. (9) Edlund 2009b; Magalene 2009; Steve Weiss, MPCA, personal communication, 2010; Kathy Bartilson, WDNR, personal communication, 2010. (10) Karen Jensen, MCES, personal communication 2011. (11) Lenz et al. 2003 and B. Lenz, USGS, personal communication, 2005. (12) Chris Klucas, MPCA, personal communication, 2011. (13) Thiel 2009. (14) MCES 2011. (15) NASS 2009, 2010.

the Minnesota Department of Natural Resources (MDNR) has extensively surveyed the drainage network in the state, and they have constructed spatial data sets of hydrologically corrected flow networks and minor watershed boundaries (Vaughn, 2010). The flow networks from the MDNR were extended across state lines for those watersheds straddling state borders, which consequently included most of the St. Croix basin. The only area missing was the subwatershed of the upper Namekagon River, in the northeastern tip of the basin. We downloaded a current stream network for that subbasin from the Wisconsin Department of Natural Resources (WDNR) and merged it with the MDNR data, to create a complete flow network for the basin. The entire flow network was carefully reviewed and manually edited where necessary to create a continuously connected simple flow network (i.e., with no gaps and no loops). Stream connections were simplified as needed where flow lines converged on virtual confluences within the boundaries of some lake lakes. This was especially important for Lake St. Croix, where in the original data set the nodes (junctions) of tributary flow lines with the main channel were not always close to the tributary mouths.

Given this DEM with the corrected and edited flow network burned in, ArcSWAT delineated the flow network and identified all confluences, or nodes, where the flow network branched. These represented subbasin outlets, except where modified as noted. The user can





Figure 5. (a) Topography of the St. Croix basin and (b) the lakes, stream network, and subbasin delineation in the SWAT model.

force the creation of extra subbasin outlets at other points along the stream network as needed. We added points to locate the outlets and inlets to most on-channel lakes included in the model, called “reservoirs” in SWAT, and we deleted any in-lake nodes. The net effect was that we moved in-lake nodes to the lake margin at mouth of each inlet. This added detail assured that the subbasin delineation routine in ArcSWAT would make each lake outlet coincide with a subbasin outlet, and that each inlet would have a distinct subbasin, separate from the direct drainage area of the lake.

The St. Croix basin has far more lakes than can be included individually in the model. We arbitrarily chose to consider lakes with surface areas larger than 200 ha (about 500 acres), which resulted in about 40 lakes. We included a few smaller lakes of particular interest based on previous studies (namely, three reservoirs in the Willow River watershed, western Wisconsin). We also separated Lake St. Croix into four pools, to correspond to previous studies (Robertson and Lenz, 2002; Triplett et al., 2009; Edlund et al., 2009a and b). A total of 45 lakes were identified by this process for possible inclusion, 39 of which were selected for this version of the model. The remaining open-water bodies were simulated as Ponds, which are conceptual aggregations of water bodies in each subbasin (see SWAT Ponds and Wetlands section below).

Finally, given the DEM, the channel network with branch points (nodes), and the reservoir inlets and outlets, the delineation routine within ArcSWAT created a total of 419 subbasins within the St. Croix basin (Figure 5b).

Lakes: SWAT Reservoirs

The reservoirs (on-channel lakes) included in the model needed further configuration to account for their hydraulic influence on streamflow (Table 3). For lakes on the Minnesota side of the basin, reported areas and volumes were available as attributes attached to the lake morphology spatial data set posted by the MDNR. For Wisconsin lakes, reported areas and volumes were taken from WDNR (2009). If volume was not reported, it was calculated from lake area and mean depth; if mean depth was not reported, it was estimated as half the maximum depth.

SWAT requires that each reservoir be given a principal volume and area (below which the reservoir will not spill) and an emergency volume and area (above which all water is released downstream). These data are not commonly available for lakes, and estimating their values would require knowledge of how lake volume and area change as lake level changes. In a previous study in the Sunrise River watershed, one of the principal tributaries to the St. Croix, we used bathymetric data for 11 lakes to construct the following relations between lake area (which is commonly known), and how area and volume change with a change in lake level:

- (1) “Area change factor” = change in lake area (ΔA) per change in lake water level (ΔH):

$$\text{Area change factor} = 7.8761 * \sqrt{A} - 48.669$$

$$(N = 11, r^2 = 0.91)$$

Table 3. Data summary for on-channel lakes included as reservoirs in the SWAT model of the St. Croix River basin.

Name	Lat	Lon	Area (ha)			Volume (ha-m)			Mean D (m)
			Reported	Principal	Emergency	Reported	Principal	Emergency	
<i>Border Pools (upstream to downstream)</i>									
St. Croix Falls Reservoir	45.426	-92.648	241	205	278	960	879	1041	3.98
Lake St. Croix Pools:									
Bayport Pool	45.030	-92.777	1134	1026	1242	7710	7215	8205	6.80
Troy Beach Pool	44.940	-92.757	1266	1150	1382	13300	12739	13861	10.51
Black Bass Pool	44.870	-92.769	545	477	613	7360	7150	7570	13.50
Kinnickinnic Pool	44.788	-92.791	583	512	654	5710	5482	5938	9.79
<i>Minnesota Lakes</i>									
Big Marine Lake	45.219	-92.859	684	605	762	2419	2144	2693	3.54
Coon Lake	45.305	-93.168	632	557	706	1237	986	1487	1.96
Cross Lake	45.852	-92.944	374	323	426	1567	1432	1702	4.18
Forest Lake	45.273	-92.948	913	818	1007	2988	2603	3373	3.27
Green Lake	45.343	-92.900	694	614	773	2200	1921	2480	3.17
Knife Lake	45.981	-93.297	510	445	574	1347	1153	1541	2.64
Lindstrom-Chisago Lakes	45.367	-92.866	681	603	760	2216	1943	2490	3.25
North Center Lake	45.406	-92.828	373	321	424	813	679	946	2.18
Pine Lake	46.198	-93.062	314	269	360	1419	1309	1528	4.51
Pokegama Lake	45.845	-93.040	614	540	687	2148	1906	2390	3.50
Rush Lake	45.687	-93.068	1239	1124	1353	3857	3310	4405	3.11
South Center Lake	45.378	-92.821	411	355	466	1628	1478	1779	3.97
Sturgeon Lake	46.379	-92.757	691	611	770	3897	3619	4175	5.64
Sunrise Lake	45.428	-92.865	308	263	352	350	243	457	1.14
<i>Wisconsin Lakes</i>									
Balsam Lake	45.465	-92.426	832	742	921	4689	4344	5034	5.64
Bardon Lake	46.213	-91.872	337	289	385	3080	2961	3199	9.14
Bass Lake	45.066	-92.649	169	142	196	901	846	955	5.33
Big Round Lake	45.524	-92.301	411	355	466	1253	1102	1403	3.05
Big Sand Lake	45.824	-92.218	567	497	636	1555	1335	1775	2.74
Bone Lake	45.535	-92.389	721	640	803	5055	4763	5347	7.01
Cedar Lake	45.214	-92.571	448	389	507	1912	1746	2079	4.27
Clam Lake	45.793	-92.325	625	551	699	2382	2135	2629	3.81
Deer Lake	45.402	-92.522	327	280	374	2589	2475	2704	7.92
Devils Lake	45.909	-92.337	405	350	460	1729	1581	1877	4.27
Eau Claire Lakes	46.294	-91.513	1093	987	1199	7552	7078	8026	6.91
Little Falls Lake	45.018	-92.695	70	61	78	166	139	192	2.38
Mallalieu	44.990	-92.743	109	92	126	180	144	216	1.65
McKenzie Lakes	45.926	-92.039	694	615	774	4127	3847	4406	5.94
Minong Flowage	46.152	-91.928	633	558	708	1737	1486	1988	2.74
Namekagon Lake	46.223	-91.104	1306	1188	1425	6371	5790	6953	4.88
Nancy Lake	46.093	-91.984	306	262	351	1822	1715	1928	5.94
Nelson Lake	46.093	-91.470	1013	912	1114	3398	2963	3832	3.35
New Richmond Flowage	45.127	-92.529	96	81	110	102	70	134	1.07
Sand-Birch Island Lakes	45.932	-92.161	729	647	811	3332	3036	3628	4.57
Shell Lake	45.733	-91.899	1045	942	1148	7323	6873	7773	7.01
Spooner Lake	45.840	-91.824	442	384	501	943	779	1107	2.13
St. Croix Flowage	46.256	-91.872	774	689	860	1652	1335	1970	2.13
Upper St. Croix Lake	46.357	-91.803	358	308	409	1420	1292	1548	3.96
Wapogasset Lake	45.328	-92.425	480	418	542	2488	2307	2669	5.18
Yellow Lake	45.919	-92.398	926	830	1021	5362	4971	5754	5.79

NOTES: Lat, latitude of lake centroid; Lon, longitude of lake centroid; ha, hectare; ha-m, hectare-meter (a measure of volume); D, depth, m, meter; "Principal" refers to lake area and volume at the level of the lake's threshold. "Emergency" refers to the area and volume at the level the lake is unlikely to rise above. See text for explanations of how Principal values, Emergency values, NSED, and PSETLR were estimated. Reported areas and volumes for Minnesota lakes were taken from the attribute table of the lake morphology spatial data set posted by the Minnesota Department of Natural Resources. Reported areas and volumes for Wisconsin lakes were taken from WDNR, 2009, Wisconsin Lakes, Publication PUB-FH-800, 180 pp. Volume was calculated, as necessary, from reported lake area and mean depth; if mean depth was not reported, it was assumed to be half the maximum depth.

(2) “Volume change factor” = change in lake volume (ΔV) per change in lake water level (ΔH):

$$\text{Volume change factor} = 1.2074 * \text{sqrt}A^2 - 13.755 * \text{sqrt}A + 83.369$$

$$(N = 11, r^2 = 0.99)$$

where lake area A is given in hectares (ha) and $\text{sqrt}A$ is the square root of A . As might be expected, a unit change in lake level (1 m, for example) would produce a larger change in area and volume for a large lake than a small lake. Hence the functions were built based on lake size, represented here by lake area, of which we took the square root to get a simpler linear metric. To use the functions, multiply the change factor by a selected change in lake level (ΔH , in meters). The result is the change in area or volume resulting from that change in lake level. Volume is returned in units of hectare-meters (ha-m), which is equivalent to a 1-m thick slice covering 1 ha (or 10,000 m³). These units happen to be what the SWAT model uses; the ha-m unit is conceptually similar to acre-feet.

Each lake has a unique range of lake-level changes, based on catchment topography and outlet (threshold) configuration (if the lake has an outlet). However, for simplicity we assumed that 1 m was the maximum rise of lake level over the outlet threshold during snowmelt or stormflow events. Further we assumed each lake was approximately at the mid-point of this range as reported, as a starting point. So for each lake, the principal (threshold) area was calculated as the starting area *minus* 0.5 m times the area change factor; likewise the principal volume was calculated as the starting volume *minus* 0.5 m times the volume change factor. The emergency areas and volumes were calculated by *adding* the same changes to the reported (starting) values (Table 3). The percentage of lake area and volume that changes with a unit change in lake level is inversely proportional to lake area. That is, according to these relations, for a 1-m change in lake level, the *relative* change in lake area and volume would be much greater for a small lake than for a large lake. For the 45 lakes explored in the St. Croix basin, a 1-m rise in lake level would increase lake area by an average of 24% and increase lake volume by an average of 22%. While these relations are certainly inexact, they are also simple to use and provide an objective measure where no site-specific data are otherwise available.

Lakes are natural sediment traps, and SWAT assumes that all sediment above a certain suspended sediment concentration will settle and not be passed downstream. This concentration, called the NSED parameter in SWAT, is the maximum concentration of sediment to be passed downstream and is generally larger in small shallow lakes where turbulent mixing can maintain sediment in suspension. Hence, NSED should be inversely proportional to lake depth. In modeling practice, however, NSED is a calibration parameter that is adjusted to whatever value helps the model match the selected monitoring data set, commonly the load of total suspended sediment (TSS). For the construction of the St. Croix SWAT model, we began by setting NSED inversely proportional to the mean lake depth D according to the following equation:

$$\text{NSED} = 100 * D^{-2}$$

This relation reasonably fit the NSED values determined in a previous study that constructed a

SWAT model for the Willow River, another tributary to the St. Croix (Almendinger and Murphy, 2007). For the lakes in the St. Croix basin, the equation gave initial values of NSED ranging from 1 to 88 mg/L, with a median of 6 mg/L. Further work needs to be done to test whether these sediment trapping parameters are realistic; i.e., are the modeled lake-sediment accumulation rates realistic? During calibration, these initial estimates of NSED were adjusted as needed to improve the model fit.

Likewise, lakes also trap some of the phosphorus load in their sediments. SWAT simulates the loss of phosphorus to lake sediments by using an apparent settling velocity V_s (called PSETLR in SWAT, with units of m/yr), in accordance with a well-used algorithm originally put forth by Vollenweider (1975, 1976). The V_s is not a true settling velocity for particles, but a lumped, black-box parameter that represents the net result of all processes that trap (or release) phosphorus to (or from) lake sediments. Because these many processes are not explicitly addressed and unlikely to be perfectly covariant, values for V_s reported in the literature vary widely. For natural lakes V_s ranges from about 1 to 100 m/yr but more frequently falls between 5 to 20 m/yr (Chapra, 1997). Reservoirs tend to have higher values (Panuska and Robertson, 1999) and wider ranges, from -90 to 269 m/yr in one study (Higgins and Kim, 1981).

SWAT allows the user to set two values for V_s , PSETLR1 for the runoff-prone part of the year and PSETLR2 for the rest of the year. These values were initially parameterized as follows. For the part of the year when runoff events are less common and phosphorus delivery to lakes is less likely to be influenced by coincident sediment loads, we assigned all lakes a constant value of 10 m/yr as the V_s (PSETLR2 in this case), to match representative rates for natural lakes given in the literature. For the spring snowmelt and rain period (March-May) when sediment delivery is likely to be the greatest, we developed a simple but untested relation to estimate V_s (PSETLR1 in this case) from available lake morphometric data. The V_s parameter is defined as the product of the mean depth (D) of the lake times a rate constant (s) (Vollenweider, 1975). Brett and Benjamin (2008) demonstrate that the rate constant s is inversely proportional to the square root of hydraulic residence time. If we assume that residence time is directly proportional to lake volume (V), then s is likewise inversely proportional to the square root of V . Multiplying both sides of the proportionality by D , dividing V by D to obtain lake area (A), and rearranging results in the following expression:

$$V_s = D * s = k * \text{SQRT}(D/A) = \text{PSETLR1}$$

where V_s (or PSETLR1) is the apparent settling velocity of phosphorus in m/yr; D is mean depth of the lake in m; A is lake area in ha; and k is a constant of proportionality to be determined by fitting the equation to available data, if any. We set the value of k to 500 so that the estimated PSETLR1 values then ranged from 25 to 92 m/yr, with a median of 47 m/yr. These values tend to be high for natural lakes but fit within the range for reservoirs, without reaching extreme values. This method appears to be a reasonable way to set provisional V_s values that may prove useful when no calibration data exist. More work needs to be done to better predict V_s values based on available data. As with the sediment data, these initial parameter estimates for phosphorus settling were adjusted as needed during the calibration process.

Landscape Depressions: SWAT Ponds and Wetlands

Depressions on the landscape -- of all sizes at all scales -- can have a large influence on runoff and infiltration processes, in turn influencing transport of sediment and nutrients. However, few modeling studies acknowledge the problem and fewer still attempt to quantitatively incorporate an appropriate configuration to simulate the influence of these depressions. SWAT allows for depressional storage on the landscape with two very similar features called Ponds and Wetlands. Each model subbasin may have one Pond and one Wetland, and the user specifies what fraction of each subbasin's water yield (overland and subsurface flows) is routed to the Pond or Wetland. Ponds and Wetlands can trap sediment and nutrients at user-specified rates and then pass water, sediment, and nutrients downgradient to the receiving reach. The only difference between Ponds and Wetlands in SWAT is that Ponds allow for slightly more user-control of surficial outflow, much like that from a reservoir.

In the St. Croix SWAT model, we used the NLCD 2001 data set to identify all open-water and wetland (wooded and emergent) grid cells (excluding those open-water grid cells representing the 39 reservoirs). For each subbasin, the Pond principal area was set to the aggregate open-water area, and the Wetland normal area was set to the aggregate wetland area. Each Pond was assumed to have a mean depth of 1.5 m, and each Wetland 1 m. Emergency (maximum) volumes and areas were set to 1.3 times the principal (normal) values, and drainage areas set to 3.3 times the principal surface areas. These Pond and Wetland geometries were determined as averages from a more detailed analysis of depressions and drainage areas in the Sunrise River watershed, one of the principal tributaries to the St. Croix (Almendinger and Ulrich 2010). However, in reality these parameters are probably highly variable across the basin, and the St. Croix model could be greatly improved by development of an objective algorithm to systematically identify

Table 4. Summary of Pond and Wetland areas in the subbasins of the St. Croix SWAT model.

Statistic	Subbasin	<i>Percent of subbasin occupied by:</i>			
	Area (km ²)	Pond	Wetland	Pond Catchment	Wetland Catchment
Mean	47.70	2.6%	11.5%	8.3%	36.9%
Median	39.59	1.6%	9.4%	5.1%	30.9%
Min	0.01	0.0%	0.0%	0.0%	0.0%
Max	205.80	17.0%	52.6%	56.1%	100.0%

NOTES: Data are for 419 subbasins. "Ponds" refers to open water and "Wetlands" to emergent and woody wetlands in the 2001 NLCD data set. Catchments were calculated as 3.3 times the Pond and Wetland areas, a factor estimated for the Sunrise River watershed, a tributary in the southwest quadrant of the St. Croix basin.

depressional drainage areas and their relation to existing surface-water bodies (ponds and wetlands). These Ponds and Wetlands influenced a substantial fraction of the St. Croix basin: on average, about 8% of each subbasin drained to a Pond, and 37% to a Wetland (Table 4). That is, runoff from nearly half of the basin (about 45%) was processed by Ponds or Wetlands before being delivered to the channel network.

Both Ponds and Wetlands were allowed to spill at a rate of one-tenth their volume above principal each day (i.e., the NDTARG parameter was set to 10 days). At volumes below principal, no surface outflow occurs. Evaporation was set equal to the potential evapotranspiration (PET) for each day (rather than the default of $0.6 \times \text{PET}$). Seepage from such surface-water bodies can be a substantial portion of groundwater recharge. In prior releases of SWAT, seepage from Ponds and Wetlands was lost from the system. Presumably in the current release of SWAT, this seepage is quantified and contributes to the subbasin reach as baseflow from groundwater discharge. Water-quality parameters for Ponds and Wetlands were initially set similarly as for Reservoirs but modified as needed during calibration. Again, further work needs to be done to better parameterize these features objectively.

Soils

Two soil spatial datasets were available for the St. Croix basin, the State Soil Geographic Database (STATSGO) and the Soil Survey Geographic database (SSURGO). Both datasets were produced by the NRCS (Natural Resources Conservation Service) with STATSGO available as statewide spatial datasets and SSURGO distributed by county (NRCS 2008a, 2008b). The SSURGO data set is much more detailed and thus in theory should improve model accuracy for selected localities within the basin; however, the trade-off is that the added detail reduces the model run efficiency for large modeled areas (Geza and McCray, 2008). Given the large size of the St. Croix basin, we chose to go with the coarser STATSGO soils data to make model runs tractable.

In SWAT, the principal soil parameter that affects the rainfall-runoff process is the hydrologic soil group (HSG), which ranges from coarse well-drained soils (HSG type A) to fine poorly-drained soils (HSG type D). According to the STATSGO data set, about 75% of the basin area has well drained soils, of either HSG type A (29%) or type B (46%). Type A soils have low runoff potential, with commonly $>90\%$ sand and $<10\%$ clay. Type B soils have moderately low runoff potential, with 50-90% sand, 10-20% clay, and loamy sand or sandy loam textures. About 24% of the area has HSG type C soils, with moderately high runoff potential, $<50\%$ sand, 20-40% clay, and a variety of loamy textures. Only a small fraction (1%) are designated as type D soils, with high runoff potential and $>40\%$ clay (see NRCS 2007 for HSG descriptions). The coarse (A and B) soils were developed on pitted glacial outwash plains or shallow lake plains in the central part of the basin, while the finer (C) soils correspond to terminal or ground moraines in the northern third and extreme southeast part of the basin (see Figure 6) (Hadley and Pelham, 1976;

Cummins and Grigal, 1981; Hobbs and Goebel, 1982). Where the landforms are flat enough to limit drainage, water tables can be high and peatlands can form the surface soils, despite coarse underlying deposits.




Figure 6. Hydrologic soil groups in the St. Croix basin, based on the STATSGO data set.

Land Cover: Agricultural Land

Cropland Area

At least five post-2000 spatial data sets were considered as input to the SWAT model (Table 1). We chose to begin with the Crop Data Layer (CDL) for 2007 because it appeared to be broadly representative of land use during the 2000-09 decade (the “2000s”), meaning the present-day conditions for the purposes of this report (Figure 3b). The CDL data sets have the advantage of identifying the principal crops individually, whereas the National Land Cover Dataset (NLCD) layers identify only generic cropland.

To more fully characterize the area of tilled cropland, we compared the available spatial data sets with tabular data. Tilled cropland here refers to corn, soybeans, small grains, and alfalfa; pasture and other untilled grassland were excluded. The spatial data included the CDL layers from 2006-10 (NASS 2011), and the tabular data were annual harvested areas for 2000-08 compiled by the National Agricultural Statistics Service for each county (NASS 2009), scaled by the percent of each county within the St. Croix basin. The area of tilled cropland varied from year to year in the CDL data sets, ranging from 1182 km² in 2008 to 2199 km² in 2006, with an average of 1699 km². In contrast, the area of tilled cropland in the NASS tabular data sets was always larger than that in the spatial data, with a 2000-08 average area of 2264 km². We hypothesize that the spatial data sets may systematically underestimate the true area of tilled cropland because some areas cropped as hay (and that are part of a tillage rotation) may be incorrectly categorized as grassland or other non-tilled herbaceous vegetation. Consequently, we chose to use the 2264 km² value from the NASS tabular data set as the more representative area of cropland during the 2000s for model construction. Of the tilled cropland in the basin, 33% was occupied by corn-grain, 9% by corn-silage, 22% by soybeans, 5% by small grains, and 31% by alfalfa (Table 5, bottom).

General Crop Rotations in Basin Quadrants

Cropland areas and yields are not evenly distributed across a basin as large as that of the St. Croix because of differences in climate, soils, and culture. For example, the growing season is shorter in the northern half of the basin, resulting in smaller crop yields, and dairy farming has been traditionally more important in Wisconsin than in Minnesota. To account for these spatial differences, we divided the St. Croix basin into approximate quadrants (Figure 7), by which crop areas and yields were stratified (Table 5). Yields were converted from the NASS-reported units (bushels per acre) to SWAT-consistent units (metric tons dry biomass per hectare) with the conversion factors given in Table 6.

The relative cropland areas in each quadrant formed the basis for identifying the basic crop rotations in the St. Croix basin. A crop rotation is a sequence of crops planted in the same field, commonly over several years. For example, a 2-year corn-soybean rotation would

Table 5. Crop areas and yields by quadrant and county in the St. Croix basin, 2000-08.

County	Corn-grain		Corn-silage		Soybeans		Small grains		Alfalfa		Hay, other	
	Area (km ²)	Yield (t/ha)	Area (km ²)	Yield (t/ha)	Area (km ²)	Yield (t/ha)	Area (km ²)	Yield (t/ha)	Area (km ²)	Yield (t/ha)	Area (km ²)	Yield (t/ha)
Northwest Quadrant (NW)												
MIN-Aitkin	0.83	4.25	0.54	8.32	2.26	1.88	2.24	1.71	4.61	4.67	26.42	3.36
MIN-Carlton	0.46	4.94	1.76	7.98	n/a	n/a	0.58	1.61	16.65	4.66	40.46	3.33
MIN-Kanabec	44.08	5.20	12.63	9.50	36.27	1.56	13.97	2.10	50.33	6.19	80.10	3.92
MIN-Mille Lacs	10.57	5.60	2.79	10.50	8.17	1.79	1.52	1.98	7.36	6.6	10.50	4.14
MIN-Pine	44.40	5.63	27.78	9.70	37.89	1.87	21.22	1.91	74.35	6.67	149.73	3.88
Total area & average yield	100.33	5.12	45.49	9.20	84.58	1.77	39.55	1.86	153.30	5.76	307.21	3.73
Percent of tilled area	23.7%		10.7%		20.0%		9.3%		36.2%			
Southwest Quadrant (SW)												
MIN-Anoka	3.64	5.42	0.29	8.50	2.21	1.52	0.73	2.21	2.15	5.48	1.42	3.66
MIN-Chisago	88.22	6.12	11.70	11.11	94.68	1.81	3.50	1.60	46.67	6.15	16.42	4.08
MIN-Isanti	22.63	5.75	0.91	9.53	21.46	1.52	1.80	1.64	8.51	5.52	2.78	3.66
MIN-Ramsey	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
MIN-Washington	51.67	7.38	2.91	10.94	38.27	2.09	4.15	1.95	27.04	6.17	10.30	4.13
Total area & average yield	166.16	6.17	15.81	10.02	156.62	1.74	10.19	1.85	84.37	5.83	30.92	3.88
Percent of tilled area	38.4%		3.7%		36.2%		2.4%		19.5%			
Northeast Quadrant (NE)												
WI-Bayfield	n/a	n/a	n/a	n/a	n/a	n/a	1.25	2.10	9.26	4.07	16.41	3.09
WI-Burnett	40.24	5.23	15.31	10.29	21.60	1.70	5.93	2.16	51.01	4.50	20.16	3.04
WI-Douglas	n/a	n/a	n/a	n/a	n/a	n/a	1.04	1.96	14.39	3.95	30.46	2.86
WI-Sawyer	1.44	4.60	0.83	8.37	0.42	1.45	0.27	2.01	2.73	4.65	2.82	3.47
WI-Washburn	26.11	4.93	13.18	9.33	11.20	1.55	4.92	2.50	38.83	4.36	29.59	3.05
Total area & average yield	67.79	4.92	29.32	9.33	33.22	1.57	13.40	2.15	116.22	4.30	99.44	3.10
Percent of tilled area	26.1%		11.3%		12.8%		5.2%		44.7%			
Southeast Quadrant (SE)												
WI-Barron	15.00	6.16	4.87	11.61	6.23	2.05	1.84	2.40	15.39	5.04	3.43	3.61
WI-Pierce	26.49	7.52	4.15	13.56	11.67	2.28	2.95	2.68	16.35	5.74	1.25	3.76
WI-Polk	190.40	6.20	49.27	11.60	93.42	1.86	20.24	2.25	181.52	5.00	44.46	3.99
WI-St. Croix	184.99	6.66	49.44	13.67	105.45	2.04	23.46	2.61	144.66	5.51	20.08	4.07
Total area & average yield	416.88	6.63	107.74	12.61	216.78	2.06	48.49	2.48	357.92	5.33	69.23	3.85
Percent of tilled area	36.3%		9.4%		18.9%		4.2%		31.2%			
Whole Basin												
Total area & average yield	751	5.72	198	10.28	491	1.80	112	2.08	712	5.27	507	3.62
Percent of tilled area	33.2%		8.8%		21.7%		4.9%		31.4%			
Total tilled area in basin = 2264 km ²												

NOTES: County-wide data for 2000-08 from U.S. Department of Agriculture (USDA) National Agricultural Statistics Service (NASS) web site (NASS 2009). Areas for each crop have been scaled by the fractional land area of each county within the St. Croix basin. Crop yields refer to dry biomass per unit area. See conversion table for factors to convert reported yields to dry biomass.




Figure 7. St. Croix quadrants for crop and livestock characterization.

consist of corn and soybeans being planted in alternate years. In SWAT, crop rotations are applied to cropland HRUs, staggered in time so that they reproduce the reported relative areas of each crop on the landscape, year after year. To simplify crop rotations we added the area of small grains to that of soybeans. Rotations including corn-grain, corn-silage, soybeans, and alfalfa were constructed for each of the four quadrants according to the relative areas of each crop given in Table 5. Two simple crop rotations could adequately reproduce the NASS-reported crop areas: a 2-yr corn-grain/soybean rotation (CS), and a 6-yr corn-grain/corn-silage/alfalfa (4 yr) rotation (CA). The areas of these two rotations

were nearly equal within the basin as a whole: 52% of cropland was CS (1175 km²) and 48% was CA (1089 km²). However, the rotations were not distributed evenly across the basin; i.e., the four quadrants of the basin had different proportions of these two rotations (Table 7; see data for 2000s).

Table 6. Factors to convert crop yields as commonly reported in the USA to metric dry biomass units.

Crop	Standard Densities (lb/bushel)	Common Reporting Units in USA	Moisture Content (%)	Conversion Factor to Dry Biomass Yield (metT/ha)
Barley	48	bushels/acre	14.5%	0.0461
Corn	56	bushels/acre	15.5%	0.0531
Oats	32	bushels/acre	14.0%	0.0309
Wheat	60	bushels/acre	13.5%	0.0583
Soybeans	60	bushels/acre	13.0%	0.0586
Rye	56	bushels/acre	14.0%	0.0541
Sunflower	100	bushels/acre	10.0%	0.1010
Flax	56	bushels/acre	9.0%	0.0572
Sorghum	55	bushels/acre	14.0%	0.0531
Corn silage	na	short tons/acre, moist	65.0%	0.3182
Alfalfa, hay	na	short tons/acre, dry	0.0%	0.9091

NOTES: Common grain densities and moisture contents obtained from North Dakota State University (NDSU) Agriculture and University Extension, 1987, Equivalent Weights of Grain and Oilseeds, Publication AE-945, 3 pp. Corn silage (optimal) moisture content from Schroeder, J.W., 2004, Corn silage management, North Dakota State University (NDSU) Agriculture and University Extension, Publication AS-1253.

Spatial Distribution of Rotations within Quadrants

To identify the spatial location of different crop rotations, we overlaid the five CDL data sets from 2006-10 and compared how crops changed from year to year. (In ArcGIS terms, the grids were combined to form a grid identifying all unique sequences of crops.) This process demonstrated significant annual variability in crop locations or errors in identification of crops. The *intersection* of these five data sets identified grid cells that were cropland *every* year from 2006-10 and totaled only 647 km², whereas the *union* of the data sets identified grid cells that were cropland in *any* year and totaled 4371 km². Neither value is close to any other reported value for cropland area during this time: the intersection underestimates actual cropland area, and the union overestimates it. Further, the divergence between the intersection and union areas increases as data sets are added. Thus, while such combined grids may be useful for identifying the general location and sequence of principal crops, they should not be used to assess the total area of cropland. Again, for total cropland area we adhered to the 2000-08 average area of 2264 km² derived from the NASS tabular data.

To distribute the rotations spatially we then began with the union of all CDL cropland from 2006-10 because it included all possible land that was cropland (4371 km²), out of which we chose 2264 km² that represented the most likely location of actual cropland in a “typical” year during the 2000s. Each grid-cell category of the CDL-cropland union was reclassified according

Table 7. Cropland rotations by quadrant in the St. Croix SWAT model.

Quadrant	1990s: Percent of Cropland	2000s: Percent of Cropland	Rotation
Minnesota			
Northwest Quadrant (NW)	35% 65%	53% 47%	Cg1-S1 Cg1-Cs1-A4
Southwest Quadrant (SW)	65% 35%	76% 24%	Cg1-S1 Cg1-Cs1-A4
Wisconsin			
Northeast Quadrant (NE)	15% 85%	36% 64%	Cg1-S1 Cg1-Cs1-A4
Southeast Quadrant (SE)	30% 70%	46% 54%	Cg1-S1 Cg1-Cs1-A4
St. Croix Basin			
	36% 64%	52% 48%	Cg1-S1 Cg1-Cs1-A4
Total cropland area:	1990s:	2000s:	
-- in km ²	2329 km ²	2264 km ²	
-- as % of basin	11.7%	11.3%	

NOTES:

Cg1-S1 = 1-yr Corn-grain / 1-yr Soybeans

Cg1-Cs1-A4 = 1-yr Corn-grain / 1-yr Corn-silage / 4-yr Alfalfa

Northwest quadrant includes Aitkin, Carlton, Kanbec, Mille Lacs, and Pine counties.

Southwest quadrant includes Anoka, Chisago, Isanti, Ramsey, and Washington counties.

Northeast quadrant includes Bayfield, Burnett, Douglas, Sawyer, and Washburn counties.

Southeast quadrant includes Barron, Pierce, Polk, and St. Croix counties.

to (a) its quadrant and (b) whether its 5-yr crop sequence (from 2006-10) could be best represented by the CS or the CA rotation. To determine the rotations within each quadrant, grid-cell categories were ranked according to years (out of 5) that were corn-grain and soybeans and assigned the CS rotation down to the rank where the cumulative targeted area for CS in that quadrant was achieved. Likewise, grid-cell categories were ranked according to years of corn-silage, alfalfa, and grass and assigned the CA rotation, until the target area for CA in that quadrant was achieved. The

remaining grid-cell categories (commonly grassland for three or four years out of five) in each quadrant were assigned to be pasture, under the assumption that land that is occasionally cropped, or mis-identified as cropland because of proximity, is more likely to be pasture than are other grasslands scattered across the basin. The three basic rotations (CS, CA, and pasture) within each of four quadrants resulted in 12 total rotation identifiers. The final CDL-union grid, with all cells reclassified according to these 12 possible rotations, was then overlaid (“mosaicked”) back onto the original CDL-2007 grid to form the land-use grid for use by the ArcSWAT interface. In this way, the total cropland area, the relative areas among crops, the temporal rotation of crops, and their spatial distribution across the basin were faithfully reproduced in the model.

Land Cover: Developed Land

The total area of developed land in the St. Croix basin is not large, averaging about 5% of the basin area for the 2001-07 data sets examined (Table 1). Here, by “developed” we mean land with large enough impervious surfaces to be identified as such in the spatial land-use data sets. Roads, cities, and villages would be included, but rural residential areas with low densities would be excluded. In the CDL 2007 data set, the template for land-use input to the model, developed land totaled 5.9%, the sum of NLCD land-cover types 121-124 (Developed/Open Space, Developed/Low Intensity, Developed/Medium Intensity, and Developed/High Intensity). These types were reclassified to the SWAT categories: type 121 to URLD (urban low density), type 122 to URML (urban medium/low density), and types 123-4 to URHD (urban high density). These three categories were chosen because they appeared to correspond to useful distinctions on the ground and for modeling purposes. In the CDL 2007 data set, URHD covered 0.3% of the basin and appeared to correspond to the core of urban areas, surrounded by a fringe of URML that covered 0.9% of the basin. These categories constitute the commercial, industrial, and high-density residential areas of cities in the St. Croix basin. URLD covered 4.7% of the basin and appeared to correspond mostly to the background, section-line road network, although some could be attributed to urban fringes. For our purposes, we considered that the URHD and URML units were where urban growth has occurred in proportion to their population growth, whereas the URLD unit has been established for many years and would increase only slightly with population growth.

The population in these land covers may be roughly estimated, given some assumptions about housing density and household size. We used estimates of household size and density as developed for the Sunrise River watershed, a tributary to the St. Croix in eastern Minnesota (Almendinger and Ulrich, 2012), and assumed they were broadly representative for the St. Croix basin. First, assume the 2005 population (about 465,000; U.S. Census Bureau) is representative for the 2000s period. About 162,000 people, or 35% of the population, live in the URML land-use type, if it represents urban single-family residential areas with a housing density of 3.7 units/ha (1.5 units/acre) with 2.92 persons per household. About 80,000 people, or 17%, live in URHD

land-use type, if 22% of it is residential (78% being commercial / industrial) with 25 units/ha (10 units/acre) and 2.92 persons per household. The remaining people, about 224,000 or 48%, apparently live in rural residential settings.

Hydrologic Response Unit (HRU) Determination

As explained earlier, HRUs are determined with the ArcSWAT interface by intersecting spatially referenced (GIS) layers of land cover, soil type, and slope class. Configuration of land cover and soil type data sets are discussed above. During the DEM processing to delineate the watershed (channel hydrography and subbasin boundaries), the ArcSWAT interface also generates a grid of land-slope values that can be divided into user-selected categories and included as a criterion in defining HRUs. We chose two land-slope categories, 0-10% slope, and >10% slope (percent slope = $100 \cdot \tan$ of the angle from horizontal).

To avoid undue model complexity, the user sets thresholds for the percent of subbasin area covered by each category in these data layers so that only the dominant categories are included during HRU determination. We chose thresholds of 5% for land use, 10% for soils, and 5% for slope. For example, a land use occupying less than 5% of a subbasin area will be ignored in constructing HRUs for that subbasin. Similarly, soil categories covering less than 10% of the subbasin area, and slope classes covering less than 5%, were ignored in HRU construction. Given these thresholds, ArcSWAT determined a total of 3010 HRUs within the 419 subbasins, or about seven to eight HRUs per subbasin.

We note that these threshold exemptions during HRU construction tend to make small categories of land use, soil, or slope even smaller in the model than in reality. Conversely, dominant categories are expanded. Thus for small land-use categories of interest – such as urban land in the St. Croix basin – it was important to keep the land-use exemption threshold rather low. The 5% threshold was adequate for most land uses, but urban lands were reduced to only 1.5% of the basin area, rather than the 5.9% shown in the CDL 2007 layer. In particular, URHD was reduced from 0.3% to 0.1%, and URML was reduced from 0.9% to 0.3%. To compensate, we expanded all URHD and URML HRUs such that their areal coverage matched the original values. This procedure required simultaneous reductions of grassland or forest HRUs in the same subbasin. However, most of the under-representation of developed land was from URLD being too low in rural subbasins to exceed the threshold for inclusion, such that HRUs for this type were not created in these rural subbasins. And, because such HRUs were not created, the URLD type could not be expanded back up to original, target values.

Land Use: Agricultural Practices

Manure Quantities

The location, timing, and spreading rate (mass per area) of manure applications are important influences on nonpoint-source contributions of nutrients to receiving waters. We compiled livestock numbers for 2000-09 data for each county in the St. Croix basin (NASS, 2010). Livestock included dairy cows, beef cattle, hogs, sheep, and poultry. Manure from wildlife was not considered. A few herds of bison and red deer are kept in Chisago County (C. Mell, Chisago County Soil and Water Conservation District, personal communication 2009). If a livestock species was not reported at all, we assumed its numbers were negligible in that county. Missing years of livestock numbers were interpolated, assuming data existed before and after the missing year. Livestock numbers were adjusted by the fractional area of each county within the St. Croix basin.

For constructing the SWAT model, we wanted to keep agricultural practices as representative as possible without undue complexity. To that end we decided to focus on only three major livestock types: beef cattle, dairy cows, and horses. While horses were calculated to produce only about 5% of the current total phosphorus load in manure in the basin, their numbers seem likely to increase in the future. To account for manure production by other livestock types, we created equivalency tables between different animals based on their phosphorus production (Tables 8 and 9) and converted the excluded livestock types to one of the three included types. Based on the nature of the animal and how its manure is ultimately spread, we chose to convert bison to beef cattle equivalents, hogs to dairy cow equivalents, and sheep and red deer to horse equivalents. Thus, while not all animal types were explicitly represented in the model, the total load of phosphorus from manure was preserved. Typical manure characteristics of dairy cows, beef cattle, and horses are given in Table 10, which were used to calculate manure quantities and nutrient loads from reported livestock populations.

For 2000-09, livestock numbers were dominated by dairy cows, with nearly 153,000 animal units in the basin producing about 2.4 million short tons of manure annually, of which 2,620 short tons is phosphorus. (One short ton = 2000 pounds, and one metric ton = 2200 pounds = 1.1 short tons. We use short tons here because agronomists in the USA commonly use these units with regard to manure.) By far, most dairy cows are in the southeast part of the basin, especially in Polk and St. Croix counties in Wisconsin (Figure 8a and Table 11). Beef cattle numbered about 51,000 animal units, producing about 540,000 short tons of manure containing 860 short tons of phosphorus (Table 12), essentially all on the Minnesota side of the basin (Figure 8b). Horses totaled about 16,000 animal units, producing about 150,000 short tons of manure containing 210 short tons of phosphorus (Table 13) and were more common in the southern half of the basin (Figure 8c). In summary, livestock generated a total of 3,690 short tons (3,355 metT) of phosphorus: 71% from dairy cows, 23% from beef cattle, and 6% from horses.

Manure can be applied by grazing in pastures or by mechanical means in crop or hay

Table 8. Equivalent animal numbers, in terms of daily phosphorus production in manure.

<i>One of these animals ...</i>	<i>... equals this many of these animals:</i>										<i>... based on these data:</i>	
	Dairy cow	Beef cow	Hog	Sheep	Horse	Bison	Red deer	Chicken	Turkey	(lbs P/day/ 1000-lb animal unit)	(typical wt, lbs)	
Dairy cow	1	1.149	4.029	14.586	1.787	1.254	13.260	105.750	19.705	0.094	1350	
Beef cow	0.870	1	3.505	12.690	1.555	1.091	11.536	92.000	17.143	0.092	1200	
Hog	0.248	0.285	1	3.621	0.444	0.311	3.292	26.250	4.891	0.18	175	
Sheep	0.069	0.079	0.276	1	0.123	0.086	0.909	7.250	1.351	0.087	100	
Horse	0.559	0.643	2.254	8.161	1	0.702	7.419	59.167	11.025	0.071	1000	
Bison	0.797	0.917	3.213	11.632	1.425	1	10.575	84.333	15.714	0.092	1100	
Red deer	0.075	0.087	0.304	1.100	0.135	0.095	1	7.975	1.486	0.087	110	
Chicken (layer)	0.009	0.011	0.038	0.138	0.017	0.012	0.125	1	0.186	0.3	4	
Turkey	0.051	0.058	0.204	0.740	0.091	0.064	0.673	5.367	1	0.23	28	

Notes: All animals assumed to be adults.

Table 9. Equivalent animal unit numbers, in terms of daily phosphorus production in manure.

<i>One of these animal units ...</i>	<i>... equals this many of these animal units:</i>										<i>... based on these data:</i>	
	Dairy cow	Beef cow	Hog	Sheep	Horse	Bison	Red deer	Chicken	Turkey	(lbs P/day/ 1000-lb animal unit)	(typical wt, lbs)	
Dairy cow	1	1.022	0.522	1.080	1.324	1.022	1.080	0.313	0.409	0.094	1350	
Beef cow	0.979	1	0.511	1.057	1.296	1.000	1.057	0.307	0.400	0.092	1200	
Hog	1.915	1.957	1	2.069	2.535	1.957	2.069	0.600	0.783	0.18	175	
Sheep	0.926	0.946	0.483	1	1.225	0.946	1.000	0.290	0.378	0.087	100	
Horse	0.755	0.772	0.394	0.816	1	0.772	0.816	0.237	0.309	0.071	1000	
Bison	0.979	1.000	0.511	1.057	1.296	1	1.057	0.307	0.400	0.092	1100	
Red deer	0.926	0.946	0.483	1.000	1.225	0.946	1	0.290	0.378	0.087	110	
Chicken (layer)	3.191	3.261	1.667	3.448	4.225	3.261	3.448	1	1.304	0.3	4	
Turkey	2.447	2.500	1.278	2.644	3.239	2.500	2.644	0.767	1	0.23	28	

Table 10. Typical manure characteristics for livestock in the St. Croix SWAT model.

Livestock Type	Raw Manure (lbs/day/1000-lb animal unit)	Total Solids		
		(Dry Wt) (lbs/day/1000-lb animal unit)	Nitrogen (lbs/day/1000-lb animal unit)	Phosphorus (lbs/day/1000-lb animal unit)
Dairy cows	86	12	0.45	0.094
Beef cattle	58	8.5	0.34	0.092
Horses	51	15	0.3	0.071

Abbreviations:

Dry Wt, dry weight; lbs, pounds

Notes:

Manure characteristics obtained from ASAE (1998), as cited by Arnold et al. (2011).




Figure 8. Animal unit densities of (a) dairy cows, (b) beef cattle, and (c) horses in the St. Croix basin, 2000-09.

Table 11. Dairy cow manure production and associated nutrient loads for portions of counties in the St. Croix basin, 2000-09.

DAIRY COWS Quadrant / County	(a) Manure production			(b) Nutrients from manure		
	Animal Units	Raw Manure (short T/yr)	Total Solids (Dry Wt) (metric T/yr)	Percent of Total (%)	Nitrogen (short T/yr)	Phosphorus (short T/yr)
Northwest Quadrant (NW)						
MN-Aitkin	283	4,436	563	0.2%	23	5
MN-Carlton	1,518	23,823	3,022	1.0%	125	26
MN-Kanabec	6,819	107,029	13,577	4.5%	560	117
MN-Mille Lacs	1,611	25,280	3,207	1.1%	132	28
MN-Pine	12,623	198,111	25,130	8.3%	1,037	217
<i>Totals</i>	<i>22,853</i>	<i>358,679</i>	<i>45,498</i>	<i>14.9%</i>	<i>1,877</i>	<i>392</i>
Southwest Quadrant (SW)						
MN-Anoka	195	3,056	388	0.1%	16	3
MN-Chisago	6,746	105,881	13,431	4.4%	554	116
MN-Isanti	870	13,657	1,732	0.6%	71	15
MN-Ramsey	1	19	2	0.0%	0	0
MN-Washington	1,850	29,040	3,684	1.2%	152	32
<i>Totals</i>	<i>9,662</i>	<i>151,653</i>	<i>19,237</i>	<i>6.3%</i>	<i>794</i>	<i>166</i>
Northeast Quadrant (NE)						
WI-Bayfield	1,731	27,168	3,446	1.1%	142	30
WI-Burnett	10,294	161,564	20,494	6.7%	845	177
WI-Douglas	2,445	38,373	4,868	1.6%	201	42
WI-Sawyer	764	11,987	1,521	0.5%	63	13
WI-Washburn	8,179	128,368	16,283	5.4%	672	140
<i>Totals</i>	<i>23,413</i>	<i>367,462</i>	<i>46,612</i>	<i>15.3%</i>	<i>1,923</i>	<i>402</i>
Southeast Quadrant (SE)						
WI-Barron	4,109	64,491	8,181	2.7%	337	70
WI-Pierce	5,150	80,824	10,252	3.4%	423	88
WI-Polk	44,889	704,535	89,370	29.4%	3,687	770
WI-St. Croix	42,796	671,685	85,203	28.0%	3,515	734
<i>Totals</i>	<i>96,944</i>	<i>1,521,535</i>	<i>193,007</i>	<i>63.4%</i>	<i>7,962</i>	<i>1,663</i>
Basin totals	152,872	2,399,328	304,355	100.0%	12,555	2,623

Abbreviations:

Dry Wt, dry weight; lbs, pounds; short T, short ton = 2000 lb; metric T, metric ton = 1000 kilograms; n/a, not applicable

Notes:

See Table 10 for manure characteristics for each livestock type. Livestock populations obtained from the National Agricultural Statistics Service (NASS, 2010). Calves apportioned to dairy and beef according to the proportions of adult cattle.

Dairy cow AUs here include AU-equivalents of hogs; see Table 9 for conversion factors.

Table 12. Beef cattle manure production and associated nutrient loads for portions of counties in the St. Croix basin, 2000-09.

BEEF CATTLE Quadrant / County	(a) Manure production				(b) Nutrients from manure	
	Animal Units	Raw Manure (short T/yr)	Total Solids (Dry Wt) (metric T/yr)	Percent of Total (%)	Nitrogen (short T/yr)	Phosphorus (short T/yr)
Northwest Quadrant (NW)						
MN-Aitkin	1,837	19,448	2,591	3.6%	114	31
MN-Carlton	3,051	32,293	4,302	6.0%	189	51
MN-Kanabec	15,759	166,806	22,223	30.8%	978	265
MN-Mille Lacs	1,380	14,605	1,946	2.7%	86	23
MN-Pine	18,601	196,894	26,232	36.3%	1,154	312
<i>Totals</i>	<i>40,628</i>	<i>430,046</i>	<i>57,295</i>	<i>79.4%</i>	<i>2,521</i>	<i>682</i>
Southwest Quadrant (SW)						
MN-Anoka	252	2,663	355	0.5%	16	4
MN-Chisago	6,427	68,028	9,063	12.6%	399	108
MN-Isanti	877	9,284	1,237	1.7%	54	15
MN-Ramsey	1	7	1	0.0%	0	0
MN-Washington	2,998	31,735	4,228	5.9%	186	50
<i>Totals</i>	<i>10,554</i>	<i>111,718</i>	<i>14,884</i>	<i>20.6%</i>	<i>655</i>	<i>177</i>
Northeast Quadrant (NE)						
(WI counties of Bayfield, Burnett, Douglas, Sawyer, and Washburn)						
Too few beef cattle to include						
Southeast Quadrant (SE)						
(WI counties of Barron, Pierce, Polk, and st. Croix)						
Too few beef cattle to include						
Basin totals	51,182	541,764	72,179	100.0%	3,176	859

Abbreviations:

Dry Wt, dry weight; lbs, pounds; short T, short ton = 2000 lb; metric T, metric ton = 1000 kilograms; n/a, not applicable

Notes:

See Table 10 for manure characteristics for each livestock type. Livestock populations obtained from the National Agricultural Statistics Service (NASS, 2010). Calves apportioned to dairy and beef according to the proportions of adult cattle.

Table 13. Horse manure production and associated nutrient loads for portions of counties in the St. Croix basin, 2000-09.

HORSES Quadrant / County	(a) Manure production				(b) Nutrients from manure	
	Animal Units	Raw Manure (short T/yr)	Total Solids (Dry Wt) (metric T/yr)	Percent of Total (%)	Nitrogen (short T/yr)	Phosphorus (short T/yr)
Northwest Quadrant (NW)						
MN-Aitkin	166	1,542	412	1.0%	9	2
MN-Carlton	581	5,410	1,447	3.6%	32	8
MN-Kanabec	1,676	15,600	4,171	10.3%	92	22
MN-Mille Lacs	243	2,259	604	1.5%	13	3
MN-Pine	2,775	25,826	6,905	17.1%	152	36
<i>Totals</i>	<i>5,440</i>	<i>50,637</i>	<i>13,539</i>	<i>33.5%</i>	<i>298</i>	<i>70</i>
Southwest Quadrant (SW)						
MN-Anoka	198	1,847	494	1.2%	11	3
MN-Chisago	1,677	15,607	4,173	10.3%	92	22
MN-Isanti	429	3,991	1,067	2.6%	23	6
MN-Ramsey	0	1	0	0.0%	0	0
MN-Washington	1,610	14,983	4,006	9.9%	88	21
<i>Totals</i>	<i>3,914</i>	<i>36,430</i>	<i>9,741</i>	<i>24.1%</i>	<i>214</i>	<i>51</i>
Northeast Quadrant (NE)						
WI-Bayfield	168	1,560	417	1.0%	9	2
WI-Burnett	680	6,327	1,692	4.2%	37	9
WI-Douglas	343	3,193	854	2.1%	19	4
WI-Sawyer	48	446	119	0.3%	3	1
WI-Washburn	745	6,938	1,855	4.6%	41	10
<i>Totals</i>	<i>1,984</i>	<i>18,464</i>	<i>4,937</i>	<i>12.2%</i>	<i>109</i>	<i>26</i>
Southeast Quadrant (SE)						
WI-Barron	136	1,270	339	0.8%	7	2
WI-Pierce	224	2,086	558	1.4%	12	3
WI-Polk	2,224	20,702	5,535	13.7%	122	29
WI-St. Croix	2,330	21,687	5,799	14.3%	128	30
<i>Totals</i>	<i>4,915</i>	<i>45,744</i>	<i>12,231</i>	<i>30.2%</i>	<i>269</i>	<i>64</i>
Basin totals	16,253	151,274	40,448	100.0%	890	211

Abbreviations:

Dry Wt, dry weight; lbs, pounds; short T, short ton = 2000 lb; metric T, metric ton = 1000 kilograms; n/a, not applicable

Notes:

See Table 10 for manure characteristics for each livestock type. Horse numbers taken from 2002 Census of Agriculture (USDA, 2004). Horse AUs here include AU-equivalents of sheep; see Table 9 for conversion factors.

fields. We assumed that grazing was the principal way of applying horse and beef manure. In contrast, most dairy manure was applied mechanically to crop fields, with a lesser amount spread by grazing. Details of these applications follow in the next two sections.

Pasture

Areas of pastureland reported for 2002 and 2007 (USDA, 2009) in each quadrant of the basin were averaged for input to the model. Reported pastureland included cropland, permanent, and woodland, but to avoid undue uncertainty in the model, pastured woodland was converted to a grassland-equivalent area at a ratio of 2:1 (i.e., 2 ha of woodland pasture was replaced by 1 ha of grassland pasture). The resulting area of reported pastureland in the St. Croix basin totaled 1107 km².

Two possible grazing densities were assumed: low density at 0.82 AU/ha (animal units per hectare) and medium density at 1.23 AU/ha (1 AU/3 acres and 1 AU/2 acres, respectively). In addition, 5% of the reported pastureland area was reserved for much higher manure application rates under the assumption that winter accumulation of manure was deposited (either by animals or mechanically) in a paddock or barnyard area. We think it is safe to assume that such areas exist in the basin, but we do not know their true areas or locations. Nonetheless, including such areas in the model affords us the opportunity to test their hypothetical impact. Grazing operations included parameters for biomass eaten and trampled, as well as for manure produced (Table 14). Because the number of animal units for each type of livestock was given, and because the grazing densities were made to be uniform in the model across the basin, the modeled grazed area could not be matched exactly with the reported grazed area, especially within each quadrant. Still, for the basin as a whole, modeled area grazed (1103 km²) was within 1% of the reported area (1107 km²).

Horse pastureland was assigned first. All horses were assumed to graze at the low density (0.82 AU/ha) for 169 days/yr, thereby depositing 46% of their annual manure load. For the remainder of the year, horses were assumed to be kept in a “paddock” area, presumed to be in or near a barn and set to 5% as large as the horse pastured area. The remainder of the annual manure production (54%) was applied to this area.

Table 14. Daily forage requirements and manure production for animal units (AUs) of grazing livestock.

Animal Unit	Biomass Eaten (kg/AU/d, dry wt)	Biomass Trampled (kg/AU/d, dry wt)	Manure (kg/AU/d, dry wt)	Ratio of Biomass Eaten / Manure
Beef	11.36	2.27	3.86	2.94
Dairy cow	11.36	2.27	5.45	2.08
Horse	11.36	2.27	6.82	1.67

NOTES: One animal unit = 1000 lbs, or 454.5 kg. Biomass eaten set to 2.5% bodyweight, and biomass trampled set to 0.5% bodyweight (UWEX 2002). Manure production from ASAE (1998), as cited by Arnold et al. (2011).

Beef pastureland was similarly assigned, but at a higher density of 1.23 AU/ha (1 AU / 2 acres) for 169 days/yr, thus depositing 46% of the annual manure load. This density might be a little high for many beef grazing operations, but some beef feedlot operations do not graze their cattle

much at all. The higher density seemed to be a fair compromise to cover both types of beef operations, in aggregate. As with horses, paddock areas were set at 5% of beef pastureland, and these paddocks received the remaining 54% of beef manure that presumably accumulates during the non-grazing period (196 days/yr).

Dairy pastureland was assigned at the low animal density of 0.82 AU/ha for 169 days/yr, but under the assumption that only 25% of dairy cows are pastured. A paddock area equal to 5% of the dairy pasture area received 10% of the annual manure production (as if all the cattle spent 10% of their time in this area). The rest of the dairy manure was applied to the CA (corn-alfalfa) rotation either as seasonal (spring and fall) applications or as daily-haul applications. Seasonal applications were applied only to corn fields before planting and after harvest. Daily haul applications were simulated as monthly applications to all fields (corn and alfalfa) except during the months that corn was growing. Of all the land in CA rotation, about 14% received daily-haul applications, 20% received seasonal applications, and 66% received no manure (only inorganic fertilizer).

Specific Crop Rotations

Crop rotations in SWAT are constructed by specifying not only the sequence of crops over a series of years, but also the schedule of all field operations (tillage, planting, fertilizing, and harvesting) within each year of the rotation. We assumed a simple tillage sequence for cropped lands. Generally, prior to planting corn, soybeans, or alfalfa, fields were chisel plowed in the fall or spring and disked in the spring after an initial fertilizer application. When corn followed alfalfa, the alfalfa field was moldboard plowed in the fall and disked in the spring just prior to planting corn. SWAT defaults were initially accepted for depth of tillage and mixing efficiencies for each implement, although some of these were altered during calibration. Planting and harvesting dates for each crop were kept uniform across the basin and from year to year in the model. If necessary, the model could be modified to allow for earlier planting and harvesting in the southern half of the basin or for scheduling operations by plant heat units (growing season degree days).

Crops were fertilized with inorganic fertilizer and manure applications. For corn, inorganic fertilizer was applied at a rate 216 kg/ha (192 lb/acre) nitrogen (N) and 15 kg/ha (13 lb/acre) phosphorus (P). Soybeans received a little starter fertilizer amounting to 20 kg/ha N (18 lb/acre) and 23 kg/ha P (20 lb/acre). Alfalfa did not receive inorganic fertilizer in the model. Even though potassium (K) is often applied to alfalfa, SWAT does not track K and instead assumes that it is not limiting.

Some of the CA rotations received dairy manure in addition to inorganic fertilizer. In these cases the amount of inorganic fertilizer received by corn was reduced by about half, which effectively credited some, but not all, of the additional nutrients from manure. Corn fields in CA rotations with seasonal manure applications received 15 short tons per acre (shT/acre) fresh

manure in the spring (pre-planting) and another 15 shT/acre in the fall (post-harvest), resulting in a total of 469 kg/ha N (418 lb/acre) and 90 kg/ha P (80 lb/acre). These rates are substantial; however, at least some of the N content of the fall manure application will be lost to volatilization or denitrification. All fields (corn and alfalfa) in the CA rotations with daily-haul manure applications received manure, except for the months when corn was growing, with an average annual rate of 463 kg/ha N (412 lb/acre) and 95 kg/ha P (84 lb/acre). These rates correspond to an average annual rate of spreading 36 shT/acre of fresh manure (less in years when corn restricts the months of application, and more in years of with alfalfa.)

Pastureland grazed by dairy cows, beef cattle, and horses had much lower application rates of nutrients from manure, about 19-32 kg/ha N (17-29 lb/acre) and 4-9 kg/ha P (3-8 lb/acre). However, the paddock areas, which represent small areas where winter accumulations of manure are spread, had very high application rates, about 438-744 kg/ha N (390-663 lb/acre) and 88-205 kg/ha P (78-182 lb/acre). These values correspond to a fresh-manure application rate of about 33-56 shT/acre. Horses were at the lower end of these ranges, and beef cattle at the higher end.

The basic CS and CA rotations had to be staggered into subrotations with different starting years in order to not have the entire basin change from one crop to another in the same year. For example, for the HRUs assigned to the CS rotation, half were started with corn and the other half started with soybeans, so in any subsequent year in the model run, the total areas of corn and soybeans remained about constant. Further, because curve number is related not only to crop but also (especially) to hydrologic soil group (HSG), separate subrotations also had to be created for each of the four HSGs. All possible combinations of these variables are given in Table 15, resulting in 68 possible rotations as qualified by various subrotations. Table 16 shows the areas of the base rotations plus the three CA subrotation types in the four quadrants of the basin. The details of each of these rotations are laid out in tabular form in Appendix A.

Land Use: Urban Practices

In this version of the model, urban land-use practices were not explored. SWAT default parameters were accepted for urban low-density, urban medium-low density, and urban high-density HRUs (URLD, URML, and URHD, respectively). Later use of the model to investigate urban land-use practices will likely require re-parameterization and recalibration for subbasins with significant areas of urban land.

Table 15. Description of agricultural rotations in the St. Croix SWAT model.

Base Rotation	Subrotation Qualifiers			Description
	Type	Hydrologic Soil Group	Sequence	
<i>Tilled cropland</i>				
C1-S1 (="CS")	none	A, B, C, D	a, b	Corn-Soybean rotation
Cg1-Cs1-A4 (="CA")	no manure seasonal (= "seas") daily haul (= "dh")	A, B, C, D	a, b, c	Corn-grain (1 yr), Corn-silage (1 yr), and Alfalfa (4 yr). Begin sequence a with Corn-grain, b with yr-1 alfalfa, and c with yr-3 alfalfa. Seasonal = spring and fall applications. Daily haul = monthly applications.
<i>Pasture and paddocks</i>				
Dairy_Pasture (="DPAST")	none	A, B, C, D	none	Pasture, grazed 169 days/yr (46% of annual manure production for 25% of herd) at 0.82 AU/ha (= 1 AU/3 acres)
Dairy_Paddock (="DPADD")	none	A, B, C, D	none	Pasture, 10% of annual manure production, at 20x grazing density, as 12 equal monthly applications
Beef_Pasture (="BPAST")	none	A, B, C, D	none	Pasture, grazed 169 days/yr (46% of annual manure production) at 1.23 AU/ha (= 1 AU/2 acres)
Beef_Paddock (="BPADD")	none	A, B, C, D	none	Pasture, 54% of annual manure production, at 20x grazing density, as 12 equal monthly applications
Horse_Pasture (="HPAST")	none	A, B, C, D	none	Pasture, grazed 169 days/yr (46% of annual manure production) at 0.82 AU/ha (= 1 AU/3 acres)
Horse_Paddock (="HPADD")	none	A, B, C, D	none	Pasture, 54% of annual manure production, at 20x grazing density, as 12 equal monthly applications

Table 16. Areas of cropland and grazing rotations by basin quadrant in the St. Croix SWAT model for the 2000-09 decade.

Rotation	Quadrant			
	NE (km ²)	NW (km ²)	SW (km ²)	SE (km ²)
CS	94.0	224.0	329.0	528.0
CA, no manure	116.2	149.3	78.0	372.0
CA, seasonal applications	24.9	24.9	13.0	155.0
CA, daily haul	24.9	24.9	13.0	93.0
Dairy Pasture	71.4	69.7	0.0	295.6
Dairy Paddock	3.6	3.5	0.0	14.8
Beef Pasture	0.0	330.3	85.8	0.0
Beef Paddock	0.0	16.5	4.3	0.0
Horse Pasture	24.2	66.3	47.7	59.9
Horse Paddock	1.2	3.3	2.4	3.0

Land Cover: Differences between 1990s and 2000s

Land cover during the 1990s was also an important consideration in model development because the TMDL study for the St. Croix basin has set the phosphorus loads to Lake St. Croix during that period as the baseline against which future changes will be measured (MPCA and WDNR, 2012). That is, the clean-water goal for the basin is to reduce phosphorus loads to Lake St. Croix by about 27%, down to about 337 metric tons (metT) from about 460 metT, which was the 1990s decadal average annual load. Hence we needed an accurate land-cover configuration in the model for the 1990s to calibrate model to the known loads during that decade.

For cropland, we again relied on countywide NASS tabular data, averaged from 1990-99 (Table 17) to remain consistent with the tabular data compiled for the 2000s. These data sets indicate that the total area of cropland changed very little from the 1990s to the 2000s, decreasing from 11.7% of the basin to 11.3% of the basin (Table 7, bottom). This is in contrast to the trend indicated by the spatial data sets, where the NLCD 1992 data show about 16% of the basin in tillage, which drops to about 9% in the CDL 2007 data set (Table 1). Imprecision in the spatial data and differences in algorithms to interpret the imagery can make comparisons among spatial data sets problematic for detailed analyses, which further demonstrates the need to use other data sets such as the NASS tabular data as a means of ground-truthing. Even though the cropland area remained relatively constant from the 1990s to the 2000s, there was a large change in areas of tillage rotations. In the 1990s about two-thirds of the cropland was in a forage rotation of corn and alfalfa (CA), with about one-third in a corn-soybean (CS) cash-crop rotation. By the 2000s, these two rotations had become approximately equal (Table 7).

Changes in pasture areas were determined based on differences in livestock populations between the 1990s and the 2000s. Livestock populations for the 1990s were determined as the 1990-99 average of the countywide NASS data sets, scaled by the percent of each county within the basin and summarized for each quadrant. Livestock was more diverse in the 1990s, with more hogs, chickens, and sheep. To remain consistent with our modeled livestock types, hogs and chickens were converted to dairy-cow equivalents, constituting 7% of the resulting dairy-cow AUs. Likewise, sheep were converted to horse equivalents, constituting 9% of the resulting horse AUs. For these AU types over the entire basin, from the 1990s to the 2000s the population of dairy cows dropped by 27% and that of horses increased 10%. Beef population changes were more of a problem, because the tabular data show almost 21,000 beef in Wisconsin in the 1990s, but none in the 2000s. In contrast, in Minnesota beef population increased by about 7,000 AUs, or 16%.

Urban land area was adjusted based on population changes from 1995 to 2005, assuming 1995 was representative of the 1990s and 2005 of the 2000s. U.S. Census Bureau data were tallied for each county and scaled by the percent of each county in the basin and summarized by quadrant. During this time, population increased by 21% over the whole basin (from 385,000 to

Table 17. Crop areas and yields by quadrant and county in the St. Croix basin, 1990-99 averages, distributing areas of minor crops among major crops.

Quadrant/County	Corn-grain		Corn-silage		Soybeans		Alfalfa		Hay, other	
	Area (km ²)	Yield (t/ha)	Area (km ²)	Yield (t/ha)	Area (km ²)	Yield (t/ha)	Area (km ²)	Yield (t/ha)	Area (km ²)	Yield (t/ha)
Northwest Quadrant (NW)										
MN-Aitkin	0.40	4.48	0.84	8.10	0.92	1.49	4.05	6.30	26.01	4.21
MN-Carlton	0.58	4.44	2.27	8.16	n/a	n/a	14.49	5.41	46.60	4.06
MN-Kanabec	62.98	5.10	17.04	9.04	19.73	1.66	41.86	6.80	80.56	4.47
MN-Mille Lacs	14.31	5.29	3.97	9.95	4.66	1.72	9.90	7.66	10.63	4.85
MN-Pine	63.37	5.02	35.72	8.87	20.49	1.70	82.81	7.27	165.85	4.30
Total area & average yield	141.63	4.87	59.84	8.83	45.80	1.64	153.11	6.69	329.65	4.38
Percent of tilled area	35.4%		14.9%		11.4%		38.2%			
Total tilled area in quadrant	400.38									
Southwest Quadrant (SW)										
MN-Anoka	5.92	5.32	0.66	9.23	2.90	1.66	3.39	6.16	1.05	4.27
MN-Chisago	115.04	5.30	13.80	9.43	65.05	1.59	51.33	6.99	32.47	4.89
MN-Isanti	29.78	5.43	1.42	8.76	17.72	1.63	7.57	6.98	3.05	4.45
MN-Ramsey	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
MN-Washington	67.22	6.73	4.05	9.83	41.30	2.26	33.73	7.00	15.22	4.41
Total area & average yield	217.97	5.70	19.92	9.31	126.97	1.78	96.02	6.78	51.79	4.50
Percent of tilled area	47.3%		4.3%		27.5%		20.8%			
Total tilled area in quadrant	460.88									
Northeast Quadrant (NE)										
WI-Bayfield	0.60	5.05	0.84	6.95	0.04	1.33	13.42	4.27	12.78	3.73
WI-Burnett	52.67	5.06	12.89	8.90	11.12	1.47	61.74	5.09	19.60	4.04
WI-Douglas	0.37	4.38	0.41	7.39	n/a	n/a	19.59	4.04	26.51	3.91
WI-Sawyer	1.82	5.20	0.83	8.43	0.22	1.75	3.27	5.25	2.45	3.72
WI-Washburn	25.11	5.30	10.28	9.08	1.49	1.53	60.38	4.84	18.96	4.61
Total area & average yield	80.58	5.00	25.24	8.15	12.87	1.52	158.41	4.70	80.30	4.00
Percent of tilled area	29.1%		9.1%		4.6%		57.2%			
Total tilled area in quadrant	277.10									
Southeast Quadrant (SE)										
WI-Barron	14.92	5.72	4.73	10.48	1.38	2.06	23.52	5.25	3.27	4.86
WI-Pierce	27.51	6.57	4.94	11.94	6.42	2.29	21.74	6.50	1.62	4.70
WI-Polk	195.47	5.92	59.51	10.53	38.19	2.02	256.24	5.39	47.23	5.23
WI-St. Croix	220.85	6.29	46.38	11.84	63.70	2.11	205.50	5.87	23.01	5.00
Total area & average yield	458.75	6.13	115.55	11.20	109.69	2.12	507.00	5.75	75.14	4.95
Percent of tilled area	38.5%		9.7%		9.2%		42.6%			
Total tilled area in quadrant	1190.99									
Whole Basin										
Total area & average yield	899	5.42	221	9.37	295	1.77	915	5.98	537	4.46
Percent of tilled area	38.6%		9.5%		12.7%		39.3%			
Total tilled area in basin = 2,329 km ²										

NOTES: County-wide data for 1990-99 from NASS (2009). Areas for each crop have been scaled by the fractional land area of each county within the St. Croix basin. Crop yields refer to dry biomass per unit area. See conversion table for factors to convert reported yields to dry biomass.

465,000), with most growth (28%) occurring in the SE quadrant and least growth (8%) occurring in the NE quadrant.

Table 18 summarizes the changes in the areas of selected land-cover types from the 1990s to the 2000s. The factors in the table show the area of that land cover type in the 2000s relative to the 1990s. For example, the area of the CA rotation in the NW quadrant of the basin in the 2000s was 0.76 (76%) of the area in the 1990s (Table 18, upper left cell of table). In contrast, the area of the CS rotation in that quadrant was 1.61 times larger (61% larger) in the 2000s than in the 1990s.

To implement these changes in the SWAT model, we began with our baseline 2000s land-cover configuration represented by 3010 HRUs. We then expanded or contracted the HRUs of the land-cover types that had changed between the 1990s from the 2000s. Because we were working backwards in time, from the 2000s to the 1990s, we used the inverses of the change factors shown in Table 18. To accomplish these changes, we used a Visual Basic script in Microsoft Access written by a colleague (Jason Ulrich, Dept. of Biosystems and Agricultural Engineering, Univ. of Minnesota, personal communication, March 2011). The script starts with a table of starting HRU areas (as fractions of subbasin areas) and proposed change factors, and the script output is a table of new HRU areas. HRUs with a change factor <1 will be shrunk, with other HRUs in the same subbasin expanding proportionally. HRUs with a change factor >1 will be expanded at the expense of other HRUs in the subbasin. HRUs explicitly given a change factor of 1 will be kept constant in area. We used this option, for example, to preserve the areas of wetlands and open water. All other HRUs – those without specified change factors – were then adjusted to accommodate the requested changes. The script was further constrained by making sure that

Table 18. Land-cover change factors from 1990s to 2000s in the St. Croix basin.

Land Use	Quadrant of St. Croix Basin				Average
	NW	SW	NE	SE	
<i>Tilled Crop Rotations</i>					
Corn silage / Alfalfa (CA)	0.76	0.65	0.70	0.74	0.71
Corn grain / Soybeans (CS)	1.61	1.10	2.27	1.47	1.61
<i>Pasture & Paddock</i>					
Dairy	0.55	0.54	0.88	0.79	0.69
Beef	1.22	0.96	n/a	n/a	1.09
Horse	0.93	1.27	1.34	1.14	1.17
<i>Urban Land</i>					
High density	1.19	1.21	1.08	1.28	1.19
Medium density	1.19	1.21	1.08	1.28	1.19

NOTES: Crop areas determined from countywide NASS data for crops, 1990-99 averages to 2000-08 averages (NASS, 2009). Corn, soybeans, and alfalfa were considered to be the principal crops; areas of minor crops were distributed among these three major crops. Change in pasture and paddock areas were assumed to be proportional to changes in livestock populations, obtained as countywide NASS tables for 1990-99 averages to 2000-09 averages (NASS, 2010). Change in urban land area was assumed to be proportional to change in county populations from 1995 to 2005, from U.S. Census Bureau (2011). All countywide data were area-weighted by the proportion of St. Croix Basin comprised by each county.

NW quadrant: Aitkin, Carlton, Kanabec, Mille Lacs, and Pine counties, Minnesota
 SW quadrant: Anoka, Chisago, Isanti, Ramsey, and Washington counties, Minnesota
 NE quadrant: Bayfield, Burnett, Douglas, Sawyer, and Washburn counties, Wisconsin

the total area of each subbasin remained constant, and that no HRU was made smaller than 0.001 of the subbasin area. The script does not change the number of HRUs, only their relative areas. (Changing the number HRUs would require significant changes in SWAT's FORTRAN code.)

Point-Source Data

Even though most of the phosphorus load to the St. Croix is from nonpoint sources, the load from point sources remains significant and critical to quantify for several reasons. First, point-source loads of phosphorus are one of the few components of phosphorus cycle that can be measured accurately, at least in theory. In practice, reliable calculations of point-source phosphorus loads from wastewater treatment plants were not available prior to 1970 and did not become routine until the 1990s (Edlund et al., 2009b). Nonetheless, these measurements have been valuable in documenting recent changes in phosphorus load due to population growth and treatment technology. Second, knowledge of point-source loads has been critical in allowing inference of the how total load is partitioned into point versus nonpoint-source loads (Edlund et al., 2009b). Third, point sources tend to discharge soluble phosphorus, which is immediately and directly available to stimulate algal growth. Smaller loads of soluble phosphorus from point sources could have a more immediate impact on eutrophication than larger loads of particulate phosphorus from nonpoint sources, at least in the short run.

There are currently about 87 permitted waste dischargers in the St. Croix basin (Edlund et al., 2009b). However, some of these sources either produce negligible phosphorus loads or apply their effluent to land rather than to surface water. Magdalene (2009) identified the 48 principal point sources in the basin discharging to surface water, and these point sources were included in the SWAT model (Table 19 and Figure 9). Nine of these sources are industrial, and 39 are municipal wastewater treatment plants of some sort. Even some of these sources have nearly negligible (or poorly known) current loads but were retained in the model to allow input of future loads as needed.

Edlund et al. (2009b) calculated decadal-average point-source phosphorus loads to the St. Croix from 1900 to 2000, based on demographics and treatment-plant effluent data where available. Magdalene (2009) updated the analysis, adding recent treatment-plant data from 1999-2007. For data entry into the SWAT model, we chose to use the time series of annual average loads for each of the 48 point sources included. For the period 1999-2007 we used the annual loads as calculated by Magdalene (2009). Prior to 1999, we then used the decadal average basin-wide load as given in Edlund et al. (2009b) and distributed it among the point sources based on the proportions of effluent flow volumes during the 1990s. We then applied those loads to the middle year of each decade (e.g., 1995, 1985, and so forth) and interpolated between these values to obtain a time series of average annual point-source loads of phosphorus back to 1900. In this time series, we excluded all industrial point sources (which are a minor component) and all current municipal dischargers that were not operating prior to 1990. This time series is fairly

Table 19. Permitted point-source dischargers to surface waters in the St. Croix basin.

Model ID	State ID	Name	Type	Geographic coordinates		UTM coordinates		Phosphorus load	
				Longitude (dec deg)	Latitude (dec deg)	Easting (m)	Northing (m)	1990s (kg/yr)	2005-07 (kg/yr)
psmn001	MN0055662	Aitkin agri-peat Inc - Cromwell	I	-92.7820	46.6717	516681	5168685	166	71
psmn002	MN0022616	Askov WWTP	M	-92.7836	46.1785	516701	5113898	166	91
psmn003	MNG580142	Barnum WWTP	M	-92.7969	46.5051	515580	5150185	415	274
psmn004	MN0055808	Chisago Lakes Joint STC	M	-92.8755	45.4058	509624	5028018	4648	3288
psmn005	MN0050636	Cimarron Park WWTP	M	-92.8692	44.9626	510316	4978799	0	0
psmn006	MN0023418	Finlayson WWTP	M	-92.9085	46.1967	507057	5115916	830	4
psmn007	MNG580052	Grasston WWTP	M	-93.1579	45.7916	487731	5070900	166	18
psmn008	MN0050130	Harris WWTP	M	-92.9728	45.5814	502193	5047753	82	82
psmn009	MN0023701	Hinckley WWTP	M	-92.9089	46.0187	507054	5096125	1410	324
psmn010	MN0023809	Isle WWTP	M	-93.4584	46.1254	464646	5108179	114	150
psmn011	MN0057002	Kettle River WWTP	M	-92.5240	46.2930	509364	5148679	166	52
psmn012	MN0054372	Linwood Terrace Co.	I	-93.1082	45.3633	491715	5023402	17	8
psmn013	MN0020699	Moose Lake WWTP	M	-92.7946	46.4419	515852	5143150	1327	1030
psmn014	MN0021156	Mora WWTP	M	-93.3107	45.8767	475901	5080401	1981	2247
psmn015	MN0024350	North Branch WWTP	M	-92.9706	45.5156	502199	5040280	4480	230
psmn016	MN0021997	Ogilvie WWTP	M	-93.4088	45.8318	468260	5075406	498	291
psmn017	MN0021784	Pine City WWTP	M	-92.9386	45.8399	504915	5076255	2074	128
psmn018	MN0021342	Rush City WWTP	M	-92.9495	45.6952	503874	5060102	664	519
psmn019	MN0056910	Sandstone WWTP	M	-92.8303	46.0999	511414	5104579	1161	1408
psmn020	MN0030848	Shafer WWTP	M	-92.7588	45.3907	519040	5026288	166	301
psmn021	MN0051390	Shorewood Park Sanitary District	I	-93.0263	45.6930	497627	5059746	27	50
psmn022	MN0029998	St Croix Valley WWTP	M	-92.7881	45.0392	516693	4987323	1237	2487
psmn023	MN0053309	Taylor Falls WWTP	M	-92.6778	45.3837	525398	5025568	374	240
psmn024	MNG580051	Wahkon WWTP	M	-93.5283	46.0918	459158	5104384	0	181
psmn025	MNG580054	Willow River WWTP	M	-92.8441	46.3175	512002	5129337	0	115
psmn026	MN0000825	Xcel - Allen S King Power Plant	I	-92.7706	45.0294	518032	4986270	0	0
pswi001	WI0031861	Amani	M	-92.6370	45.2496	528489	5010750	24	9
pswi002	WI0020125	Amery	M	-92.3630	45.3005	549943	5016530	743	488
pswi003	WI0039039	Burnett Dairy	I	-92.5812	45.7715	532565	5068750	239	208
pswi004	WI0036706	Clayton	M	-92.1701	45.3488	565009	5022030	233	361
pswi005	WI0023639	Clear Lake	M	-92.2547	45.2452	558490	5010450	2512	129
pswi006	WI0025356	Deer Park	M	-92.3795	45.1699	548762	5002010	108	87
pswi007	WI0060429	Grantsburg	M	-92.6930	45.7797	523869	5069620	1129	1104
pswi008	WI0024279	Hudson	M	-92.7594	44.9664	518971	4979240	6031	1065
pswi009	WI0002836	Lakeside Foods/Chiquita	I	-92.5488	45.1229	535486	4996700	11	23
pswi010	WI0021482	Luck	M	-92.4837	45.5879	540272	5048390	486	423
pswi011	WI0021245	New Richmond	M	-92.5608	45.1153	534546	4995860	1758	631
pswi012	WI0025020	Osceola	M	-92.7174	45.3153	522150	5018020	1859	296
pswi013	WI0029394	River Falls	M	-92.6378	44.8536	528616	4966750	6552	858
pswi014	WI0028835	Roberts	M	-92.5648	44.9699	534316	4979700	42	64
pswi015	WI0028924	Siren	M	-92.3917	45.7776	547291	5069520	497	651
pswi016	WI0030252	Somerset	M	-92.6830	45.1346	524928	4997960	987	137
pswi017	WI0020796	St. Croix Falls	M	-92.6474	45.4067	527596	5028190	1159	1522
pswi018	WI0060984	Star Prairie	M	-92.5446	45.1903	535776	5004200	0	217
pswi019	WI0049191	WDNR GTT Fish Hatchery	I	-91.8988	45.8204	585543	5074690	79	66
pswi020	WI0004197	WDNR Osceola Fish Hatchery	I	-92.6796	45.3496	525100	5021840	184	1
pswi021	WI0004201	WDNR SCF Fish Hatchery	I	-92.6469	45.4064	527634	5028160	160	3
pswi022	WI0028843	Webster	M	-92.3558	45.8657	550000	5079320	315	404

NOTES: Model ID, identification number for the purposes of model development; State ID, identification number assigned by state agencies; Discharger Type, either municipal (M) or industrial (I); dec deg, decimal degree; UTM, Universal transverse mercator projection, Zone 15 North, based on National Altitude Datum (NAD) of 1983; m, meter; kg, kilogram, 1990s refers to the period 1990-99. **REFERENCES:** Edlund 2009b; Magalene 2009; Steve Weiss, MPCA, personal communication, 2010; Kathy Bartilson, WDNR, personal communication, 2010.




Figure 9. Permitted point sources discharging to surface waters in the St. Croix basin.

speculative, since most of the treatment plants in the list did not physically exist in the early 1900s. But, including these point sources in the model provides a mechanism to deliver the loads estimated by Edlund et al. (2009b) that is consistent with known population patterns, should we choose to run the model that far back in time.

According to Edlund et al. (2009b), loads peaked in the 1960s-70s but declined in the 1980s after both Minnesota and Wisconsin banned phosphorus in laundry detergent. Loads began rising again, however, during the 1990s in response to population growth in the basin. Point-source loads during the 1990s were estimated at 47.8 metT/yr by Edlund et al. (2009b), at 52 metT/yr by Magdalene (2009), and at 47.3 metT/yr in our analysis (Table 20). About 98% of the load was from municipal, rather than industrial, dischargers, with a little higher loading from Wisconsin (53%) than from Minnesota (47%). By the 2000s, point-source loads dropped to 22.3 metT/yr, down by more than half, because of upgrades to wastewater treatment plants in both Minnesota and Wisconsin. We note the importance of the point-source load estimates for the 1990s, because this is the decade that sets the benchmark against which future phosphorus loads will be measured. Likewise, the load estimate for the 2000s (from data for 2005-07) will form the baseline for “current” conditions in the SWAT model.

Table 20. Summary of point-source phosphorus loads to the St. Croix receiving waters.

Category	Annual P Load (kg)		Percent of basin total	
	1990s	2005-07	1990s	2005-07
Municipal	46,391	21,904	98.1%	98.1%
<i>Minnesota</i>	21,958	13,460	46.4%	60.3%
<i>Wisconsin</i>	24,433	8,445	51.7%	37.8%
Industrial	883	431	1.9%	1.9%
<i>Minnesota</i>	209	129	0.4%	0.6%
<i>Wisconsin</i>	674	303	1.4%	1.4%
Minnesota	22,167	13,588	46.9%	60.8%
Wisconsin	25,107	8,747	53.1%	39.2%
Basin total	47,274	22,335		

Climate Data

Climate data are one of the foundations required for accurate hydrologic modeling. Yet, within any climate data set, there are spatial gaps between weather stations and temporal gaps when data were not being collected. To fill these gaps, Zhang and Srinivasan (2009) developed a geospatial interpolation scheme that uses only weather stations with data available for a selected day, thus filling temporal gaps from station with missing values. The method then spatially interpolates the data across the watershed between weather stations, thus filling spatial gaps. The result is a continuous time series of daily precipitation and temperature values that are smoothly distributed across the basin in a spatial grid. For application to SWAT, the method then averages the precipitation and temperature grid values within each subbasin polygon delineated by ArcSWAT for each day of the climate data record. In essence, the method creates a weather “pseudo-station” at the centroid of each subbasin polygon with its own continuous daily weather record.

For the St. Croix basin, daily precipitation and temperature observations of 25 weather stations (Table 21 and Figure 10) within or close to the St. Croix basin were obtained from National Climatic Data Center (NCDC, 2010). The methods given in Zhang and Srinivasan (2009) include a number of spatial interpolation options. In this study, we used the ordinary kriging method to spatially interpolate daily weather data from 1960 to 2009, producing basin-wide grids of precipitation and temperature values for each day during this period. As an



Figure 10. Weather stations in the high-density cooperative network used to generate daily values for each of the pseudo-stations in the SWAT model.




Figure 11. Example of spatially interpolated precipitation for the rain event of 8 August 2008.




Figure 12. Annual mean precipitation over the St. Croix basin, 1960-2008.

example, the spatial grid of interpolated precipitation on 8 August 2008 is shown in Figure 11. The time series of basin-wide annual areal mean precipitation from 1960-2008, which ranges from 400 mm to 1050 mm, is shown in Figure 12. Rather than apply the method to the full set of 419 subbasins in the SWAT model, we chose to use a slightly simpler delineation with only 114 subbasins. Consequently, each weather pseudo-station provided climate data to three or four subbasins.

Table 21. Weather stations included in the St. Croix SWAT model as sources of daily precipitation, maximum temperature, and minimum temperature.

ID	Name	Altitude (ft)	Geographic coordinates		UTM coordinates	
			Longitude (dec deg)	Latitude (dec deg)	Easting (m)	Northing (m)
<i>Minnesota</i>						
210059	Aitkin 2 E	1215	-93.0667	46.5167	494886	5151458
211074	Bruno 7 ENE	845	-92.5333	46.3000	535939	5127486
211227	Cambridge 5 ESE	960	-93.1167	45.5500	490893	5044058
212881	Forest Lake 5 NE	960	-92.9000	45.0333	507877	4986658
213793	Hinckley	1035	-92.9833	45.9833	501291	5092196
214103	Isle 12 N	1285	-93.0500	46.3167	496151	5129234
215598	Moose Lake 1 SSE	1110	-92.7500	46.4333	519206	5142226
215603	Moose Lake RS	1060	-92.7667	46.4500	517920	5144074
215615	Mora	1018	-93.3000	45.8667	476715	5079277
216166	Onamia RS	1260	-93.0667	46.0667	494844	5101457
218037	Stillwater 1 SE	710	-92.7833	45.0333	517067	4986676
218039	Stillwater 2 SW	898	-92.8500	45.0333	511815	4986664
218986	Wild River SP	940	-92.7333	45.5167	520828	5040383
<i>Wisconsin</i>						
470175	Amery	1070	-92.3500	45.3000	550962	5016483
471978	Danbury	950	-92.3667	46.0000	549040	5094242
472934	Frederic	1240	-92.4667	45.6500	541557	5055300
473186	Gordon	1040	-91.8000	46.2333	592527	5120673
473244	Grantsburg	990	-92.6833	45.7667	524623	5068172
474894	Luck	1220	-92.4833	45.5667	540318	5046033
475525	Minong 5 WSW	1075	-91.8667	46.0667	587651	5102079
477226	River Falls	933	-92.6000	44.8500	531608	4966365
477230	Roberts WWTP	977	-92.5500	44.9667	535487	4979346
477464	St. Croix Falls	770	-92.6333	45.4000	528697	5027452
477892	Solon Springs	1130	-91.8167	46.3500	591048	5133616
478027	Spooner Ag Res	1100	-91.8667	45.8167	588046	5074303
479012	Webster 9 SE	1005	-92.2167	45.7833	560892	5070273

SOURCE: NCDC (2010).

Model Construction Summary

The resulting SWAT model of the St. Croix basin had 419 subbasins with 3010 HRUs. A total of 39 lakes were included; these were most of the lakes larger than 200 ha plus four smaller lakes of particular interest from previous studies. Smaller lakes and wetlands were modeled as aggregate units within each subbasin. Agricultural practices included a corn-soybean rotation and a corn-alfalfa rotation, some of which received seasonal or monthly applications of dairy manure. Grazing by horses, beef cattle, and dairy cows was simulated at several densities. The model included 48 point sources with annual data for flow and phosphorus estimated from 1900 to 2007. Daily climate data were compiled from 1960 to 2009.

Model Calibration and Validation

Model calibration (or parameterization) means to adjust model parameters so that model output matches measured data from the watershed as closely as possible. Model validation means to compare output from a calibrated model to a second, independent set of measurements from the watershed as a test of model reliability, without any further parameter adjustment. Variables used for the comparison commonly include flow (daily or monthly), constituent loads (typically monthly), and sometimes constituent concentrations.

Goodness of Fit Measures

Both calibration and validation require goodness of fit measures to determine how well the model matches the target data, i.e., to determine the “model performance.” An essential first step in model evaluation is to compare plots of observed data with model output (ASCE, 1993). These plots commonly display a time series of flow (e.g., a hydrograph) or transported constituent (e.g., a sedigraph for suspended sediment) at daily, monthly, or annual time steps. Overlaying plots of observed and simulated data can help identify model bias, differences in timing and magnitude of peaks and troughs, and differences in plot shape (e.g., slopes of rises and falls).

To provide more objectivity and quantitative rigor, indices have been developed to measure how closely the model output matches the observed data. In evaluating the St. Croix SWAT model, we used three quantitative statistics recommended by Moriasi et al. (2007): the Nash-Sutcliffe efficiency (NSE), the percent bias (PBIAS), and the ratio of the root-mean-square error to standard deviation (RSR).

Nash-Sutcliffe efficiency (NSE): The Nash-Sutcliffe efficiency (NSE) is a normalized statistic that determines the relative magnitude of the residual variance (“noise”) compared to the measured data variance (“information”) (Nash and Sutcliffe, 1970). NSE indicates how well the plot of observed versus simulated data fits the 1:1 line. NSE is computed as shown in equation 1:

$$NSE = 1 - \left[\frac{\sum_{i=1}^n (Y_{obs,i} - Y_{sim,i})^2}{\sum_{i=1}^n (Y_{obs,i} - Y_{mean})^2} \right] \quad [1]$$

Where

$Y_{obs,i}$ is the i th observation for the constituent being evaluated,
 $Y_{sim,i}$ is the i th simulated value for the constituent being evaluated,
 Y_{mean} is the mean of observed data for the constituent being evaluated,
and n is the total number of observations.

NSE ranges between negative infinity and 1.0, with 1.0 being the optimal value (a perfect model fit) and values <0.0 indicating that the mean observed value is a better predictor than the simulated value, thereby demonstrating unacceptable model performance. Good performance is indicated by values >0.5 and acceptable performance by values between 0.0 and 0.5 (Moriasi et al., 2007). NSE is known to be greatly influenced by larger deviations (Legates and McCabe 1999, Krause et al. 2005). Thus, in comparing modeled flows for example, NSE is a better measure simulating peak flows rather than baseflows. Nonetheless, NSE remains highly recommended (ASCE, 1993; Legates and McCabe, 1999) and widely used, providing extensive information on reported values. Sevati and Dezetter (1991) also found NSE to be the best objective function for reflecting the overall fit of a hydrograph.

Percent bias (PBIAS): Percent bias (PBIAS) is the model deviation expressed as a percentage of the observed value. The optimal value of PBIAS is 0.0, with low-magnitude values indicating accurate model simulation. Positive values indicate model underestimation bias, and negative values indicate model overestimation bias (Gupta et al., 1999). PBIAS is calculated with equation 2:

$$PBIAS = \frac{[\sum_{i=1}^n (Y_{obs,i} - Y_{sim,i}) * (100)]}{\sum_{i=1}^n (Y_{obs,i})} \quad [2]$$

Root-mean-square error to observations standard deviation ratio (RSR):

Root-mean-square error (RMSE) is one of the commonly used error index statistics (Chu and Shirmohammadi, 2004; Singh et al., 2004; Vasquez-Amabile and Engel, 2005). Although it is commonly accepted that the lower the RMSE the better the model performance, only Singh et al. (2004) have published a guideline to qualify what is considered a low RMSE based on the observations standard deviation. Based on the recommendation by Singh et al. (2004), a model evaluation statistic, named the RMSE-observations standard deviation ratio (RSR), was developed. RSR standardizes RMSE using the observations standard deviation, and it combines both an error index and the additional information recommended by Legates and McCabe (1999). RSR is calculated as the ratio of the RMSE and standard deviation of measured data, as shown in

equation below:

$$RSR = \frac{RMSE}{STDEV_{obs}} = \frac{\sqrt{\sum_{i=1}^n (Y_{obs,i} - Y_{sim,i})^2}}{\sqrt{\sum_{i=1}^n (Y_{obs,i} - Y_{mean})^2}} \quad [3]$$

RSR incorporates the benefits of error index statistics and includes a scaling/normalization factor, so that the resulting statistic and reported values can apply to various constituents. RSR varies from the optimal value of 0, which indicates zero RMSE or residual variation and therefore perfect model simulation, to a large positive value. A lower RSR indicates a lower RMSE relative to the observed standard deviation and therefore better model performance.

Hydrology

Hydrologic calibration and validation of the St. Croix SWAT model were done where USGS flow data were readily available, at two sites on the St. Croix River main stem (Danbury and St. Croix Falls) and for three tributaries (Kettle River, Snake River, and Apple River). Estimated flows were also available from the Metropolitan Council for the St. Croix River at Stillwater, but because these flows were not directly measured they were not used for calibration. Instead, emphasis was given to the St. Croix Falls site as the most downstream gauged site representing the largest part of the basin. Basin-wide parameters were adjusted initially to obtain an approximate calibration to flows at St. Croix Falls. Then parameters were adjusted on a sub-basin basis for the St. Croix above Danbury, the Kettle, the Snake, and the Apple river watersheds, followed by a final small re-adjustment at St. Croix Falls. Key considerations in the hydrology calibration were the overall water balance, the high-flow to low-flow distribution, storm flows, and seasonal variation. Calibration was performed at the monthly time step for the period 2000-2007, and validation was performed for the time period of 1990-1999.

The parameters altered to achieve hydrologic calibration are given in Table 22. Snowmelt parameters were adjusted to avoid excessive snowmelt peaks in the spring. Soil evaporation, soil available water capacity, and forest canopy parameters were adjusted to increase evapotranspiration over most of the basin, thereby reducing overall water yield. Curve numbers were reduced by 20% to increase infiltration and baseflow. Baseflow was also enhanced by reducing loss of shallow groundwater to evapotranspiration by phreatophytes (plants reaching the water table or near to it). Recession following runoff events was fit by adjusting the baseflow recession (alpha baseflow) parameter. A full explanation of these parameters is beyond the scope of this report. Interested readers may consult Arnold et al. (2013).

The model fit the St. Croix River flow very well, with a calibrated NSE of 0.84 at St. Croix Falls and 0.71 at Danbury (Table 23; Figures 13a and 13b). The fits for the validation period are only slightly lower but still within the acceptable range as defined by Moriasi et al. (2007). The tributaries were fit similarly well, especially the Kettle and Snake rivers. The PBIAS

statistic shows overall water yield at St. Croix Falls fitting within 2% for the calibration period, and within 5% for the validation period. Hydrographs for the St. Croix River main stem (Figure 13) and calibrated tributaries (Figure 14) demonstrate the quality of the fit.

Table 22. Parameters altered to achieve hydrologic calibration of the St. Croix SWAT model.

Files	Parameter		Values		Subbasins applied
	Abbreviation	Name	Default	Calibrated	
BSN	SFTMP	Snowfall temperature (deg C)	1	-0.5	basin-wide
BSN	SMTMP	Snow melt base temperature (deg C)	0.5	0	basin-wide
BSN	SMFMX	Snow melt factor, maximum (mm H2O / degC-day)	4.5	4.5	basin-wide
BSN	SMFMN	Snow melt factor, minimum (mm H2O / degC-day)	4.5	3.5	basin-wide
BSN	TIMP	Snow pack temperature lag factor (0.01 - 1)	1	0.1	basin-wide
BSN	FFCB	Beginning soil water storage, as fraction of field capacity	1	0.8	basin-wide
GW	GW_DELAY	Groundwater delay time (days)	31	5	basin-wide
GW	ALPHA_BF	Baseflow alpha factor (baseflow recession constant) (days)	0.048	0.182 0.2 0.003	Kettle River watershed Snake River watershed rest of basin
GW	GWQMN	Threshold depth of water in shallow aquifer for groundwater discharge to reach to occur (mm H2O)	0	1 1 200	basin above Danbury Apple River watershed rest of basin
GW	REVAPMN	Threshold depth of water in shallow aquifer for loss to deep percolation or phreatophytic transpiration to occur (mm H2O)	1	600 500	basin above Danbury rest of basin
HRU	CANMX	Maximum canopy storage (mm H2O)	0	2.5	all FRSD (deciduous forest) in basin
HRU	ESCO	Soil evaporation compensaton factor (0.01 - 1)	0.95	0.95 0.8	Kettle River watershed rest of basin
MGT	CN2	Curve number for SCS moisture condition II		minus 20%	basin-wide
MGT	CNOP	Curve number for SCS moisture condition II, for selected management operation		minus 20%	basin-wide (for land with agricultural management operations)
RES	IFLOOD1R	Beginning month of non-flood season		10	basin-wide
RES	IFLOOD2R	Ending month of non-flood season		4	basin-wide
RES	NDTARG	Number of days to reach target storage from current storage.		3	basin-wide
SOL	SOL_AWC(1)	Available water capacity, soil layer 1 (mm H2O / mm soil)		plus 5%	basin-wide

Table 23. Goodness of fit statistics for hydrologic calibration and validation of the St. Croix SWAT model.

Site	Period	Years	NSE	PBIAS	RSR
<i>Main stem:</i>					
St. Croix River at Danbury	Calibration	2000-07	0.71	11	0.54
	Validation	1990-99	0.46	11	0.73
St. Croix River at SC Falls	Calibration	2000-07	0.84	2	0.40
	Validation	1990-99	0.78	5	0.47
St. Croix River at Stillwater	Calibration	2000-07	0.83	-1	0.41
	Validation	1990-99	0.78	2	0.47
<i>Tributaries:</i>					
Kettle River	Calibration	2000-07	0.85	14	0.38
	Validation	1990-99	0.75	7	0.50
Snake River	Calibration	2000-07	0.87	-4	0.36
	Validation	1990-99	0.70	-12	0.55
Apple River	Calibration	2000-07	0.54	-3	0.68
	Validation	1990-99	0.31	4	0.83
<i>Averages</i>					
	<i>Calibration</i>	<i>2000-07</i>	<i>0.77</i>	<i>3</i>	<i>0.46</i>
	<i>Validation</i>	<i>1990-99</i>	<i>0.63</i>	<i>3</i>	<i>0.59</i>

NOTES: Calibration period = 2000-07; Validation period = 1980-99; SC, St. Croix; NSE, Nash-Sutcliffe Coefficient of Efficiency; PBIAS, percent bias; RSR, ratio of root-mean-square-error to standard deviation of observations. See text for explanations and references.




Figure 13. Flow of the main stem of the St. Croix River at (a) Danbury, (b) St. Croix Falls, and (c) Stillwater for calibration (2000-07) and validation (1990-99) periods.




Figure 14. Flow of major tributaries to the St. Croix for calibration (2000-07) and validation (1990-99) periods: (a) Kettle River, (b) Snake River, and (c) Apple River.

Water Quality

Water quality in the SWAT model was calibrated sequentially by constituent. The model was calibrated first to suspended sediment, second to total phosphorus, and last to total nitrogen. All calibration was based on monthly loads at Stillwater as calculated by the Metropolitan Council Environmental Services (MCES 2011; K. Jensen, MCES, personal communication, 2011). Sediment and phosphorus were both fit well, with NSE values exceeding the 0.5 threshold value for the 2000-07 calibration period (Table 24). Total nitrogen was fit less well, with negative NSE values, but with low PBIAS values to assure that annual total loads were approximately correct. Monthly time series of these water-quality constituents showed good relation between modeled and observed monthly loads (Figure 15).

Sediment calibration in the St. Croix watershed was challenging due to the presence of numerous ponds and wetlands that act as a trap between the uplands and the monitoring point. These depressions are a consequence of the glacial-drift landforms in the St. Croix basin and they reduce subbasin-scale loads below those expected from calculations based on the universal soil-loss equation (USLE), including the modified USLE (MUSLE) used within SWAT. Fortunately, SWAT includes a number of features that allow the net effects of these depressions to be appropriately simulated (Almendinger et al. 2014). As noted earlier (Table 4), on average, all water yield from 37% of each subbasin area was routed through a SWAT wetland feature, and 8% through a SWAT pond feature, wherein significant fractions of sediment and nutrients were trapped. On-channel lakes (reservoirs in SWAT) were likewise important sediment traps impacting net yields from all upstream contributing subbasins. To reduce sediment yields further, parameters were adjusted to alter both the availability and transport of sediment (Table 25). These adjustments included reducing peak flow rates, slope lengths, and soil erosivity below initial values. In addition, the net sediment-trapping effect of small upland depressions was simulated by reducing the support practice factor (USLE_P) to 0.5, and the net effect of vegetated overland flow paths was simulated by adding filter strips to selected land units (Table 25).

Table 24. Goodness of fit statistics for water-quality calibration and validation of the St. Croix SWAT model.

Site	Period	Years	NSE	PBIAS	RSR
Suspended sediment	Calibration	2000-07	0.76	-8.24	0.49
	Validation	1990-99	0.57	-19.68	0.65
Total phosphorus (TP)	Calibration	2000-07	0.62	18.30	0.62
	Validation	1990-99	-0.51	28.86	1.22
Total nitrogen (TN)	Calibration	2000-07	-1.88	0.47	1.69
	Validation	1990-99	-1.34	11.01	1.52

NOTES: Calibration period = 2000-07; Validation period = 1990-99; NSE, Nash-Sutcliffe Coefficient of Efficiency; PBIAS, percent bias; RSR, ratio of root-mean-square-error to standard deviation of observations. See text for explanations and references. All model runs were begun five years prior to calibration or validation period to allow for model equilibration (model spin-up).




Figure 15. Monthly loads of (a) suspended sediment, (b) total phosphorus, and (c) total nitrogen for the St. Croix River at Stillwater, 1990-2007.

Table 25. Parameters altered to achieve sediment calibration of the St. Croix SWAT model.

Files	Abbreviation	Parameter Name	Values		Subbasins applied
			Default	Calibrated	
bsn	ADJ_PKR	Peak rate adjustment factor for sediment routing in tributary channels (in subbasins)	1	0.869	basin-wide
bsn	PRF	Peak rate adjustment factor for sediment routing in main channel	1	0.10	basin-wide
hru	HRU_SLP	Average slope (m/m)	interface	0.50%	wetland and grassland with initial slopes >0.5%
hru	SLSUBBSN	Average slope length (m)	interface	minus 20%	wetland, grassland, and agricultural land
mgt1	FILTERW	Width of edge-of-field filter strip (m)	0	22.7	all HRUs
mgt1	USLE_P	USLE support practice factor	1	0.5	all HRUs
pnd	PND_NSED	Equilibrium sediment concentration in ponds (mg/L)	1	0	all ponds
pnd	WET_NSED	Equilibrium sediment concentration in wetlands (mg/L)	1	0	all wetlands
res	RES_NSED	Equilibrium sediment concentration in reservoirs (lakes) (mg/L)	1	0	all reservoirs (lakes)
sol	USLE_K	USLE soil erodibility factor	database	minus 44%	all soils
till.dat	DEPTIL	Depth of tillage (mm)	150	100	moldboard plow
			100	60	disk
			150	100	chisel plow
till.dat	EFFMIX	Efficiency of tillage (fraction mixed)	0.95	0.6	moldboard plow
			0.85	0.4	disk
			0.3	0.25	chisel plow

Total phosphorus (TP) loads are of vital importance to the St. Croix basin: phosphorus is the prime suspect causing the eutrophication impairment of Lake St. Croix. Hence calibrating phosphorus loads in the model is an important first step in understanding the sources of phosphorus and its transport to receiving waters. Once we understand the source and transport of phosphorus, we can develop mitigation efforts to abate these loads. However, phosphorus calibration was likewise complicated by the same transport factors that affected sediment, resulting in a large number of parameter adjustments (Table 26). Total phosphorus loads were reduced as a consequence of the sediment calibration, especially for low-flow months. To help bring loads up to observed values, tillage depth and efficiencies were reduced to keep more phosphorus near the land surface and available for transport by overland runoff. Ultimately, the many surface-water bodies in the St. Croix basin played an apparent major role in mediating the total phosphorus load and the timing of its routing down the stream network. The phosphorus settling parameters for ponds and lakes (reservoirs in SWAT) were adjusted so that water bodies trapped significant amounts during the months with high runoff and suspended sediment loads. However, during the low-flow months some of this phosphorus was released (i.e., a negative settling rate), thereby elevating low-flow phosphorus loads. In short, ponds and lakes smooth the seasonal signal of phosphorus loading, reducing springtime runoff peaks and increasing low-flow loads. This hypothesis needs testing but could explain why the St. Croix, with its many lakes, may cycle nutrients somewhat differently than other large basins. The pattern is consistent with other SWAT models for tributary watersheds within the St. Croix basin, namely the Willow (Almendinger and Murphy 2007) and Sunrise (Almendinger and Ulrich 2010, 2012) river watersheds.

Calibration of total nitrogen was more problematic than for either sediment or phosphorus, which we attribute to the many microbial processes that can alter nitrogen speciation and transport in a basin with as many wetlands and lakes as in the St. Croix. These processes are not well-constrained in SWAT or other such large-basin models. The negative NSE values for

Table 26. Parameters altered to achieve nutrient calibration of the St. Croix SWAT model.

Files	Parameter		Values		Subbasins applied
	Abbreviation	Name	Default	Calibrated	
bsn	CDN	Exponential rate of denitrification	1.4	0.112	basin-wide
bsn	NPERCO	Nitrogen percolation coefficient	0.2	0.012	basin-wide
bsn	RCN	Concentration of nitrogen in rainfall (mg N/L)	0	13.28	basin-wide
bsn	SDNCO	Denitrification threshold water content	1.1	0.945	basin-wide
lwq	RES_NO3	Initial concentration of nitrate in pond (mg/L)	0	0.782	all reservoirs (lakes)
lwq	RES_ORGN	Initial concentration of organic nitrogen in reservoir (mg/L)	0	0.576	all reservoirs (lakes)
pnd	NSETLP1	Season 1 nitrogen settling rate for ponds (m/yr)	5.5	-0.4	all ponds
pnd	NSETLP2	Season 2 nitrogen settling rate for ponds (m/yr)	5.5	0.15	all ponds
pnd	NSETLW1	Season 1 nitrogen settling rate for wetlands (m/yr)	5.5	-0.8	all wetlands
pnd	NSETLW2	Season 2 nitrogen settling rate for wetlands (m/yr)	5.5	6	all wetlands
pnd	PND_NO3	Initial concentration of nitrate in pond (mg/L)	0	3.525	all ponds
pnd	PND_ORGN	Initial concentration of organic nitrogen in pond (mg/L)	0	10.37	all ponds
pnd	PND_ORGP	Initial concentration of organic phosphorus in pond (mg/L)	0	0.38	all ponds
pnd	PND_SOLP	Initial concentration of soluble phosphorus in pond (mg/L)	0	2.7	all ponds
pnd	PSETLP1	Season 1 phosphorus settling rate for ponds (m/yr)	10	-15	all ponds
pnd	PSETLP2	Season 2 phosphorus settling rate for ponds (m/yr)	10	4.8	all ponds
pnd	WET_NO3	Initial concentration of nitrate in pond (mg/L)	0	20.01	all ponds
pnd	WET_ORGN	Initial concentration of organic nitrogen in pond (mg/L)	0	54.17	all ponds
res	NSETLR1	Season 1 nitrogen settling rate for reservoirs (m/yr)	5.5	-0.4	all reservoirs (lakes)
res	NSETLR2	Season 2 nitrogen settling rate for reservoirs (m/yr)	5.5	0.15	all reservoirs (lakes)
res	PSETLR1	Season 1 phosphorus settling rate for reservoirs (m/yr)	10	-15	all reservoirs (lakes)
res	PSETLR2	Season 2 phosphorus settling rate for reservoirs (m/yr)	10	4.8	all reservoirs (lakes)
res	RES_ORGP	Initial organic phosphorus concentration in reservoirs (mg/L)	0	0.7	all reservoirs (lakes)
res	RES_SOLP	Initial soluble phosphorus concentration in reservoirs (mg/L)	0	0.8	all reservoirs (lakes)
till.dat	DEPTIL	Depth of tillage (mm)	150	100	moldboard plow
			100	60	disk
			150	100	chisel plow
till.dat	EFFMIX	Efficiency of tillage (fraction mixed)	0.95	0.6	moldboard plow
			0.85	0.4	disk
			0.3	0.25	chisel plow
wwq	P_N	Algal preference factor for ammonia	0.5	0.115	basin-wide

nitrogen (Table 24) indicate a mis-match between modeled and observed values, and the plot of monthly values (Figure 15c) show how many peaks are missed and low-flow months tend to be underestimated. Part of the low-flow underestimation may be attributed to the loads of nitrogen associated with dissolved organic carbon, known to be large in the St. Croix, which is not one of the components considered in SWAT. Since the monthly pattern of nitrogen loads was not well-matched, we focused on getting the total load about right, as shown by a low PBIAS value for the calibration period (Table 24).

The average yields (annual loads per unit area) may be mapped on a subbasin-by-subbasin basis to show the net results of the source and transport factors acting across the St. Croix basin. Figures 16-18 show the average annual yields of sediment, total phosphorus, and total nitrogen, respectively. These maps represent delivery of sediment and nutrients from the landscape (including ponds and wetlands) to the stream network; they do not include the trapping of sediment and nutrients by lakes connected to the stream network. These maps can help guide implementation efforts by locating “hot spots” of sediment and nutrient sources and delivery. Because both source and delivery are considered, such maps should be superior to those based on source (land use) alone, where export coefficients are used to translate land use into area-weighted yields and annual loads.




Figure 16. Average annual sediment yield by model subbasin in the St. Croix basin, 2000-07.




Figure 17. Average annual total phosphorus yield by model subbasin in the St. Croix basin, 2000-07.




Figure 18. Average annual total nitrogen yield by model subbasin in the St. Croix basin, 2000-07.

Summary and Conclusions

Although the St. Croix National Scenic Riverway remains one of the most scenic and high-quality large rivers systems in the Upper Midwest, its water quality has been degraded by both point- and nonpoint-source pollution from its 20,000-km² basin. Lake St. Croix, the lowermost 40 km of the riverway, has been declared by both Minnesota and Wisconsin to be impaired due to eutrophication from excess phosphorus loads. Previous work has resulted in both states adopting the goal of reducing total phosphorus loads to the lake by 20% relative to loads in the 1990s. A computerized watershed model can provide a whole-basin framework for addressing this goal by integrating all loads from all sources in a mechanistic way. In particular, the model can help identify locations for implementing best management practices that could reduce nonpoint-source loads, which are the largest contributor of phosphorus to the riverway. We chose to use the SWAT modeling program, which was developed by the USDA to predict nonpoint loads of sediment and nutrients from large basins over long periods of time.

We used the ArcSWAT interface to prepare the data sets required by the SWAT program itself. A high-quality, high-density flow network from the Minnesota Department of Natural Resources (MDNR) was used in conjunction with the 30-m digital elevation model (DEM) from the U.S. Geological Survey (USGS) to delineate the St. Croix basin into 419 subbasins. The U.S. Department of Agriculture (USDA) Crop Data Layer (CDL) for 2007 served as the starting land-cover data set. However, it was modified considerably by considering all the CDL layers from 2006-10 and National Agricultural Statistics Service (NASS) tabular data for cropland. This modified land-use grid was intersected with soils from the STATSGO data layer and a slope-class (0-10% and >10%) data layer to create a total of 3028 hydrologic response units (HRUs), approximately seven per subbasin. Each HRU, having uniform land cover, soils, and slope, was modeled to have a uniform rainfall-runoff response that ultimately delivers water, sediment, and nutrients to the channel reach in that subbasin. A total of 39 lakes were explicitly included in the model, comprising most open-water bodies larger than 200 ha in area plus a few smaller reservoirs from earlier studies. Based on limited morphometric data, the lakes were provisionally parameterized to estimate stage-volume relations, sediment suspension capacity, and apparent phosphorus settling rate. Smaller open-water bodies and wetlands were modeled in a general way as aggregated conceptual depressions (SWAT ponds and wetlands) in each subbasin.

Agricultural lands were configured with a combination of spatial and tabular data from the USDA. Crops were dominated by corn, soybeans, and alfalfa, and their relative areas were broadly consistent between the spatial CDL 2007 data set and tabulated data from the National Agricultural Statistics Service (NASS). To allow for regional differences across the St. Croix, we divided the basin into four quadrants (NW, NE, SW, and SE). We could replicate the areas of the principal crops with just two rotations in each quadrant of the basin: a simple cash-crop rotation of corn and soybeans, and a livestock-feed rotation of two years of corn (one grain, one silage) followed by four years of alfalfa. Livestock numbers from NASS tables were averaged over 2000-09. Dairy cows, concentrated in the SE quadrant, dominated livestock populations in

the basin; second were beef cattle, with horses being a distant third. All other livestock species, including hogs, sheep, and poultry, were converted to animal-unit equivalents of cows, beef, or horses so that their contribution to the total phosphorus load from manure was not lost. Annual quantities of manure produced by each livestock population were calculated and applied to selected crop rotations, hay, or pasture. Application methods included daily-haul spreading, seasonal spreading, and simple grazing during the growing season. Several different application rates were incorporated into the model to allow for differences among farming practices.

Point sources in the model included 26 in Minnesota and 22 in Wisconsin. Of this total, 39 were municipal wastewater treatment plants that contributed 98% of the point-source phosphorus load, the remaining 2% coming from nine industrial dischargers. In aggregate, these wastewater treatment plants have made remarkable improvement in their discharge of phosphorus over the past 20 years. During the 1990s the annual load of total phosphorus from point sources was about 47.3 metT. By 2005-07, the load had dropped by more than half, down to 22.3 metT. Annual loads of phosphorus from wastewater were estimated back to 1900 (with data from Edlund et al., 2009b), should the model be run that far back in time.

Climate data were compiled from data downloaded from the National Climatic Data Center (NCDC) for the 1960-2009 period. Daily precipitation and temperature data from 25 weather stations from in or near the St. Croix basin were spatially interpolated and applied to 114 weather pseudo-stations across the basin, each of which corresponds to three or four subbasins in the SWAT model.

The model was calibrated to observed data for 2000-07 and validated to data for 1990-99. Calibration of monthly flows was based on data from two main-stem stations (Danbury and St. Croix Falls) and from three tributary stations (Kettle, Snake, and Apple rivers), with excellent model fits. Monthly loads of sediment and nutrients were calibrated based on data at a single main-stem station at Stillwater, MN, with acceptable model fits for both suspended sediment and total phosphorus. The calibrated model represents a whole-basin framework available for understanding the source of nonpoint pollutants in the basin and their transport to receiving waters. It furthermore can estimate changes in the loads of these pollutants caused by changes in land use or climate. In short, the model offers the most comprehensive whole-basin tool available for identifying where problems exist on the landscape, what new problems may arise as land is developed and climate changes, and which best-management practices are most likely to be effective in reducing nonpoint-source pollution. The SWAT model is thus a critical element in management efforts to improve and protect the water resources of the St. Croix basin.

Acknowledgements

We thank the St. Croix Basin Water Resources Planning Team for continued guidance during the course of this project. This interagency team of federal, state, and local agencies is exemplary for its accomplishments and cooperation. For technical assistance and insight, we thank the members of the Midwest Watershed Modeling User Group; identifying model problems and creating solutions to those problems has been a joint effort of this group for the past several years. Discussions with Adam Freihoefer (Wisconsin Department of Natural Resources), Marylee Murphy (Three Rivers Park District, MN), Pat Oldenburg (Wisconsin Department of Natural Resources), and Paul Baumgart (University of Wisconsin Green Bay) have been especially helpful.

Direct funding for this project was provided by the National Park Service, with matching funds provided by the Metropolitan Council of Minnesota and the Minnesota Pollution Control Agency.

References

- Almendinger, J.E., and Murphy, M.S. 2007. Constructing a SWAT model of the Willow River watershed, western Wisconsin. Final report to the Legislative Commission on Minnesota Resources, National Park Service, and Wisconsin Department of Natural Resources. St. Croix Watershed Research Station, Science Museum of Minnesota, 84 pp.
- Almendinger, J.E., Murphy, M.S. and Ulrich, J.S. 2014. Use of the Soil and Water Assessment Tool to scale sediment delivery from field to watershed in an agricultural landscape with topographic depressions. *Journal of Environmental Quality*, 43: 9-17.
- Almendinger, J.E., and Ulrich, J. 2010. Constructing a SWAT model of the Sunrise River watershed, eastern Minnesota. Final report to the National Park Service and the Minnesota Pollution Control Agency. St. Croix Watershed Research Station, Science Museum of Minnesota, 63 p.
- Almendinger, J.E., and Ulrich, J. 2012. Applying a SWAT model of the Sunrise River watershed, eastern Minnesota, to predict water-quality impacts from land-use changes. Final report to the Minnesota Pollution Control Agency. St. Croix Watershed Research Station, Science Museum of Minnesota, 41 p.
- Arnold, J.G., Kiniry, J.R., Srinivasan, R., Williams, J.R., Haney, E.B., and Neitsch, S.L. 2013. Soil and Water Assessment Tool Input/Output Documentation, Version 2012. U.S. Department of Agriculture Agricultural Research Service (USDA/ARS) and Texas AgriLife Research. Texas Water Resources Institute Technical Report No. 439, Texas A&M Univ., College Station, TX, 654 p.
- Arnold, J.G., Srinivasan, R., Muttiah, R.S., and Williams, J.R. 1998. Large area hydrologic modeling and assessment part I: Model development. *Journal of the American Water*

- Resources Association (JAWRA) 34(1): 73-89.
- ASCE (American Society of Civil Engineers). 1993. Criteria for evaluation of watershed models. *Journal of Irrigation and Drainage Engineering* 119(3): 429-442.
- ASAE (American Society of Agricultural Engineers). 1998. Manure production and characteristics, p. 646-648 in ASAE Standards 1998, 45th edition, Section D384.1. ASAE, St. Joseph. As cited by Arnold et al. 2011.
- Borah, D.K. and Bera, M. 2004. Watershed-scale hydrologic and nonpoint-source pollution models: Review of applications. *Transactions of the American Society of Agricultural Engineers (ASAE)* 47(3): 789-803.
- Blumentritt, D.J., Wright, H.E., Jr. and Stefanova, V. 2009. Formation and early history of Lakes Pepin and St. Croix of the upper Mississippi River. *Journal of Paleolimnology* 41(4): 545-562.
- Brett, M.T., and Benjamin, M.M. 2008. A review and reassessment of lake phosphorus retention and the nutrient loading concept. *Freshwater Biology* 53:194-211.
- Chapra, S.C. 1997. *Surface water-quality modeling*. McGraw-Hill, New York. As cited by Panuska and Robertson (1999).
- Chu, T.W. and Shirmohammadi, A. 2004. Evaluation of the SWAT model's hydrology component in the piedmont physiographic region of Maryland. *Transactions of the American Society of Agricultural Engineers (ASAE)* 47(4): 1057-1073.
- Coffin, B., and Pfannmuller, L. 1988. *Minnesota's Endangered Flora and Fauna*. University of Minnesota Press, Minneapolis, MN, 473 p.
- Cummins, J.F. and Grigal, D.F. 1981. *Legend to Map – Soils and Land Surfaces of Minnesota 1980*. Soil Series No. 110, Miscellaneous Publication 11. Department of Soil Science, Univ. of Minnesota, Agricultural Experiment Station, St. Paul, MN, 59 p.
- Edlund, M.B., Engstrom, D.R., Triplett, L.D., Lafrancois, B.M. and Leavitt, P.R. 2009a. Twentieth century eutrophication of the St. Croix River (Minnesota-Wisconsin, USA) reconstructed from the sediments of its natural impoundment. *Journal of Paleolimnology* 41(4): 641-657.
- Edlund, M.B., Triplett, L.D., Tomasek, M.D. and Bartilson, K. 2009b. From paleo to policy: partitioning the historical point and nonpoint phosphorus loads to the St. Croix River, Minnesota-Wisconsin, USA. *Journal of Paleolimnology* 41(4): 679-689.
- ESRI (Environmental Systems Research Institute). 2012. *ArcGIS Desktop: Release 10.1 (build 3035)*. Redlands, CA.
- Geza, M. and McCray, J.E. 2008. Effects of soil data resolution on SWAT model stream flow and water quality predictions. *Journal of Environmental Management* 88: 393-406.
- Gupta, H.V., Sorooshian, S., and Yapo, P.O. 1999. Status of automatic calibration for hydrologic models: Comparison with multilevel expert calibration. *Journal of Hydrologic Engineering* 4(2): 135-143.
- Hadley, D.W. and Pelham, J.H. 1976. *Glacial deposits of Wisconsin*. Wisconsin Geological and

Natural History Survey Map Series No. 10.

- Higgins, J.M., and Kim, B.R. 1981. Phosphorus retention models for Tennessee Valley Authority Reservoirs. *Water Resources Research* 17(3): 571-576.
- Hobbs H.C. and Goebel J.E. 1982. *Geologic Map of Minnesota, Quaternary Geology, Map S-1*. Minnesota Geological Survey, St. Paul, MN.
- Holmberg, K.L., Perry, J., Ferrin, R.S. and Sharrow, D.L. 1997. *Water Resources Management Plan-St. Croix National Scenic Riverway*. 155 p. + appendices.
- Krause, P., Boyle, D.P., and Base, F. 2005. Comparison of different efficiency criteria for hydrological model assessment. *Advances in Geosciences* 5: 89-97.
- Legates, D.R., and McCabe, G.J., Jr. 1999. Evaluating the use of “goodness-of-fit” measures in hydrologic and hydroclimatic model validation. *Water Resources Research* 35(1): 233-241.
- Lenz, B.N., Robertson, D.M., Fallon, J.D., and Ferrin, R. 2003. Nutrient and suspended-sediment loads and benthic invertebrate data for tributaries to the St. Croix River, Wisconsin and Minnesota, 1997-99: U.S. Geological Survey Water-Resources Investigations Report 01-4162, 57 pp.
- Lorenz, D.L., Sanocki, C.A., and Kocian, M.J. 2010. Techniques for estimating the magnitude and frequency of peak flows on small streams in Minnesota based on data through water year 2005: U.S. Geological Survey Scientific Investigations Report 2009-5250, 54 p.
- Magdalene, S. 2009. *Lake St. Croix Total Phosphorus Loading Study*. Report to St. Croix Basin Water Resources Planning Team. St. Croix Watershed Research Station, Science Museum of Minnesota, 43 pp. plus appendices.
- MCES (Metropolitan Council Environmental Services). 2011. *Environmental Information Management System (EIMS)*. Accessed 2011 at <http://es.metc.state.mn.us/eims>.
- MDNR (Minnesota Department of Natural Resources). 2010. *The DNR Data Deli*. Accessed 2010 from <http://deli.dnr.state.mn.us>.
- Moriasi, D.N., Arnold, J.G., Van Liew, M.W., Bingner, R.L., Harmel, R.D. and Veith, T.L. 2007. Model evaluation guidelines for systematic quantification of accuracy in watershed simulations. *Transactions of the ASABE (American Society of Agricultural and Biological Engineers)*, 50(3): 885-900.
- MPCA (Minnesota Pollution Control Agency) and WDNR (Wisconsin Department of Natural Resources). 2012. *Lake St. Croix Nutrient Total Maximum Daily Load*. Minnesota Pollution Control Agency and Wisconsin Department of Natural Resources, with St. Croix Basin Water Resources Planning Team, Science Museum of Minnesota St. Croix Watershed Research Station, and Barr Engineering Company, Report wq-iw6-04e. St. Paul, MN, 93 p.
- Nash, J.E., and Sutcliffe, J.V. 1970. River flow forecasting through conceptual models: Part I – A discussion of principles. *Journal of Hydrology* 10: 282-290.
- NASS (National Agricultural Statistics Service). 2009, 2010. *Crop data* accessed 2009 and

- livestock data accessed 2010 from http://www.nass.usda.gov/Data_and_Statistics/.
- NASS (National Agricultural Statistics Service). 2011. Minnesota and Wisconsin Cropland Data Layers, 2006-10. U.S. Department of Agriculture. Accessed 2011 from <http://nassgeodata.gmu.edu/CropScape/>.
- NCDC (National Climatic Data Center). 2010. Cooperative station data online. Accessed 2010 from <http://www.ncdc.noaa.gov/oa/ncdc.html>.
- NCDC (National Climatic Data Center). 2011. Climate Data Online. Accessed 2011 from <http://cdo.ncdc.noaa.gov/climatenormals/clim60/states>.
- NDSU (North Dakota State University) Agriculture and University Extension. 1987. Equivalent weights of grain and oilseeds. Publication AE-945, 3 p.
- Neitsch, S.L., Arnold, J.G., Kiniry, J.R., and Williams, J.R. 2011. Soil and Water Assessment Tool Theoretical Documentation, Version 2009. U.S. Department of Agriculture Agricultural Research Service (USDA/ARS) and Texas AgriLife Research. Texas Water Resources Institute Technical Report No. 406, Texas A&M Univ., College Station, TX, 618 p.
- NPS (National Park Service). 1995. Interpretive Prospectus: St. Croix National Scenic Riverway, Minnesota/Wisconsin.
- NRCS (Natural Resources Conservation Service). 2007. Chapter 7: Hydrologic Soils Groups. Part 630, National Engineering Handbook. 210-VI-NEH. U.S. Department of Agriculture, 5 p.
- NRCS (Natural Resource Conservation Service). 2008a. U.S. General Soil Map (State Soil Geographic Database, STATSGO) for Minnesota. U.S. Department of Agriculture. Accessed 2010 at <http://soildatamart.nrcs.usda.gov>.
- NRCS (Natural Resource Conservation Service). 2008b. Soil Survey Geographic (SSURGO) Database for Anoka, Chisago, and Washington counties, Minnesota. U.S. Department of Agriculture. Accessed 2010 at <http://soildatamart.nrcs.usda.gov>.
- Panuska, J.C., and Roberston, D.M. 1999. Estimating phosphorus concentrations following alum treatment using apparent settling velocity. *Journal of Lake and Reservoir Management* 15(1): 28-38.
- Robertson, D.M. and Lenz, B.N. 2002. Response of the St. Croix River pools, Wisconsin and Minnesota, to various phosphorus-loading scenarios. U.S. Geological Survey, Water-Resources Investigations Report 02-4181, 36 pp.
- SCBWRPT (St. Croix Basin Water Resources Planning Team). 2004. St. Croix Basin Phosphorus-Based Water-Quality Goals. Minnesota Pollution Control Agency, Report wq-b6-01. St. Paul, 28 p.
- Schroeder, J.W. 2004. Corn silage management. North Dakota State University (NDSU) Agriculture and University Extension, Publication AS-1253.
- Sevat, E., and Dezetter, A. 1991. Selection of calibration objective functions in the context of rainfall-runoff modeling in a Sudanese savannah area. *Hydrological Sciences Journal*

36(4): 307-330.

- Singh, J., H. V. Knapp, and M. Demissie. 2004. Hydrologic modeling of the Iroquois River watershed using HSPF and SWAT. ISWS CR 2004-08. Champaign, Ill.: Illinois State Water Survey. As cited by Moriasi et al. (2007). Available at: www.sws.uiuc.edu/pubdoc/CR/ISWSCR2004-08.pdf. Accessed December 2011.
- Thiel, C. 2009. Pollutant loading to the St. Croix River: Chisago County's contribution. Chisago Soil and Water Conservation District report. 29 p.
- Triplett, L.D., Engstrom, D.R. and Edlund, M.B. 2009. A whole-basin stratigraphic record of sediment and phosphorus loading to the St. Croix River, USA. *Journal of Paleolimnology* 41 (4): 659-677.
- U.S. Census Bureau. 2011. Census Bureau Home Page. Accessed 2011 from <http://www.census.gov>.
- USDA (U.S. Department of Agriculture). 2004. 2002 Census of Agriculture. United States, Summary and State Data. Volume 1: Geographic Area Series Part 51 (AC-02-A-51), 563 p. plus appendices.
- USDA (U.S. Department of Agriculture). 2009. 2007 Census of Agriculture. United States, Summary and State Data. Volume 1: Geographic Area Series Part 51, 639 p. plus appendices.
- USGS (U.S. Geological Survey). 2010. Seamless Data Distribution System, Earth Resources Observation and Science (EROS). Accessed 2010 at <http://seamless.usgs.gov/>.
- UWEX (University of Wisconsin-Extension). 2002. Pastures for profit: a guide to rotational grazing. Report A3529, 38 p.
- Vazquez-Amabile, G.G., and Engel, B.A. 2005. Use of SWAT to compute groundwater table depth and streamflow in the Muscatatuck River watershed. *Transactions of the ASAE (American Society of Agricultural Engineers)* 48(3): 991-1003.
- Vaughn, S.R. 2010. DNR Watershed Delineation: Project History, Methodology, Terminology & Data Attribution. Draft manuscript. Minnesota Department of Natural Resources - Waters.
- Vollenweider R.A. 1975. Input-output models with special reference to the phosphorus loading concept in limnology. *Schweizerische Zeitschrift fur Hydrologie* 37: 53-84. As cited by Brett and Benjamin (2008).
- Vollenweider R.A. 1976. Advances in defining critical loading levels for phosphorus in lake eutrophication. *Memorie dell'Istituto Italiano di Idrobiologia* 33: 53-83. As cited by Brett and Benjamin (2008).
- Waters, T.F. 1977. *The Streams and Rivers of Minnesota*. University of Minnesota Press, Minneapolis, MN, 373 p.
- WDNR (Wisconsin Department of Natural Resources). 2009. Wisconsin Lakes. WDNR Publication PUB-FH-800, 180 pp.
- Winchell, M., Srinivasan, R., Di Luzio, M., and Arnold, J. 2013. ArcSWAT Interface for SWAT2012 User's Guide. Blackland Research and Extension Center, Texas AgriLife

- Research, Temple, TX; and Grassland, Soil and Water Research Laboratory, USDA Agricultural Research Service, Temple, TX. 459 p.
- Wright Jr., H.E. 1972. Quaternary history of Minnesota. In: Sims, P.K. and Morey, G.B. (Editors). *Geology of Minnesota: A Centennial Volume*. Minnesota Geological Survey, pp. 515–578.
- Wright, H.E., Jr., Lease, K. and Johnson, S. 1998. Glacial River Warren, Lake Pepin, and the environmental history of southeastern Minnesota. In: C.J. Patterson and H.E. Wright, Jr. (Editors). *Contributions to Quaternary studies in Minnesota: Minnesota Geological Survey Report of Investigations 49*. Minnesota Geological Survey, St. Paul, MN, pp. 131-140.
- Zhang, X. and Srinivasan, R. 2009. GIS-based spatial precipitation estimation: a comparison of geostatistical approaches. *Journal of the American Water Resources Association (JAWRA)* 45(4):894-906.
- Zumberge, J.H. 1952. The lakes of Minnesota -- their origin and classification. *Minnesota Geological Survey Bulletin* 35, 99 p.

Appendix A: Specific Crop Rotations
Tables A1 – A10

Table A1. Corn-soybean (CS) cash-crop rotation.

Rotation Name:		CS_a									
Year	Date	Operation	Item	Rate Units	Rate Units	N (kg/ha)	P (kg/ha)	N (lb/acre)	P (lb/acre)	Notes	
Year 1	21-Apr	Fertilize	46-0-0	300 lb/acre	337 kg/ha	155	138	138	138	NSTR=0.99, EFF=2, NMXS=30, LY1=1, NMXA=155.02	
	26-Apr	Till	Disk								
	1-May	Plant	Corn-Grain							CNOP A = 67, B = 77, C = 83, D = 87	
	1-May	Fertilize	27-15-15	200 lb/acre	225 kg/ha	61	54	54	54	13 LY1 = 0	
	28-Oct	Harvest&Kill	Corn-Grain								
Year 2	23-Apr	Till	Chisel								
	10-May	Fertilize	9-23-30	200 lb/acre	225 kg/ha	20	18	18	18	20 LY1 = 0	
	15-May	Till	Disk								
	20-May	Plant	Soybeans							CNOP A = 67, B = 78, C = 85, D = 89	
	15-Oct	Harvest&Kill	Soybeans								
	31-Oct	Till	Chisel								
Nutrient additions:											
	Year 1					216	15	15	192	13	
	Year 2					20	23	23	18	20	
	Annual average					118	19	19	105	17	

NOTES:
 Basic rotation is corn-grain / soybean. Two subrotations (CS_a and CS_b) were created with the initial year being either corn or soybeans, to maintain spatial coverage of crops in the basin in any one year. Subrotations were further modified to set curve numbers (CNOPs) according to the crop planted that year and hydrologic soil group (A, B, C, or D).

Table A2. Corn-alfalfa (CA) rotation without manure application.

Rotation Name:		CA_a									
Year	Date	Operation	Item	Rate Units	N (kg/ha)	P (kg/ha)	N (lb/acre)	P (lb/acre)	Notes		
Year 1	18-Apr	Fertilize	46-0-0	337 kg/ha	155	138			NSTR=0.99, EFF=2, NMXS=30, LY1=1, NMXA=155.02		
	26-Apr	Till	Disk								
	1-May	Plant	Com-Grain						CNOP A = 67, B = 77, C = 83, D = 87		
	1-May	Fertilize	27-15-15	225 kg/ha	61	54	15	54	13 LY1 = 0		
	28-Oct	Harvest&Kill	Com-Grain								
	15-Nov	Till	Chisel								
Year 2	18-Apr	Fertilize	46-0-0	337 kg/ha	155	138			NSTR=0.99, EFF=2, NMXS=30, LY1=1, NMXA=155.02		
	26-Apr	Till	Disk								
	1-May	Plant	Com-Silage						CNOP A = 67, B = 77, C = 83, D = 87		
	1-May	Fertilize	27-15-15	225 kg/ha	61	54	15	54	13 LY1 = 0		
	25-Sept	Harvest&Kill	Com-Silage								
	5-Nov	Till	Chisel								
Year 3	16-Apr	Till	Disk								
	23-April	Plant	Alfalfa						CNOP A = 31, B = 59, C = 72, D = 79		
	5-Sep	Harvest	Alfalfa								
	25-Jun	Harvest	Alfalfa								
	1-Aug	Harvest	Alfalfa								
	10-Sep	Harvest	Alfalfa								
	25-Jun	Harvest	Alfalfa								
	1-Aug	Harvest	Alfalfa								
	10-Sep	Harvest	Alfalfa								
	5-Jul	Harvest	Alfalfa								
	5-Sep	Harvest	Alfalfa								
	1-Nov	Till	Moldboard plow								
Nutrient additions:											
Year 1					216	15	192	13			
Year 2					216	15	192	13			
Year 3					0	0	0	0			
Year 4					0	0	0	0			
Year 5					0	0	0	0			
Year 6					0	0	0	0			
Annual average					72	5	64	4			

NOTES:
 Basic rotation is corn-grain / corn-silage / alfalfa / alfalfa / alfalfa. Three subrotations (CA_a, CA_b, and CA_c) were created with the initial year being either corn-grain, year-1 alfalfa, or year-3 alfalfa to maintain spatial coverage of corn versus alfalfa in the basin in any one year. Subrotations were further modified to set curve numbers (CNOPs) according to the crop planted that year and hydrologic soil group (A, B, C, or D).

Table A3. Corn-alfalfa (CA) rotation with seasonal manure application.

Rotation Name:		CAseas_a							
Year	Date	Operation	Item	Rate Units	N (kg/ha)	P (kg/ha)	N (lb/acre)	P (lb/acre)	Notes
Year 1	18-Apr	Fertilize	46-0-0	112 kg/ha	52	46	46	46	NSTR=0.99, EFF=2, NMXS=30, LY1=1, NMXA=155.02
	21-Apr	Fertilize	Dairy manure	4700 kg/ha	179	38	159	33	
	26-Apr	Till	Disk						
	1-May	Plant	Corn-Grain	225 kg/ha	61	15	54	13	CNOP A = 67, B = 77, C = 83, D = 87 LY1 = 0
	1-May	Fertilize	27-15-15						
	28-Oct	Harvest&Kill	Corn-Grain	4700 kg/ha	179	38	159	33	
	1-Nov	Fertilize	Dairy manure						
	15-Nov	Till	Chisel						
Year 2	18-Apr	Fertilize	46-0-0	112 kg/ha	52	46	46	46	NSTR=0.99, EFF=2, NMXS=30, LY1=1, NMXA=155.02
	21-Apr	Fertilize	Dairy manure	4700 kg/ha	179	38	159	33	
	26-Apr	Till	Disk						
	1-May	Plant	Corn-Silage	225 kg/ha	61	15	54	13	CNOP A = 67, B = 77, C = 83, D = 87 LY1 = 0
	1-May	Fertilize	27-15-15						
	25-Sept	Harvest&Kill	Corn-Silage	4700 kg/ha	179	38	159	33	
	1-Nov	Fertilize	Dairy manure						
	15-Nov	Till	Chisel						
Year 3	16-Apr	Till	Disk						
	23 April	Plant	Alfalfa						
	5-Sep	Harvest	Alfalfa						
Year 4	25-Jun	Harvest	Alfalfa						
	1-Aug	Harvest	Alfalfa						
	10-Sep	Harvest	Alfalfa						
Year 5	25-Jun	Harvest	Alfalfa						
	1-Aug	Harvest	Alfalfa						
	10-Sep	Harvest	Alfalfa						
Year 6	5-Jul	Harvest	Alfalfa						
	5-Sep	Harvest	Alfalfa						
	1-Nov	Till	Moldboard plow						
Manure application rates and nutrient additions:				Manure rate:	Nutrient totals, inorganic fertilizer plus manure:				
Year 1				9400 kg/ha	469	90	418	80	
Year 2				9400 kg/ha	469	90	418	80	
Year 3				0	0	0	0	0	
Year 4				0	0	0	0	0	
Year 5				0	0	0	0	0	
Year 6				0	0	0	0	0	
Annual average				3133 kg/ha	156	30	139	27	

NOTES:
 Basic rotation is corn-grain / corn-silage / alfalfa / alfalfa / alfalfa. Three subrotations (CA_a, CA_b, and CA_c) were created with the initial year being either corn-grain, year-1 alfalfa, or year-3 alfalfa to maintain spatial coverage of corn versus alfalfa in the basin in any one year. Subrotations were further modified to set curve numbers (CNOPs) according to the crop planted that year and hydrologic soil group (A, B, C, or D).

Table A4. Corn-alfalfa (CA) rotation with daily-haul manure applications, simplified as monthly applications (years 1-4).

Rotation Name: CAAdh_a										
Year	Date	Operation	Item	Rate Units	Rate Units	N (kg/ha)	P (kg/ha)	N (lb/acre)	P (lb/acre)	Notes
Year 1	15-Jan, Feb, Mar, Apr	Fertilize	Dairy manure	1200 kg/ha, dry	3.82 sh T/acre, fresh	10	46	10	41	9 LY1 = 1
	18-Apr	Fertilize	46-0-0	112 kg/ha	100 lb/acre		52		46	NSTR=0.99, EFF=2, NMXS=30, LY1=1, NMXA=155.02
Year 2	26-Apr	Till	Disk							
	1-May	Plant	Corn-Grain							
	1-May	Fertilize	27-15-15							
	28-Oct	Harvest&Kill	Corn-Grain	225 kg/ha	200 lb/acre	15	61	15	54	CNOP A = 67, B = 77, C = 83, D = 87 13 LY1 = 0
	5-Nov	Till	Chisel							
Year 2	15-Nov, Dec	Fertilize	Dairy manure	1200 kg/ha, dry	3.82 sh T/acre, fresh	10	46	10	41	9 LY1 = 1
	15-Jan, Feb, Mar, Apr	Fertilize	Dairy manure	1200 kg/ha, dry	3.82 sh T/acre, fresh	10	46	10	41	9 LY1 = 1
	18-Apr	Fertilize	46-0-0	112 kg/ha	100 lb/acre		52		46	NSTR=0.99, EFF=2, NMXS=30, LY1=1, NMXA=155.02
	26-Apr	Till	Disk							
Year 3	1-May	Plant	Corn-Silage							
	1-May	Fertilize	27-15-15							
	25-Sept	Harvest&Kill	Corn-Silage	225 kg/ha	200 lb/acre	15	61	15	54	CNOP A = 67, B = 77, C = 83, D = 87 13 LY1 = 0
	5-Nov	Till	Chisel							
	15-Nov, Dec	Fertilize	Dairy manure	1200 kg/ha, dry	3.82 sh T/acre, fresh	10	46	10	41	9 LY1 = 1
Year 3	15-Jan, Feb, Mar, Apr	Fertilize	Dairy manure	1200 kg/ha, dry	3.82 sh T/acre, fresh	10	46	10	41	9 LY1 = 1
	20-Apr	Till	Disk							
	23-Apr	Plant	Alfalfa							
	5-Sep	Harvest	Alfalfa							
Year 4	15-Sep, Oct, Nov, Dec	Fertilize	Dairy manure	1200 kg/ha, dry	3.82 sh T/acre, fresh	10	46	10	41	9 LY1 = 1
	15-Jan, Feb, Mar, Apr, May, Jun	Fertilize	Dairy manure	1200 kg/ha, dry	3.82 sh T/acre, fresh	10	46	10	41	9 LY1 = 1
	25-Jun	Harvest	Alfalfa							
	15-Jul	Fertilize	Dairy manure	1200 kg/ha, dry	3.82 sh T/acre, fresh	10	46	10	41	9 LY1 = 1
	1-Aug	Harvest	Alfalfa							
	15-Aug	Fertilize	Dairy manure	1200 kg/ha, dry	3.82 sh T/acre, fresh	10	46	10	41	9 LY1 = 1
	10-Sep	Harvest	Alfalfa							
15-Sep, Oct, Nov, Dec	Fertilize	Dairy manure	1200 kg/ha, dry	3.82 sh T/acre, fresh	10	46	10	41	9 LY1 = 1	

Table A4. Continued (yers 5-6)

Rotation Name: CAdh_a										
Year	Date	Operation	Item	Rate Units	Rate Units	N (kg/ha)	P (kg/ha)	N (lb/acre)	P (lb/acre)	Notes
Year 5	15-Jan, Feb, Mar, Apr, May, Jun	Fertilize	Dairy manure	1200 kg/ha, dry	3.82 sh T/acre, fresh	46	10	41	41	9 LY1 = 1
	25-Jun	Harvest	Alfalfa							
	15-Jul	Fertilize	Dairy manure	1200 kg/ha, dry	3.82 sh T/acre, fresh	46	10	41	41	9 LY1 = 1
	10-Aug	Harvest	Alfalfa							
	15-Aug	Fertilize	Dairy manure	1200 kg/ha, dry	3.82 sh T/acre, fresh	46	10	41	41	9 LY1 = 1
	10-Sep	Harvest	Alfalfa							
	15-Sep, Oct, Nov, Dec	Fertilize	Dairy manure	1200 kg/ha, dry	3.82 sh T/acre, fresh	46	10	41	41	9 LY1 = 1
Year 6	15-Jan, Feb, Mar, Apr, May, Jun	Fertilize	Dairy manure	1200 kg/ha, dry	3.82 sh T/acre, fresh	46	10	41	41	9 LY1 = 1
	5-Jul	Harvest	Alfalfa							
	15-Jul, Aug	Fertilize	Dairy manure	1200 kg/ha, dry	3.82 sh T/acre, fresh	46	10	41	41	9 LY1 = 1
	5-Sep	Harvest	Alfalfa							
	15-Sep, Oct	Fertilize	Dairy manure	1200 kg/ha, dry	3.82 sh T/acre, fresh	46	10	41	41	9 LY1 = 1
	1-Nov	Till	Moldboard plow							
	15-Nov, Dec	Fertilize	Dairy manure	1200 kg/ha, dry	3.82 sh T/acre, fresh	46	10	41	41	9 LY1 = 1
Manure application rates and nutrient additions:										
	Year 1	Manure rate:			Nutrient totals, inorganic fertilizer plus manure:					
		7200 kg/ha, dry		22.90 sh T/acre, fresh	386	72	344	344	344	65
	Year 2	7200 kg/ha, dry		22.90 sh T/acre, fresh	386	72	344	344	344	65
	Year 3	9600 kg/ha, dry		30.54 sh T/acre, fresh	365	77	325	325	325	68
	Year 4	14400 kg/ha, dry		45.81 sh T/acre, fresh	547	115	487	487	487	103
	Year 5	14400 kg/ha, dry		45.81 sh T/acre, fresh	547	115	487	487	487	103
	Year 6	14400 kg/ha, dry		45.81 sh T/acre, fresh	547	115	487	487	487	103
	Annual average	11200 kg/ha, dry		36 sh T/acre, fresh	463	95	412	412	412	84

NOTES: Basic rotation is corn-grain / corn-silage / alfalfa / alfalfa / alfalfa. Three subrotations (CA_a, CA_b, and CA_c) were created with the initial year being either corn-grain, year-1 alfalfa, or year-3 alfalfa to maintain spatial coverage of corn versus alfalfa in the basin in any one year. Subrotations were further modified to set curve numbers (CNOs) according to the crop planted that year and hydrologic soil group (A, B, C, or D).

Table A5. Grazing rotation for dairy cows in grassland.

Rotation Name:		DPAST								
Year	Date	Operation	Item	Rate Units	Rate Units	N (kg/ha/day)	P (kg/ha/day)	N (lb/acre/day)	P (lb/acre/day)	Notes
Year 1	12-May	Graze start	Pasture (PAST) Dairy manure	4.50 kg/ha/d, dry	28.73 lbs/acre/d, fresh	0.17	0.04	0.15	0.03	Begin with perennial PAST land-cover type BMEAT = 9.36 kg/ha/day BMTRMP = 1.87 kg/ha/day
	28-Oct	Graze end	Dairy	169 days						
Annual manure and nutrient application rates:				Manure rate: (kg/ha/yr, dry)	Manure rate: (sh T/acre/yr, fresh)	N (kg/ha/yr)	P (kg/ha/yr)	N (lb/acre/yr)	P (lb/acre/yr)	
				761	2.43	29	6	26	5	

Table A6. Rotation for dairy cows in paddock or barnyard area, simplified as monthly applications.

Rotation Name:		DPADD								
Year	Date	Operation	Item	Rate Units	Rate Units	N (kg/ha)	P (kg/ha)	N (lb/acre)	P (lb/acre)	Notes
Year 1	15-Jan	Fertilize	Dairy manure	1100 kg/ha, dry	3.51 sh T/acre, fresh	42	9	37	8	LY1 = 1
	15-Feb	Fertilize	Dairy manure	1100 kg/ha, dry	3.51 sh T/acre, fresh	42	9	37	8	LY1 = 1
	15-Mar	Fertilize	Dairy manure	1100 kg/ha, dry	3.51 sh T/acre, fresh	42	9	37	8	LY1 = 1
	15-Apr	Fertilize	Dairy manure	1100 kg/ha, dry	3.51 sh T/acre, fresh	42	9	37	8	LY1 = 1
	15-May	Fertilize	Dairy manure	1100 kg/ha, dry	3.51 sh T/acre, fresh	42	9	37	8	LY1 = 1
	15-Jun	Fertilize	Dairy manure	1100 kg/ha, dry	3.51 sh T/acre, fresh	42	9	37	8	LY1 = 1
	15-Jul	Fertilize	Dairy manure	1100 kg/ha, dry	3.51 sh T/acre, fresh	42	9	37	8	LY1 = 1
	15-Aug	Fertilize	Dairy manure	1100 kg/ha, dry	3.51 sh T/acre, fresh	42	9	37	8	LY1 = 1
	15-Sep	Fertilize	Dairy manure	1100 kg/ha, dry	3.51 sh T/acre, fresh	42	9	37	8	LY1 = 1
	15-Oct	Fertilize	Dairy manure	1100 kg/ha, dry	3.51 sh T/acre, fresh	42	9	37	8	LY1 = 1
	15-Nov	Fertilize	Dairy manure	1100 kg/ha, dry	3.51 sh T/acre, fresh	42	9	37	8	LY1 = 1
	15-Dec	Fertilize	Dairy manure	1100 kg/ha, dry	3.51 sh T/acre, fresh	42	9	37	8	LY1 = 1
Annual manure and nutrient application rates:				Manure rate: (kg/ha/yr, dry)	Manure rate: (sh T/acre/yr, fresh)	N (kg/ha/yr)	P (kg/ha/yr)	N (lb/acre/yr)	P (lb/acre/yr)	
				13200	42.13	502	106	447	94	

Table A7. Grazing rotation for beef cattle in grassland.

Rotation Name: BPAST										
Year	Date	Operation	Item	Rate Units	Rate Units	N (kg/ha/day)	P (kg/ha/day)	N (lb/acre/day)	P (lb/acre/day)	Notes
Year 1	12-May	Grazing start	Pasture (PAST)	4.75 kg/ha/d, dry	28.87 lbs/acre/d, fresh	0.19	0.05	0.17	0.05	Begin with perennial PAST land-cover type
	28-Oct	Grazing end	Beef	169 days						BMEAT = 13.98 kg/ha/day BMTTMP = 2.80 kg/ha/day
Annual manure and nutrient application rates:										
				Manure rate:	Manure rate:	Nutrient additions:				
				(kg/ha/yr, dry)	(sh T/acre/yr, fresh)	(kg/ha/yr)	(kg/ha/yr)	(lb/acre/yr)	(lb/acre/yr)	(lb/acre/yr)
				803	2.44	32	9	29	8	8

Table A8. Rotation for beef cattle in paddock or barnyard area, simplified as monthly applications.

Rotation Name: BPADD											
Year	Date	Operation	Item	Rate Units	Rate Units	N (kg/ha)	P (kg/ha)	N (lb/acre)	P (lb/acre)	Notes	
Year 1	15-Jan	Fertilize	Beef manure	1550 kg/ha, dry	4.71 sh T/acre, fresh	62	17	55	55	15 LY1 = 1	
	15-Feb	Fertilize	Beef manure	1550 kg/ha, dry	4.71 sh T/acre, fresh	62	17	55	55	15 LY1 = 1	
	15-Mar	Fertilize	Beef manure	1550 kg/ha, dry	4.71 sh T/acre, fresh	62	17	55	55	15 LY1 = 1	
	15-Apr	Fertilize	Beef manure	1550 kg/ha, dry	4.71 sh T/acre, fresh	62	17	55	55	15 LY1 = 1	
	15-May	Fertilize	Beef manure	1550 kg/ha, dry	4.71 sh T/acre, fresh	62	17	55	55	15 LY1 = 1	
	15-Jun	Fertilize	Beef manure	1550 kg/ha, dry	4.71 sh T/acre, fresh	62	17	55	55	15 LY1 = 1	
	15-Jul	Fertilize	Beef manure	1550 kg/ha, dry	4.71 sh T/acre, fresh	62	17	55	55	15 LY1 = 1	
	15-Aug	Fertilize	Beef manure	1550 kg/ha, dry	4.71 sh T/acre, fresh	62	17	55	55	15 LY1 = 1	
	15-Sep	Fertilize	Beef manure	1550 kg/ha, dry	4.71 sh T/acre, fresh	62	17	55	55	15 LY1 = 1	
	15-Oct	Fertilize	Beef manure	1550 kg/ha, dry	4.71 sh T/acre, fresh	62	17	55	55	15 LY1 = 1	
	15-Nov	Fertilize	Beef manure	1550 kg/ha, dry	4.71 sh T/acre, fresh	62	17	55	55	15 LY1 = 1	
	15-Dec	Fertilize	Beef manure	1550 kg/ha, dry	4.71 sh T/acre, fresh	62	17	55	55	15 LY1 = 1	
Annual manure and nutrient application rates:											
				Manure rate:	Manure rate:	Nutrient additions:					
				(kg/ha/yr, dry)	(sh T/acre/yr, fresh)	(kg/ha/yr)	(kg/ha/yr)	(lb/acre/yr)	(lb/acre/yr)	(lb/acre/yr)	
				18600	56.53	744	205	663	182	182	

Table A9. Grazing rotation for horses in grassland.

Rotation Name: HPAST										
Year	Date	Operation	Item	Rate Units	Rate Units	N (kg/ha/day)	P (kg/ha/day)	N (lb/acre/day)	P (lb/acre/day)	Notes
Year 1	12-May	Graze start	Pasture (PAST) Horse manure	5.50 kg/ha/d, dry	16.66 lbs/acre/d, fresh	0.11	0.02	0.10	0.02	Begin with perennial PAST land-cover type 0.02 BMEAT = 9.36 kg/ha/day BMTRMP = 1.87 kg/ha/day
	28-Oct	Graze end	Horse	169 days						
Annual manure and nutrient application rates:										
				Manure rate: (kg/ha/yr, dry)	Manure rate: (sh T/acre/yr, fresh)	Nutrient additions: (kg/ha/yr)		(lb/acre/yr)		(lb/acre/yr)
				930	1.41	19	4	17	3	3

Table A10. Rotation for horses in paddock or barnyard area, simplified as monthly applications.

Rotation Name: HPADD										
Year	Date	Operation	Item	Rate Units	Rate Units	N (kg/ha)	P (kg/ha)	N (lb/acre)	P (lb/acre)	Notes
Year 1	15-Jan	Fertilize	Horse manure	1825 kg/ha, dry	2.76 sh T/acre, fresh	37	7	33	33	7 LY1 = 1
	15-Feb	Fertilize	Horse manure	1825 kg/ha, dry	2.76 sh T/acre, fresh	37	7	33	33	7 LY1 = 1
	15-Mar	Fertilize	Horse manure	1825 kg/ha, dry	2.76 sh T/acre, fresh	37	7	33	33	7 LY1 = 1
	15-Apr	Fertilize	Horse manure	1825 kg/ha, dry	2.76 sh T/acre, fresh	37	7	33	33	7 LY1 = 1
	15-May	Fertilize	Horse manure	1825 kg/ha, dry	2.76 sh T/acre, fresh	37	7	33	33	7 LY1 = 1
	15-Jun	Fertilize	Horse manure	1825 kg/ha, dry	2.76 sh T/acre, fresh	37	7	33	33	7 LY1 = 1
	15-Jul	Fertilize	Horse manure	1825 kg/ha, dry	2.76 sh T/acre, fresh	37	7	33	33	7 LY1 = 1
	15-Aug	Fertilize	Horse manure	1825 kg/ha, dry	2.76 sh T/acre, fresh	37	7	33	33	7 LY1 = 1
	15-Sep	Fertilize	Horse manure	1825 kg/ha, dry	2.76 sh T/acre, fresh	37	7	33	33	7 LY1 = 1
	15-Oct	Fertilize	Horse manure	1825 kg/ha, dry	2.76 sh T/acre, fresh	37	7	33	33	7 LY1 = 1
	15-Nov	Fertilize	Horse manure	1825 kg/ha, dry	2.76 sh T/acre, fresh	37	7	33	33	7 LY1 = 1
	15-Dec	Fertilize	Horse manure	1825 kg/ha, dry	2.76 sh T/acre, fresh	37	7	33	33	7 LY1 = 1
Annual manure and nutrient application rates:										
				Manure rate: (kg/ha/yr, dry)	Manure rate: (sh T/acre/yr, fresh)	Nutrient additions: (kg/ha/yr)		(lb/acre/yr)		(lb/acre/yr)
				21900	33.16	438	88	390	88	78