





## Description (continued)

---

In 1933, an open mesh deck was installed to reduce the floor weight which permitted the widening of the roadway. The decking was designed and built by the Irving Iron Works of Long Island City, New York. Shop-welded cantilever girders were extended from the steel span to support the two additional traffic lanes.

The 502 foot bridge at Fremont Avenue was completed in 1917, and provided the primary entranceway to the community of Fremont. The steel for the 242 foot bascule span was fabricated by the Pacific Coast Steel Company. The United States Steel Products Company was the contractor for the superstructure. The substructure was built by the Pacific States Construction Company. In contrast to the University Bridge, permanent concrete approaches were built initially at Fremont Avenue by the West Coast Construction Company. The Fremont Avenue Bridge was equipped with four 100 horse-power motors. The total cost of the bridge was \$410,000. In 1928, the original wood block paving was removed and replaced with open, steel pavement. At this time, new operating motors with hydraulic variable speed transmission were also added. These motors were considered to be a "new venture in moveable bridge machinery."

In 1917, the 15th Avenue N.W. Bridge was also completed, firmly linking Seattle and Ballard. The 295 foot structure which consisted of a 218 foot bascule span cost \$479,000. The steel was fabricated by the Dyer Brothers of San Francisco. Hans Pederson was the contractor for both the substructure and superstructure, and J. Charles Rathburn was the city's superintendent for the construction of the bridge. In 1941, the temporary approaches were replaced by permanent approach spans. The four towers were replaced by a single tower in 1969.


The design engineers in Seattle articulated the importance of aesthetics in city bridge design. On April 20, 1914 the city engineer wrote a letter to the city council: "of late years, it is recognized that it may be possible to secure graceful and pleasing lines, even in steel structures, without spending any large additional amount of money. It is fortunately possible owing to the height at which our bridges will be built above the water level to secure equal mechanical efficiency with a well balanced and pleasing effect." D.R. Huntington, City Architect, was responsible for the architectural treatment of the piers of the three bascule bridges. The massive, concrete piers of the University Bridge and the handsome towers on the Fremont Bridge provide an appropriate architectural frame for the passageway between Puget Sound and Lake Washington. However, the architectural treatment of these three bascule bridges do not equal the monumental stature of the cross-girder bascule bridge built across the canal at Montlake Avenue in 1924.

---

## References (continued)

F.A. Rapp, "Heavy Foundation Work for Bascule Bridge at Seattle," Engineering News Record, 15 April 1920, pp. 774-776.  
Letter from City Engineer to City Council, April 20, 1914.

25. Sketch Map of Location



- A  Montlake Avenue Bridge
- B  University Bridge
- C  Fremont Bridge
- D  Ballard Bridge

Ballard Bridge

