	ev. 6-72) NA	ES DEPARTMENT OF THE NTIONAL PARK SERVICE GISTER OF HISTORI		c	Vermon ounty:						
	INVENTO	RY - NOMINATION	FOR NPS USE ONLY								
	(Type all entrie	es - complete applicabi	la soctions)	1	NTRY DATE	P 6 1974					
	(Type all entries - complete applicable sections) SEP 6										
	COMMON:										
	Seguin Covered	Bridge	· · ·	- 'y ' 							
	AND/OR HISTORIC:										
2.	LOCATION STREET AND NUMBER: TOWN road across Lewis Creek, 3.6 miles southeast of East Charlotte village SE of East Charlotte City of town:										
Ea.	Charlotte Vici	-i		Vt. Di	strict	* .					
	STATE		CODE	UNTY:		cor	DE				
	Vermont		50	<u> </u>	hittenden	07					
3.	CLASSIFICATION CATEGORY				1	ACCESSIBLE					
	(Check One)	OWNE	RSHIP		STATUS	TO THE PUBL					
	 District Building Site Site Object 		c Acquisition: In Process Being Con	5	 Qccupied Unoccupied Preservation wor in progress 	Yes: Restricted Vonrestricted No	d				
	PRESENT USE (Check One or	More as Appropriate)					•				
) : - -	Commercial I Educational N Entertainment		ate Residence gious	-	Transportation	CELVED 2 0 107					
4.											
	Town of Charlotte										
	STREET AND NUMBER:			· · · · · ·			rmo	IJ.			
	(no street numi	ber)	1	<u> </u>	TIE	1 ¤					
	Charlotte		STATE:	Vermont	CODF 50	, 4					
5.	LOCATION OF LEGAL DES	CRIPTION	_l		1						
.	COURTHOUSE, REGISTRY OF DEEDS, ETC:										
	Office of Town Clerk Street and Number:										
	(no street num)	ber)				ttenden	:				
	CITY OR TOWN:			STATE	STATE CODE						
						en					
	Charlotte			Vermont	50						
0.	REPRESENTATION IN EXISTING SURVEYS										
	Vermont Historic Sites and Structures Survey										
	DATE OF SURVEY: 1974 🗌 Federal 🗶 State 🗌 County 🗌 Local										
	DEPOSITORY FOR SURVEY RECORDS:										
	Vermont Division of Historic Sites										
	STREET AND NUMBER										
		ing					197				
	STREET AND NUMBER: Pavilion Build CITY OR TOWN:	ing		STATE:		CODE	19/4				

(Check One) (Check O	7.	DESCRIPTION			5.5 S			
CONDITION (Check One) (Check One) (Check One) (Check One) (Check One) DESCRIBE THE PRESENT AND ORIGINAL (II known) PHYSICAL APPEARANCE The Seguin Covered Bridge consists of a single span by two flanking timber Burr arch trusses. Each trus ates an arch built of two parallel arcs of single ti mounted on each side of the diagonal braces and vert and bolted together through the posts. A central la stringer has been added to the underside of the deck parallel to the trusses for reinforcement. The Seguin Bridge is 71 feet long and 16.5 feet wide 13-foot roadway. The wood floor consists of planks edge and parallel to the trusses. The structure res ments built originally of irregular stone blocks lai have been mortared together and capped with concrete On the exterior, the timbers pegged and bolted toget the trusses (and side walls) of the bridge are sheat painted flush boards hung vertically. Unpainted flus inside the portals. The siding stops short of the e strip openings along the tops of the walls. The gable ends are also sheathed with unpainted flus vertically. The portal openings are rectangular with upper corners, which cover the first sets of interior The medium-pitch gable roof is covered with standing								
AlteredUnalteredMovedDescribe THE PRESENT AND ORIGINAL (<i>Il known</i>) PHYSICAL APPEARANCEThe Seguin Covered Bridge consists of a single span by two flanking timber Burr arch trusses. Each trus ates an arch built of two parallel arcs of single ti mounted on each side of the diagonal braces and vert and bolted together through the posts. A central la stringer has been added to the underside of the deck parallel to the trusses for reinforcement.The Seguin Bridge is 71 feet long and 16.5 feet wide 13-foot roadway. The wood floor consists of planks edge and parallel to the trusses. The structure res ments built originally of irregular stone blocks lai have been mortared together and capped with concreteOn the exterior, the timbers pegged and bolted toget the trusses (and side walls) of the bridge are sheat painted flush boards hung vertically. Unpainted flus horizontally protect the ends of the trusses im inside the portals. The siding stops short of the e strip openings along the tops of the walls.The gable ends are also sheathed with unpainted flus vertically. The portal openings are rectangular with upper corners, which cover the first sets of interior the medium-pitch gable roof is covered with standing		CONDITION			Deteriorated		Unexposed	
The Seguin Covered Bridge consists of a single span by two flanking timber Burr arch trusses. Each trus ates an arch built of two parallel arcs of single ti mounted on each side of the diagonal braces and vert and bolted together through the posts. A central la stringer has been added to the underside of the deck parallel to the trusses for reinforcement. The Seguin Bridge is 71 feet long and 16.5 feet wide 13-foot roadway. The wood floor consists of planks edge and parallel to the trusses. The structure res ments built originally of irregular stone blocks lai have been mortared together and capped with concrete On the exterior, the timbers pegged and bolted toget the trusses (and side walls) of the bridge are sheat painted flush boards hung vertically. Unpainted flu hung horizontally protect the ends of the trusses im- inside the portals. The siding stops short of the e- strip openings along the tops of the walls. The gable ends are also sheathed with unpainted flus' vertically. The portal openings are rectangular witi upper corners, which cover the first sets of interior.			🔀 Altered	Unaltered			🕅 Original Site	
by two flanking timber burf arch trusses. Each trus ates an arch built of two parallel arcs of single ti mounted on each side of the diagonal braces and vert and bolted together through the posts. A central la stringer has been added to the underside of the deck parallel to the trusses for reinforcement. The Seguin Bridge is 71 feet long and 16.5 feet wide 13-foot roadway. The wood floor consists of planks edge and parallel to the trusses. The structure res ments built originally of irregular stone blocks lai have been mortared together and capped with concrete On the exterior, the timbers pegged and bolted toget the trusses (and side walls) of the bridge are sheat painted flush boards hung vertically. Unpainted flu hung horizontally protect the ends of the trusses im- inside the portals. The siding stops short of the e- strip openings along the tops of the walls. The gable ends are also sheathed with unpainted flus- vertically. The portal openings are rectangular wit- upper corners, which cover the first sets of interior The medium-pitch gable roof is covered with standing		DESCRIBE THE PR	RESENT AND ORIGINAL (if kr	own) PHYSICAL	APPEARANCE			
by two flanking timber burf arch trusses. Each trus ates an arch built of two parallel arcs of single ti mounted on each side of the diagonal braces and vert and bolted together through the posts. A central la stringer has been added to the underside of the deck parallel to the trusses for reinforcement. The Seguin Bridge is 71 feet long and 16.5 feet wide 13-foot roadway. The wood floor consists of planks edge and parallel to the trusses. The structure res ments built originally of irregular stone blocks lai have been mortared together and capped with concrete On the exterior, the timbers pegged and bolted toget the trusses (and side walls) of the bridge are sheat painted flush boards hung vertically. Unpainted flu hung horizontally protect the ends of the trusses im- inside the portals. The siding stops short of the e- strip openings along the tops of the walls. The gable ends are also sheathed with unpainted flus- vertically. The portal openings are rectangular wit- upper corners, which cover the first sets of interior The medium-pitch gable roof is covered with standing		The Seguin	n Covered Bridg	e consist	s of a ci	nglo gno		,
ates an arch built of two parallel arcs of single ti mounted on each side of the diagonal braces and vert and bolted together through the posts. A central la stringer has been added to the underside of the deck parallel to the trusses for reinforcement. The Seguin Bridge is 71 feet long and 16.5 feet wide 13-foot roadway. The wood floor consists of planks edge and parallel to the trusses. The structure res ments built originally of irregular stone blocks lai have been mortared together and capped with concrete On the exterior, the timbers pegged and bolted toget the trusses (and side walls) of the bridge are sheat painted flush boards hung vertically. Unpainted flu hung horizontally protect the ends of the trusses im- inside the portals. The siding stops short of the e- strip openings along the tops of the walls. The gable ends are also sheathed with unpainted flus- vertically. The portal openings are rectangular wit- upper corners, which cover the first sets of interior The medium-pitch gable roof is covered with standing		0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	anking timber B	urr arcn	Trusses	Each tru	ice incorne	~~
and bolted together through the posts. A central la stringer has been added to the underside of the deck parallel to the trusses for reinforcement. The Seguin Bridge is 71 feet long and 16.5 feet wide 13-foot roadway. The wood floor consists of planks edge and parallel to the trusses. The structure res ments built originally of irregular stone blocks lai have been mortared together and capped with concrete On the exterior, the timbers pegged and bolted toget the trusses (and side walls) of the bridge are sheat painted flush boards hung vertically. Unpainted flu hung horizontally protect the ends of the trusses im- inside the portals. The siding stops short of the e- strip openings along the tops of the walls. The gable ends are also sheathed with unpainted flus- vertically. The portal openings are rectangular with upper corners, which cover the first sets of interior The medium-pitch gable roof is covered with standing		ates an an	ren duilt of two	o paralle	1 arcs of	single t	timbers or	
stringer has been added to the underside of the deck parallel to the trusses for reinforcement. The Seguin Bridge is 71 feet long and 16.5 feet wide 13-foot roadway. The wood floor consists of planks edge and parallel to the trusses. The structure res ments built originally of irregular stone blocks lai have been mortared together and capped with concrete On the exterior, the timbers pegged and bolted toget the trusses (and side walls) of the bridge are sheat painted flush boards hung vertically. Unpainted flu hung horizontally protect the ends of the trusses im- inside the portals. The siding stops short of the e- strip openings along the tops of the walls. The gable ends are also sheathed with unpainted flus- vertically. The portal openings are rectangular with upper corners, which cover the first sets of interior.		and boited	1 together throu	igh the p	osts. A	central 1	laminated -	:s,
The Seguin Bridge is 71 feet long and 16.5 feet wide 13-foot roadway. The wood floor consists of planks edge and parallel to the trusses. The structure res ments built originally of irregular stone blocks lai have been mortared together and capped with concrete On the exterior, the timbers pegged and bolted toget the trusses (and side walls) of the bridge are sheat painted flush boards hung vertically. Unpainted flu hung horizontally protect the ends of the trusses im- inside the portals. The siding stops short of the e- strip openings along the tops of the walls. The gable ends are also sheathed with unpainted flust vertically. The portal openings are rectangular with upper corners, which cover the first sets of interior The medium-pitch gable roof is covered with standing		stringer	nas been added :	to the un	derside o	f the dec	ck beams	
13-root roadway. The wood floor consists of planks edge and parallel to the trusses. The structure res ments built originally of irregular stone blocks lai have been mortared together and capped with concrete On the exterior, the timbers pegged and bolted toget the trusses (and side walls) of the bridge are sheat painted flush boards hung vertically. Unpainted flush hung horizontally protect the ends of the trusses imminside the portals. The siding stops short of the extrip openings along the tops of the walls. The gable ends are also sheathed with unpainted flush vertically. The portal openings are rectangular with upper corners, which cover the first sets of interior.		parallel	to the trusses :	for reinf	orcement.	· · · · ·		
 ments built originally of irregular stone blocks lai have been mortared together and capped with concrete On the exterior, the timbers pegged and bolted toget the trusses (and side walls) of the bridge are sheat painted flush boards hung vertically. Unpainted flush hung horizontally protect the ends of the trusses imminside the portals. The siding stops short of the estrip openings along the tops of the walls. The gable ends are also sheathed with unpainted flust vertically. The portal openings are rectangular with upper corners, which cover the first sets of interior. 		edge and p	padway. The woo	trusses.	consists The str	of planks ucture re	s laid on ests on abu	1t -
 the trusses (and side walls) of the bridge are sheat painted flush boards hung vertically. Unpainted flush hung horizontally protect the ends of the trusses imported the portals. The siding stops short of the ends strip openings along the tops of the walls. The gable ends are also sheathed with unpainted flust vertically. The portal openings are rectangular with upper corners, which cover the first sets of interior The medium-pitch gable roof is covered with standing 		ments buil	lt originally of	irregula	ar stone [blocks la	id drv. th	iey v
nung norizontally protect the ends of the trusses imminside the portals. The siding stops short of the ends strip openings along the tops of the walls. The gable ends are also sheathed with unpainted flust vertically. The portal openings are rectangular with upper corners, which cover the first sets of interior The medium-pitch gable roof is covered with standing		the trusse	es (and side wal	lls) of t	he bridge	are shea	thed with	un- IT
The gable ends are also sheathed with unpainted flus vertically. The portal openings are rectangular with upper corners, which cover the first sets of interior The medium-pitch gable roof is covered with standing		inside the	portally protect	the ends siding st	s of the [·] tops shor [·]	trusses i t of the	mmediatelv	· -
vertically. The portal openings are rectangular with upper corners, which cover the first sets of interior The medium-pitch gable roof is covered with standing				-				
upper corners, which cover the first sets of interior The medium-pitch gable roof is covered with standing		The gable vertically	ends are also s	heathed w	with unpar	inted flu	sh boards	1
The medium-pitch gable roof is covered with standing		upper corn	ers. which cove	er the fi	irst sets	of inter	ior struts	
NECEIVEU IN' A ' IN' A NATIONAL RECIGTED		The medium	-pitch gable ro	of is cov	vered wit	ı s t andin	ıg seam met	a1 🗥
NECEIVEIJ INV A 154 NATIONAL RECISTEN		sneeting.				·		
NECEIVET INV AL ANA NAVIONAL REGISTER								0
NATIONAL NATIONAL RECISTED A					A STALL	12N	(1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,	z
WATTOMAL NATIONAL REGISTED:				и 1.11	1 Arrive	n (A)		S
MATIGANA RECIGITED AND AND AND AND AND AND AND AND AND AND				6	y Henry L DBY A V			
				C	M.B. Stress		<u>.</u> .	
					RECIST	5 /5/		
							 A state of the sta	
					NUM.			
		·						
			•			· .		
			¢					
					· .	:		
							·	

PERIOD (Check One or More	as Appropriate)		
Pre-Columbian	🔲 16th Century	18th Century	20th Century
] 15th Century	17th Century	X 19th Century	
SPECIFIC DATE(S) (If Applic	able and Known) C . 1 (850	
AREAS OF SIGNIFICANCE	Check One or More as Appropri	iate)	
Abor iginal	Education	Political	🔲 Urban Planning
Prehistoric	Engineering	🗌 Religion/Phi-	Other (Specify)
· 🔲 Historic	🗌 Industry	. losophy	<u> </u>
Agriculture	Invention	Science	
Architecture	Landscape	Sculpture	
Art	Architecture	🔲 Social/Human-	
Commerce	Literature	* itarian	
Communications	🔲 Military	Theater	
Conservation	Music	Transportation	
The Seguin Cove remaining in th	ered Bridge, one ne town of Charl	e of three cover lotte, crosses I	red wood bridges Lewis Creck a sho
remaining in the distance downst is one of only are supported b	ered Bridge, one ne town of Char cream from scent nine covered br	e of three cover lotte, crosses I ic waterfalls. ridges remaining usses. The brid	red wood bridges Lewis Creck a sho The Seguin Bridg g in Vermont whic lge has been main

1. R. S. Allen, <u>Covered Bridges of the Northeast</u>, The Stephen Greene Press, Brattleboro, Vt., 1957, p. 50.

National Register of Historic Places to a majority of the remaining covered bridges.



9. N	AAJOR	BIBLIOGRA	PHICAL R	EFERENCE	S								1
									<u></u>				
A	\11e	n, Richa	ard San	nders,	Covered	Bri	dges	oft	he No	orthea	ast, T	he	
		Stepher	n Green	ie Pres	s, Brat	tleb	oro,	Vt.,	195	7.			
C	Cong	don, Her	rbert !	Wheaton	, The C	over	ed B	ridge	e, Vei	rmont	Books		
1		Middlel	bury, N	/ t. , 19	970.								
10.	GEOGI	RAPHICAL D	ράτα										
T		LATITUDE AN				0		ING THE	CENTER	POINIO	OORDINAT		
co	DRNER	LATIT	TUDE	LONG		R	L <i>I</i>	TITUDE	LESS TH	N TEN A	CRES	E	18/647550
		Degrees Minut	es Seconds	Degrees Min	nutes Seconds	De	grees	Minutes	Seconds	Degrees	Minutes	Seconds	18/647550
	NW NE	0	, n	0 0	, , , ,,		44°	17	21"	73°	09'	03″	1905 410
	SE	• 0	1 9	- 0		1	•		:		1.		CD
	sw	0	• •	o	· · · · · · · · · · · · · · · · · · ·	. i		· · · · · ·	•		•••		с. С.
		MATE ACREA				one			UNITO A.	NIN dalar	~		S
	ATE:	_ JIAIEJ AND	.:	FOR PROP	CODE	COUN			X P	2 3		CODE	ш
	_				· [-	· ·		Nr. RI	CEIVFN	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~		m
ST	ATE:				CODE	COUN	ITY:	1	MAY	2 0 1974	El	CODE	
ST	ATE:		· ···								rin .		z
31	ATE:	· · · · ·	• • • •		CODE		TY:	Ē		TIONAL		CODE	S
ST	ATE:				CODE	COUN	TY:		JA RE	GISTE	<u> </u>	CODE	
		• • • •		· · · ·	-	1	·	1	Vior	· · · · · · · · · · · · · · · · · · ·	<u>_</u>		נג
		PREPÁRED	BY						\sim				C
		D TITLE:	· · · · · · · · ·	•			3	, e î î		•	1 · · · · ·	at in the	0
OR	GANIZ	H. Henr	ry, llis	toric	Sites Re	sear	chei	<u> </u>		DATE		<u>.</u>	
V	ermo	ont Divi	ision o	f Hist	oric Si	tes			•		1/74		
Р		lion Bui		ent of st		•••		•		- 1.23 - 1.4	•		o z
CIT	TYOR	TOWN:				STATE	 	•		Y	• •	CODÈ	S
<u> M</u>	ontr	<u>belier</u>		OTICICI				mont_				50	
12. 3		LIAISON OF	FILER CE	RIFICAL	IUN		NA	TIONAL	REGISTI	ER VERI	FICATION		
	A	dog is not ad S				1							
		designated S Historic Pres				Ihe	ereby c	ertify tha	t this pr	operty is	included	in the	
), I hereby no				Nat	ional F	Register.					
		National Reg						\sim	-		_	[
evaluated according to the c-iteria and procedures set													
forth by the National Park Service. The recommended													
level of significance of this nomination is:													
	National 🗌 State 🔀 Local 🗌												
		1,1,11	1- /	RP		Date	e	_4/0	2/74				
	Name _	-AiUA	Lin V). from	ney	AT	TEST:	с -	,				
		D .	-		1								
	Title	Directo Histor	r of H	istori	<u>c Sites</u>		[}],	sele	0	مد لم	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~		
10	tate ffic	: Histor	ic Pre	servat	10N	a	in	Keeper	of The N	ational R	egister		
1	LLLC Date		5/14/	74		Date	. 1		9.6	- 70			
			5/14/	17				· · · · · ·	<u> </u>	-17			

☆ U.S. GOVERNMENT PRINTING OFFICE : 1973-729-147/1442 3-1