NPS Form 10-900	OMB No. 10024-0018
(Oct. 1990) United States Department of the Interior National Park Service	RECEIVED 2280
National Register of Historic Places Registration Form	SEP - 3
This form is for use in nominating or requesting determinations for individual pr National Register of Historic Places Nomination Form (National Register Bullet by entering the information requested. If an item does not apply to the property architectural classification, materials, and areas of significance, enter only cate and narrative items on continuation sheets (NPS Form 10-900a). Use a typewr	being documented, enter "N/A" for "not applicable." For functions, gories and subcategories from the instructions. Place additional entries
1. Name of Property	······································
historic nameSeybold, George, House	
other names/site number <u>Kelley, Fred W., House</u>	
2. Location	
street & number111 E. Main St	not for publication
city or town Waveland	vicinity
state Indiana code IN county Montgomery	code_ <u>107</u> zip code_ <u>47989</u>
3. State/Federal Agency Certification	
Historic Places and meets the procedural and professional requirements meets boes not meet the National Register criteria. I recommend nationally statewide tocally. See continuation sheet for ad Signature of certifying official/Title Date State of Federal agency and bureau	d that this property be considered significant
In my opinion, the property meets does not meet the National R comments.)	egister criteria. (See continuation sheet for additional
Signature of certifying official/Title Date	
State or Federal agency and bureau	
/ /	
4. National Park Service Certification	
I hereby certify that the property is: entered in the National Register. See continuation sheet. determined eligible for the National Register	ture of the deeper Date of Action
See continuation sheet.	
determined not eligible for the National Register.	
removed from the National	
other, (explain:)	

Seybold,	George,	House	
Name of Pro			

5. Classification			
Ownership of Property (Check as many boxes as apply)	Category of property (Check only one box)	Number of Resources within Property (Do not include previously listed resources in the coun	t)
IX private public-local public-State public-Federal	building district site structure object	site	uctures jects
Name of related multiple property listing (enter "N/A" if property is not part of a multiple property listing)		Number of contributing resources previously listed in the National Register	
N/A		N/A	
6. Function or Use			<u></u>
Historic Functions (Enter categories from instructions)		Current Functions (Enter categories from instructions)	
DOMESTIC/single dwelling		DOMESTIC/single dwelling	
			,
7. Description			<u> </u>
Architectural Classification (Enter categories from instructions)		Materials (Enter categories from instructions)	
LATE VICTORIAN/ Stick		foundation <u>BRICK; CONCRETE</u>	
<u>-</u>		walls <u>WOOD</u> : weatherboard; shingle	
		roof ASPHALT; METAL: tin	
		other	
		······································	

Narrative Description (Describe the historic and current condition of the property on one or more continuation sheets.)

.

Seybold, George, House	Montgomery County, Indiana
Name of Property	County and State
8. Statement of Significance	
Applicable National Register Criteria	Areas of Significance
(Mark "x" in one or more boxes for the criteria qualifying the property National Register listing.)	(Enter categories from instructions)
	Architecture
A Property is associated with events that have made a significant contribution to the broad patterns of	
our history.	
I B Property is associated with the lives of persons significant in our past.	
X C Property embodies the distinctive characteristics	
of a type, period, or method of construction or	
represents the work of a master, or possesses	
high artistic values, or represents a significant and distinguishable entity whose components lack	Period of Significance
individual distinction.	
	1886
D Property has yielded, or is likely to yield,	
information important in prehistory or history.	
Criteria Considerations (Mark "x" in all the boxes that apply)	Significant Dates
Property is:	
rioperty is.	
A owned by a religious institution or used for religious purposes	Significant Person
B removed from its original location	(Complete if Criterion B is marked above)
c a birthplace or grave	
	Cultural Affiliation
b a cemetery	
E a reconstructed building, object, or structure	
F a commemorative property	Architect/Builder
G less than 50 years of age or achieved significance	
Narrative Statement of Significance (Explain the significance of the property on one or more continuation sh	eets.)
9. Major Bibliographic References	
Bibliography (Cite all the books, articles, and other sources used in preparing this for	rm on one or more continuation sheets.)
Previous documentation on file (NPS):	Primary location of additional data:
Dipreliminary determination of individual listing (36	State Historic Preservation Office

Impreliminary determination of individual listing (36
CFR 67) has been requested
Tpreviously listed in the National Register
Tpreviously determined to be eligible by the National
Register
designated a National Historic Landmark
Trecorded by Historic American Buildings Survey
#

Trecorded by Historic American Engineering Record #_____

State Historic Preservation Office Other state agency Federal agency Local government University X Other Name of repository: Historic Landmarks Foundation of Indiana

Seybold, George, House Name of Property	Montgomery IN County and State
10. Geographical Data	
Acreage of Property Less than 1 acre	
UTM References (Place additional UTM references on a continuation sheet.)	
1 16 496200 4413760 Zone Easting Northing 2 Image: State of the	3 Zone Easting Northing 4 See continuation sheet
Verbal Boundary Description (Describe the boundaries of the property on a continuation sheet.)	
Boundary Justification (Explain why the boundaries were selected on a continuation sheet.) 11. Form Prepared By	
name/title Tommy Kleckner, Program Assistant organization Historic Landmarks Foundation of Indian Office street & number 643 Wabash Avenue	
city or town Terre Haute	
Additional Documentation Submit the following items with the completed form: Continuation Sheets	
Maps A USGS map (7.5 or 15 minute series) indicating the A Sketch map for historic districts and properties ha	
Photographs	
Representative black and white photographs of the	e property.
Additional items (Check with the SHPO or FPO for any additional items)	
Property Owner	
(Complete this item at the request of SHPO or FPO.)	
name Fred Kelley	
street & number 111 East Main Street	telephone 765/ 435-3002
city or town Waveland	state IN zip code 47989

Paperwork Reduction Act Statement: This information is being collected for applications to the National Register of Historic Places to nominate properties for listing or determine eligibility for listing, to list properties and to amend existing listings. Response to this request is required to obtain a benefit in accordance with the National Historic Preservation Act, as amended (16 U.S.C. 470 *et seq.*).

Estimated Burden Statement: Public reporting burden for this form is estimated to average 18.1 hours per response including time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding this burden estimate or any aspect of this form to the Chief, Administrative Services Division, National Park Service, P.O. Box 37127, Washington, DC 20013-7127; and the Office of Management and Budget, Paperwork Reductions Projects (1024-0018), Washington, DC 20503.

National Register of Historic Places Continuation Sheet

Section number _____ Page ____

Seybold, George, House Montgomery County, IN

Description:

The George Seybold House is eligible for the National Register of Historic Places under Criteria C for its distinctive architectural design. The house is located at 111 East Main Street in the City of Waveland, Indiana. It should be noted that historical records identify the address of the property as 101 East Main Street. Situated in the southeast quadrant of the intersection of Main and Cross Streets, the primary façade of the house faces north (Photo 1). It is surrounded by a grass lawn, which slopes gradually to the southern end of the property. Several mature maple and spruce trees are situated east of the house and an aspen tree is located to the northwest of the house. Foundation plantings of coniferous and deciduous shrubbery are found along the north and west facades. Concrete sidewalks run along the west and north sides of the property with grass-filled tree rows separating the street from the sidewalks. A gravel drive, located on the southern end of the property and accessible from South Cross Street, leads to a modern, two-car garage. The nominated property is located at the northern edge of a residential neighborhood with residential properties abutting to the east and south. The residential neighborhood continues on the west side of Cross Street. Directly north of the nominated property, across Main Street, is the downtown commercial district of Waveland.

Constructed in 1886, the wood frame structure was designed with elements from the late Stick style period. The asymmetrical plan of the house can be divided into two sections: the main three-story section with a cross gable extension on the west side and the 1 ½-story rear wing. The main section has a full basement with the foundation constructed of soft red brick. The rear wing has a crawl space only with a foundation of red brick and concrete. The house is clad in wood clapboard siding with wood shingle siding located in the upper portion of the gable ends of the main roof. The house also features baseboards, corner boards and distinctive Stick-style horizontal and vertical bands. The wood sidings are painted peach and tan with trim elements painted white. Common fenestration consists of double-hung, 1-over-1 windows. Modern vinyl-replacement windows have been inserted in several original window openings. All windows on the main section of the house feature wide casings and decorative drip caps. All original wood windows feature exterior aluminum storm windows. Modern metal-framed storm doors have been installed on all exterior doorways. These storm doors feature upper and lower glazed panels with vertical, metal security bars and small, decorative metal grillwork centered in both panels.

Roof shapes consist mainly of gabled, shed and flat. All gable ends on the main section of the house, including the projecting gabled roof on the front porch, are embellished with decorative verge boards with incised geometric shapes, decorative king's post trusses and large, decorative brackets (Photo 2). These brackets, which extend slightly down the corner boards on the main section of the house, feature incised patterns on the flat, vertical surfaces and hollow chamfers on the broad curved portions. The main section and front porch of the house feature decorative scroll-cut rafter tails. A brick chimney is located in the center of the main section and another is located south-of-center on the rear section. A metal ventilation pipe projects from the lower end of the eastern slope of the main section of the house.

The primary elevation of the building is the north façade, which faces East Main Street (Photo 3). The asymmetrical, gable-front façade features two common windows and front doorway evenly spaced on the first floor, three common windows evenly spaced on the second floor, and paired common windows centered on the third floor. The first-story windows are vinyl-replacements. The front doorway with transom features the modern storm door and an original wood-paneled door. The north gable end features the decorative verge board, king's post truss, and brackets. An attic vent is located in the upper, wood shingled portion of the gable end.

National Register of Historic Places Continuation Sheet

Section number ____7 Page ___2

Seybold, George, House Montgomery County, IN

Description (continued)

Dominating the first-story of the asymmetrical façade is a highly decorative L-shaped, wood porch. Extending along the north façade, the porch wraps around the northwest corner of the house and abuts the north wall of the extension of the west elevation. The foundation of the porch is red brick covered with parge coat. Decorative metal ventilation grills are spaced along the front foundation wall. The porch has wood board decking and a plaster ceiling. The shed roof of the porch features scroll-cut rafter tails. Square, fluted posts with decorative carvings support the front porch. These posts are paired on the east side of the front steps. Pilasters matching the appearance of the porch posts are found on the east

and west ends of the porch where the porch meets the house. Flanking the tops of the porch posts are small, decorative brackets, which help support the rafter plate of the porch roof. Detailing the exterior vertical surface of the rafter plate is a decorative wood band in a simplified "egg-and-dart" pattern.

A small, gabled roof projects from the front porch roof over the front steps (Photo 4). The triangular flat surface of the gable end features vertical tongue-and-groove siding above a decorative wood band identical to that found on the rafter plate of the main porch roof. The gable end of the projecting roof features the decorative verge board, king's post truss and brackets common to the house. The brackets extend slightly down the front of the porch posts that flank the front steps (Photo 5).

Horizontal bands extend across all three stories of the primary façade. These bands are located at window sill and window head levels on the first story but only at window head level on the second and third stories. Vertical bead board siding is found in the area between the bottom horizontal band and the porch decking. This feature is found on all three exterior walls that are sheltered by the front porch.

The west facade of the house is dominated by the three-story, cross-gabled extension (Photo 6). The interior stairway connecting all floors is located in this extension. This extension is located slightly north-of-center of the main body of the house and features the decorative verge board, king's post truss, and brackets. Flush with the west wall of the cross-gabled extension is an L-shaped section of the first story. Extending from the main body of the house, this L-shaped section wraps around the southwest corner of the house and intersects with the 1 ½-story rear wing. A common window is located in the northern end of the first story, in the area sheltered by the front porch. Three common windows are also located in the L-shaped, first-story extension. A common window is located just above the top of the shed roof of the first-story L-shaped section. The cross-gabled extension features paired common windows are found on the north and south walls of the cross-gabled extension. All first-story windows and the paired windows in the cross-gabled extension are vinyl-replacements.

Horizontal bands located at window sill and window head level extend along the northern end of the first story. These bands wrap around the north wall of the cross-gabled extension and continue along the west wall to the southern end of the L-shaped section. The sill of the paired windows in the cross-gabled extension are set at the same level as the top horizontal band of the first story. A second horizontal band is located at window head level of the paired windows. Horizontal bands are also located at window sill and window head level of the third-story window in the cross-gabled extension. The horizontal band at window sill level wraps around the south wall of the cross-gabled extension and continues to the southern end of the main body of the house at window head level of the

National Register of Historic Places Continuation Sheet

Section number 7 Page 3

Seybold, George, House Montgomery County, IN

Description (continued)

second-story window. The southwest corner board of the cross-gabled section extends from the upper stories to the baseboard, creating a vertical band. Similarly, a vertical band located on the first-story L-shaped section aligns with the southwest corner board of the main body of the house. Vertical bands are also found extending from the window sills to the base board in the L-shape section, aligning with the side casings of the windows.

A small flat-roofed side porch extends from the south wall of the first-story L-shaped section along the west wall of the rear wing (Photo 7). The porch has a concrete foundation with wood board decking and concrete steps off the west side. A porch post supports the southwest corner and pilasters are found where the porch intersects the house walls. The corner post and pilasters match the appearance of those on the front porch. Similarly, small, decorative brackets located at the top of the corner post and pilasters help support the rafter plate. A larger, unique scrolled bracket extends from the upper west face of the corner post to the soffit of the flat roof. The rafter plate of this porch features vertical siding in an inverted picket-fence pattern.

The 1 ½-story rear wing extends from the south façade of the main body of the house, leaving only portions of the south façade visible. These portions include the south wall of the first-story, L-shaped section, part of the second story and the third-story gable end (Photos 8 & 9). An exterior doorway with transom is located in the south wall of the L-shaped section. This doorway features the modern storm door and an original wood-paneled door. A common window is located on the eastern side of the second story. A double-hung window, much shorter than the common window, is located in the third story of the gable end. A horizontal band extends across the south elevation at the window head level of both the second- and third-story windows. The decorative verge board, king post's truss and brackets common to the house are found on the south gable end.

The east façade of the main body of the house features two widely spaced windows on the first story with a second set similarly spaced on the second story (Photo 10). The first-story windows are vinyl-replacements. Horizontal bands extend across the first and second stories of this façade at window sill and window head levels. Vertical bands, aligned with the side casings, extend from the sill of the second-story windows to the heads of the first-story windows and then again from the sill of the first-story windows to the base board.

The rear wing can best be described separately from the main section of the house. The roof of the wing features metal roofing panels with stamped patterns and a decorative metal ridge cap with a perforated circular design. The west elevation of the rear wing features two windows and banding (see photo 8). A double-hung window, shorter than the common window, is located towards the northern end of the west wall. This window is sheltered by the side porch. A common window is located towards the southern end of the west wall. The sill and head of this window is the level at which the horizontal bands of this wall are located. Vertical bands, aligned with the side casings, extend from the sill of this window to the baseboard.

The south elevation of the rear wing features a common window towards the apex of the gable end (see photo 8). Horizontal bands extend across the elevation at the same level as that of the west elevation. Vertical bands, aligned with the side casings, extend from the sill of the window to just below the top horizontal band. A second set of vertical bands extend from roughly the mid-portion of the south wall past the base board and foundation to grade. With the southern end of the rear wing once used as a carriage house, these vertical bands demarcate the location

National Register of Historic Places Continuation Sheet

Section number ____7 Page ___4

Seybold, George, House Montgomery County, IN

Description (continued)

of the carriage entry. Concrete encloses the foundation of this space.

An unusual feature of the east elevation of the rear wing is the extension of the northern half of the east slope of the roof (see photo 9). This portion extends slightly past the east wall of the main section of the house, covering an enclosed porch to the north and sheltering an exterior side porch to the south. A common window is centered in the southern half of the east elevation. A doorway with transom and a common window are located under the extension of the roof slope. The doorway features the modern storm door and an original wood-paneled door. A doorway with similar features is located in the south wall of the enclosed porch. The east wall of the enclosed porch features a tripartite window unit with the center window slightly wider than the side windows. This window unit extends from the roof soffit to approximately the base board. Horizontal bands are located at window sill and window head levels extend across the east elevation. Vertical bands, aligned with the side casings, extend from the window sills of both common windows to the base board.

The southeast side porch features a concrete foundation and a wood decking. Concrete steps are found on the south side of the porch. A series of stone steps with a wooden railing connect the side porch with the gravel drive to the south. A stone patio is situated just east of the side porch. This patio is screened on the north by a wood fence.

The interior ceilings and walls of the house are plaster. Common throughout the house is original stained woodwork . The window and door trim in the first-floor formal spaces and the second-floor spaces is more decorative. The wood trim surrounding the windows and doorways in the front entry hall and first-floor parlors overlaps at the top corners with wood blocks applied at the corners. Similar blocks are located on the vertical trim elements approximately three feet up from the floor. The carved blocks feature three distinct designs: bullseye, rosettes, and a simple, incised design. Wide, wood baseboards are found throughout the house. Located below the windows throughout the house are decorative wood panels (Photo 11). The rectangular panels consist of detailed wood trim applied around the perimeter with carved corner blocks in a bullseye pattern.

The formal entrance to the house is accessed through the first-story entryway on the north façade. The front wood door is original and features glazing on the upper two-thirds with a lower wood panel. Highly decorative, woodcarvings in an Eastlake motif are applied to the door (Photo 12). The front entry hall features an exposed wood floor, decorative wood trim with blocks in a bullseye design, and wide baseboards. Through the large doorway to the left is the formal front parlor. A doorway in the south wall leads to a small hallway with the dining room beyond (Photo 13). The stairway to the second floor is found at the southern end of the west wall. A small door located between the stairway and the south wall provides access to a small storage area. A window is located in the west wall between the stairway and the north wall.

The formal front parlor features an exposed wood floor, decorative wood trim, and wide baseboards. A rosette design is found in the upper corner blocks of the trim with a bullseye design in the lower blocks. Two windows are found in the north wall and one window in the east wall. A diagonal wall in the southwest corner of the parlor features a period fireplace with an ornate slate surround and tile hearth (Photo 14). The slate surround has a two-tiered mantel and a raised cartouche centered above the firebox. The front parlor also has a central ceiling light fixture in a turn-of-the-century period style.

National Register of Historic Places Continuation Sheet

Section number ____7 Page ___5

Seybold, George, House Montgomery County, IN

Description (continued):

In the south wall of the front parlor is a large doorway, which provides access to the rear parlor. This doorway features original wood-paneled pocket doors. The rear parlor features decorative wood trim with blocks in a bullseye design and wide baseboards. A window is located in the east wall and two doorways with transoms are located in the south wall of the rear parlor. The eastern most doorway leads to the enclosed porch and features a solid, wood-paneled door. The other doorway featuring a similar door leads to a small bathroom with modern fixtures. The rear parlor has a central ceiling light fixture similar in design to the fixture in the front parlor.

A large doorway in the west wall of the rear parlor leads to the dining room (Photo 15). The dining room features simplified wood trim around the doors and windows. Located unusually low around the perimeter of the room is tongue-and-groove wainscoting with chair rail. Three windows are found in the west wall and two doorways in both the north and south walls. The western most doorway on the north wall provides access to a closet. The other doorway with transom leads to the small hallway between the dining room and the front entry hall. Both doorways feature solid, wood-paneled doors. The western most doorway on the south wall leads to the southwest side porch. This doorway with transom features a wood-paneled door with single-lite glazing on the upper half. The eastern most doorway on the south wall leads to the kitchen.

The simple woodwork of the kitchen is painted. A corner cabinet located in the northeast corner appears to be original to the space. A window is located on the west wall. Another window is located on the northern end of the east wall. An exterior doorway is centered in the east wall. This doorway features a wood-paneled door with single-lite glazing in the upper half. A doorway on the western end of the south wall leads to a rear bedroom. The wood trim in this bedroom is not original but is of a similar period and design as that in the rest of the house. A window is centered in the east walls.

The small hallway between the front entry hall and the dining room features a doorway in the west wall that leads to a stairway that accesses the basement. The doorway has a solid, wood-paneled door.

Winding steeply counter clockwise, the stairway to the second floor features tongue-and-groove wainscoting (Photo 16). At the top of the stair is a central hall space. Decorative wood trim is found around all doorways in the central hall (Photo 17). This trim features blocks with a bullseye design and a dart pattern. Directly to the right of the stairway is a diagonal wall with a doorway that leads to a storage closet. The doorway on the south wall of the central hall leads to the second floor bathroom. This bathroom features modern fixtures of period design including twin pedestal sinks. An antique claw foot tub has also been installed. A window is located in the west wall of the bathroom and a small doorway in the south wall provides access to the attic of the rear wing.

In the east end of the central hall is a doorway leading to one of two second-floor bedrooms. This bedroom features decorative wood trim and solid, wood-paneled doors. A doorway towards the eastern end of the north wall provides access to a closet. A window is centered on the east and south walls. The second bedroom is accessed through a doorway in the central hall across from the stairway. This bedroom also features decorative wood trim. A doorway towards the western end of the south wall leads to a closet. A window is centered on the east wall with two windows located in the north wall.

National Register of Historic Places Continuation Sheet

Section number ____7, 8 Page ___6

Seybold, George, House Montgomery County, IN

Description (continued):

To the left of the stairway in the central hall is a doorway that provides access to the stairway that leads to the third floor. Similar to the stairway below, this stairway winds steeply counter clockwise. It enters a room, which is currently used as a study (Photo 18). The room features simple, painted wood trim and wide plank flooring. A sloped section of ceiling is found on the east and west walls, reflecting the pitch of the gabled roof. Paired windows are located on the north wall and provide a panoramic view of downtown Waveland. A rectangular projection from the south wall encloses the central chimney. A doorway towards the eastern end of the south wall leads to a third-floor bedroom. Similar to the front room, this bedroom features the sloped ceiling on the east and west walls, painted wood trim, and wide plank flooring. A shorter, double-hung window is centered in the south wall.

Statement of Significance

The George Seybold House is eligible for the National Register of Historic Places under Criteria C for its distinctive architectural design. Constructed in 1886, the house is an outstanding local example of Stick style architecture. The building has served its original residential use continuously since its construction and remains virtually unchanged from its late nineteenth century appearance. Listed as an outstanding-rated Queen Anne structure in the Montgomery County Historic Sites and Structures Survey, the house possesses various defining elements of the Stick style and would thus more appropriately be identified as such.

Located in the far southwest corner of Montgomery County, Waveland is the oldest town in Brown Township. As early as the 1820s, travelers on the road from Terre Haute to Lafayette were stopping to drink from the fresh springs located in the area. Around 1830, a small settlement had been established complete with trading post and post office. Platted in 1835 by John Milligan, Waveland was not officially incorporated until 1866. By this time, Waveland was a thriving community, home to numerous successful businesses, prominent businessmen, and a prestigious educational institution, the Waveland Collegiate Institute, which was established in 1848. Contributing to the continued growth of Waveland through the nineteenth century was the arrival of the Logansport, Crawfordsville and Southwestern (Vandalia) Railroad in the 1870s followed by the Anderson, Lebanon and St. Louis (Midland) Railroad in 1890.

It was during this period of growth from the 1870s through the 1890s that many of the prominent residences that remain in Waveland were constructed, including that of George Seybold. Seybold was born in 1851 on the farm of his parents, James and Annie Seybold, located approximately four miles southwest of Waveland in Parke County. His grandfather had settled in Parke County earlier in the 19th century. Schooled locally, George Seybold engaged himself in the hardware business at the age of twenty-three. In addition to his role as a prominent merchant, he was involved with the Dell Mineral Springs Company to which he served as a treasurer and a director. Seybold also helped organize the Waveland Building and Loan Association in 1884. George Seybold eventually partnered with James McCormick in the hardware business though it was not determined when this partnership began. He constructed his house in 1886 but by 1890 had sold it to William McClain. Seybold moved his family to the town of Darlington, also in Montgomery County, and established a hardware business there. It was in the second floor of his hardware store that George Seybold hung himself in 1901.

National Register of Historic Places Continuation Sheet

Section number 8 Page 7

Seybold, George, House Montgomery County, IN

Statement of Significance (continued)

After William McClain, George Slavens and his wife, Stella, owned the property at 111 East Main Street. An interesting event still associated with the house during the Slavens' ownership is that of an attempted heist of the State Bank of Waveland in 1932. Several historical accounts recognize George Slavens's efforts to thwart the heist by firing his army rifle at the robbers from a third floor window of his house. After George Slavens death in 1952, Stella retained ownership of the property until her death in 1958. The property then passed through several owners before it was purchased by the current owner, Fred W. Kelley, in 1989.

The first account of any building being constructed on the southeast corner of Main and Cross Streets was that of a hotel. Constructed by an early entrepreneur by the name of Jack Collier, this hotel burned down and the lot was left vacant for several years before George Seybold constructed his house on the site in 1886.

George Seybold's decision to construct the house in the Stick style may have been influenced by architectural pattern books, which were popular at the time. Supporting this is the fact that the house was constructed towards the end of the 1860-1890 period in which the Stick style predominantly appeared in residential architecture. The Stick style is considered a transitional stylistic period, influenced by the preceding Gothic Revival style and proceeding Queen Anne style. The most significant feature borrowed from the Gothic Revival style is the steeply-pitched gable roof.

It is in decorative treatment that the Stick style deviates, treating the wall surface as a decorative element itself by the use of varying cladding materials and the application of horizontal, vertical, and diagonal wood banding. The Seybold House serves as an excellent example of this use of decoration. Vertical and horizontal banding is found on almost all elevations of the Seybold House. The stickwork banding of the style was believed to mimic the half-timbered houses of Medieval England. Contemporary architectural historians support the idea that the wood banding of the Stick style was also intended to reflect the new construction method of the time – balloon framing.

An element of the Queen Anne architectural style often seen in the Stick style is the use of varying wall textures. Examples of this element as seen on the Seybold House include the horizontal clapboard siding, the wood shingles in the gable ends, and vertical tongue-and-groove siding along the lower exterior walls of the front porch.

In addition to the stickwork banding and varying wall textures, the Seybold House possesses other defining elements of the Stick style, including decorative gable trusses, verge boards, and brackets on the main section of the house. As mentioned previously, the steeply pitched roofs with exposed rafter tails are also features of the style. The Seybold House possesses both of these features. Another common characteristic of the Stick style is an emphasis on verticality and this can be seen in the tall, narrow appearance of the primary façade and west cross-gabled extension. The corner boards also contribute to this vertical emphasis.

Although the Seybold House is one of two historic houses in Waveland that display Stick style features – the other being located at 501 East Green Street – it remains as the best local example of the style. Both the exterior and interior of the Seybold House possess a high degree of integrity in terms of both stylistic form and elements.

National Register of Historic Places Continuation Sheet

Section number 9, 10 Page 8

Seybold, George, House

Montgomery County, IN

Bibliography

Baker, John Milnes, AIA. American House Styles. W.W. Norton, 1994

Blumenson, John J.-G. Identifying American Architecture: A Pictorial Guide to Styles and Terms, 1600-1945. Nashville, TN: American Association for State and Local History, 1977, 1981.

Foley, Mary Mix. The American House. Harper & Row, 1980.

McAlester, Virginia & Lee. A Field Guide to American Houses. New York: Alfred A. Knopf, Inc., 1984

Montgomery County Interim Report: Indiana Historic Sites and Structures Inventory. Historic Landmarks Foundation of Indiana. May, 1986.

Sharpe, Virginia Banta. A History of Waveland, Indiana. Wabash Valley Printing Company, 1958

Verbal Boundary Description

Lots 49 & 94 in Milligan's 2nd Eastern Addition to the Town of Waveland, Montgomery County, Indiana.

Boundary Justification

These city lots retain their original property lines.

National Register of Historic Places Continuation Sheet

Section number _____ Page 9

Seybold, George, House Montgomery County, IN

Additional Documentation

Photographs

Photo #1

- 1. Seybold, George, House
- 2. Montgomery County, Indiana
- 3. Tommy Kleckner
- 4. November 1, 2001
- 5. Historic Landmarks Foundation of Indiana
- 6. View of property. Photograph taken facing southeast.

Photo #2

6. View of gable end details. Photograph taken facing south.

Photo #3

6. View of north (main) façade of the building. Photograph taken facing southwest.

Photo #4

6. View of front porch details. Photograph taken facing south.

Photo #5

6. View of common bracket and porch details on building. Photograph taken facing east.

Photo #6

6. View of west façade of building. Photograph taken facing east.

Photo #7

6. View of southwest side porch. Photograph taken facing northeast.

Photo #8

6. View of south elevation of main house and rear wing. Photograph taken facing northeast.

Photo #9

6. View of south elevation and southeast side porch. Photograph taken facing northwest.

Photo #10

6. View of east façade of building. Photograph taken facing west.

National Register of Historic Places Continuation Sheet

Section number _____ Page 10

Seybold, George, House

Montgomery County, IN

Additional Documentation (cont.):

Photo #11

6. View of common interior decorative wood panels below windows . Photograph taken facing west.

Photo #12

6. View of front entry door details. Photograph taken facing north.

Photo #13

6. View of front entry hall with dining room beyond doorways. Photograph taken facing south.

Photo #14

6. View of front (north) parlor with fireplace. Photograph taken facing southwest.

Photo #15

6. View of dining room. Photograph taken facing northeast.

Photo #16

6. View of stairway in front entry hall leading to second floor. Photograph taken facing southwest.

Photo #17

6. View of common wood door and trim of second floor. Photograph taken facing southwest.

Photo #18

6. View of third-floor study. Photograph taken facing north.

UNITED STATES DEPARTMENT OF THE INTERIOR NATIONAL PARK SERVICE

NATIONAL REGISTER OF HISTORIC PLACES EVALUATION/RETURN SHEET

REQUESTED ACTION: ADDITIONAL DOCUMENTATION

PROPERTY Seybold, George, House NAME:

MULTIPLE NAME:

STATE & COUNTY: INDIANA, Montgomery

DATE RECEIVED: 2/20/04 DATE OF PENDING LIST: DATE OF 16TH DAY: DATE OF 45TH DAY: 4/04/04 DATE OF WEEKLY LIST:

REFERENCE NUMBER: 02001172

REASONS FOR REVIEW:

APPEAL:NDATAPROBLEM:NLANDSCAPE:NLESSTHAN 50 YEARS:NOTHER:NPDIL:NPERIOD:NPROGRAM UNAPPROVED:NREQUEST:NSAMPLE:NSLRDRAFT:NNATIONAL:N

COMMENT WAIVER: N

ACCEPT RETURN REJECT DATE

ABSTRACT/SUMMARY COMMENTS:

~

RECOM. / CRITERIA	Ω_{0}
REVIEWER CLACK Beall	DISCIPLINE How
TELEPHONE	DATE 3/8/04

DOCUMENTATION see attached comments Y/N see attached SLR Y/N

If a nomination is returned to the nominating authority, the nomination is no longer under consideration by the NPS.

Joseph E. Kernan, Governor John Goss, Director



Indiana Department of Natural Resources

Division of Historic Preservation & Archaeology+402 W. Washington Street, W274 · Indianapolis, IN 46204-2739 Phone 317-232-1646+Fax 317-232-0693 · dhpa@dnr.state.in.us

February 12, 2004

Carol D. Shull Keeper of the National Register of Historic Places National Park Service National Register of Historic Places 1201 Eye Street, NW, 8th floor Washington, D.C. 20005

	RECEIVED 22	
		1
in the second	202	
	GISTER OF HISTO ATIONAL PARK SET	

Dear Ms. Shull,

The George Seybold House in Montgomery County, Indiana was listed in the National Register of Historic Places on October 16, 2002. At that time, no architect was know for the house. It now appears that the house was based on plans from Palliser, Palliser & Company's *Model Homes* of 1878 (see enclosed copy). Also, the same plans and elevations were published in 1888 by the firm as Palliser's *American Architecture*, plate 15.

The Seybold House was built in 1886, so *Model Homes* seems the likely source of the plan. The Seybold House matches closely enough in plan, elevation, and in the described interior molding finishes, that the influence of the Palliser plan is without doubt. We would therefore request that the blank for Architect/Builder for this nomination be changed to read "Palliser, Palliser, & Co."

It also appears that the Charles Newell House in the State of Washington is based on the same Palliser design, though I understand that Howard Spaulding is listed as its architect.

Please contact me if you should have any questions about our request.

Sincererly,

CI Z

Paul C. Diebold Senior Architectural Historian

enclosures: copies from Palliser's Model Homes, copy of photo of the Newell House.

PALLISER'S

MODEL HOMES

DESIGNS FOR MODEL DWELLINGSCIEVEL2Dd, ODI

FARM-BARN AND HENNERY, STABLE AND CARRIAGE HOUSE, SCHOOL HOUSE, MASONIC ASSOCIATION BUILDING, BANK AND LIBRARY, TOWN HALL AND THREE CHURCHES.

TOGETHER WITH A LARGE AMOUNT OF MISCELLANEOUS MATTER, MAKING IN ALL A VERY VALUABLE BOOK FOR EVERY ONE WHO CONTEMPLATES BUILDING.

Fifteenth Thousand.

The genius of the Architect, in his practice, unlike that of the Sculptor and the Painter, which may be manifested in their highest forms almost single handed, and within the four walls of the studio, deals with sterner materials, and has to wield not only the intractabilities of matter, but the even greater intractabilities of men's. adverse wills, and to move the apathy, and frequently the ignorance, of ill-constituted public opinion .-- SIR M. DIGBY WYATT.

STACK.

PALLISER, PALLISER & CO., ARCHITECTS,

NEW YORK.

AUTHORS OF PALLISER'S AMERICAN COTTAGE HOMES, PALLISER'S USEFUL DETAILS, PALLISER'S SPECIFICATIONS, ETC., ETC.

Plate III.

COTTAGE AT WEST STRATFORD, CONN.

This handsome little house is near completion for E. R. Tomlinson, and for a compact strangement of plan cannot be beat. There is a splendid celler under the whole house, arranged for the storage of fuel and other purposes; a wall has also been put down in the cells, which with the clester supplets an unificated annuot of water at the Klichen sink through the aid of a pump. The attic is very spacious, and will be found very useful as a place for drying colloce, or should it be found necessary at some future time two rooms could be finished off, which would be almost as good sleeping rooms as any in the house.

There is but one chimney, which is so placed that it can be used from all the rooms on First floor; the stair-case is also placed in a position to be easy of access from all parts of the house; two doors are placed between the Hall and Kitchen, a feature which cannot fail to commend itself.

The windows in the IIall and staircase are filled entirely with ornamental and stained gins, an are also those in the attic; the other windows in the house have the lower scale, ginzed in two lights of ordinary gins, while the upper such has a while light in center and mult colored lights on each side. The interior is finished in a very pleasing, yet economical manner, the casings of doors and windows are trimmed with a back modil, though they are not mitred at the angles as its smulp! does, but a square black, ornamented with suck work to be picked out in color is placed in the corner, and the molding cut square against it; it is is a decided improvement on the monotonous mitred back mold which we see in nearly every house. The rooms are all of ample accommodation to meet the requirements, and each chamber is supplied with a good closet.

The exterior is very striking, the front gable is very handsome, and is a free rendering of what is known as the Queen Anne style of architecture ; the front veranda and especially the hood over entrance is very pretty—In fact this is one of the prettilly designed Ottages, which will always attract attention.

An architect designs a building with apecial reference to the colors to be used in palating, and as a color is the life of design, his instructions in this resplect Mould be immulely followed if the desired result is to be arrived at. This Cottage is palated wentian red, trimmed with Indian red, the channfers, cut and sank work being ploked on in black, making it very effective and showing the detail boldy. The costs \$1,400, and we colubil if there is any one who can show a prettier house, either in arrangement or especarate for the same price.

Blessed are they who have homes !

Let every man strive to own a home.

Plate III.





