For NPS use only

United States Department of the Interior National Park Service

National Register of Historic Places Inventory—Nomination Form

istoric Places received JAN 2 4 1983 n Form date entered

See instructions in How to Complete National Register Forms
Type all entries—complete applicable sections

1. Name

historic Ra:	inbow Arch (Marsh A	rch) Bridges of Kans	as Thematic la	esources
and/or common	N/A			
2. Loca	ation			
street & number	See individua	1 nomination forms	N/A-	not for publication
city, town	N/A	vicinity of	/	
state	N/A code	e county ^G	eary, Linh, Lyon, M	erokee, Caffey, niamicode
3. Clas	sification	М	ontgomery, and	Shawnee
Category district building(s) structure site object X thematic group	Ownership public private both Public Acquisition in process being considered	Status X occupied unoccupied work in progress Accessible yes: restricted X yes: unrestricted no	Present Use agriculture commercial educational entertainment government industrial military	museum park private residence religious scientific Xtransportation other:
4. Own	er of Prope	rty	•	
name Mul	ltiple ownerships	ee individual nomina	tion forms	
street & number	N/A			
city, town	N / A	vicinity of	state	
5. Loca	tion of Lega	al Descriptio	'n	<u></u>
courthouse, regis	stry of deeds, etc.	See individual nomi	nation forms	
street & number	N/A			
city, town	. N/A		state	
6. Repr	resentation	in Existing S	urveys	
title Inv	ventory of Marsh Ar	ch Bridges has this prop	erty been determined elig	gible? yes X no
date _{Ks. Depa}	rtment of Transport	ation, 1980	federal _X state	e county local
depository for su	rvey records Kansa	s State Historical S	ociety	
city, town	Topeka		state	Kansas

7. Description

Con	diti	on
CON	aiti	on

Condition		Check one
X excellent	deteriorated	unaltered
X_ good	ruins	\underline{X} altered
fair	unexposed	

Check one _ original site moved date _

Describe the present and original (if known) physical appearance

A survey carried out by the Kansas Department of Transportation (KDOT) in 1980 revealed that there are at least 73 Marsh Arch bridges (also called Rainbow arch) currently standing in Kansas. The bridges were discovered through computer files and through information provided by field representatives of KDOT. All of the bridges were inspected by KDOT personnel, and all bridges included in the thematic nomination were inspected by Kansas State Historical Society staff. Photographs, dates of construction, and original plans when available, were provided for the State Historic Preservation Officer's (SHPO) review.

In a signed agreement KDOT and the SHPO consented that they would jointly select some of the bridges for National Register nomination and KDOT would be free to repair or replace the others unless extenuating circumstances developed. It was agreed that should strong local interest in an undesignated bridge develop, or any new significant information come to light, or any previously unidentified bridges be discovered, these would not be covered under the agreement and could be added to the nomination.

The bridges selected for National Register designation were chosen on the basis of their likelihood to survive. The bridges' roadbeds are generally very narrow and therefore subject to replacement. The selected bridges are located for the most part on roads that have been abandoned or are used only locally and are representative of fixed and tied, single and multiple spans. As Historic American Engineering Record officials have mentioned, a multiple span Marsh arch is no more technologically significant than a single span. The same technology is simply repeated. It was therefore not deemed necessary to nominate these bridges on the basis of length.

Of the 73 "rainbow" arches discovered, 27 (37%) were of the tied arch design while 46 (63%) were of the fixed arch design. Thirty-five were located on the state system while the remaining were located either on the county, urban or off-systems. Fifty-six of the bridges consisted of a single span while there were six double spans, eight triple spans, one four-span, one seven-span and one eight-span bridge.

Marsh's plan was to construct a bridge of reinforced concrete using arches that would expand and contract along with the floor under varying condition of temperature and moisture.

The major parts were quite simple, consisting of two abutments or piers, two arches disposed between and springing from the abutments, a floor carried by and between the arches and reaching from abutment to abutment, and the railings. The abutments consisted of footings and three interlocked walls of reinforced concrete.

There were two possibilities for the arch design. The fixed design was more popular in Kansas than the tied design. With the fixed design, the arches, springing from points within the bases of the abutments, passed through the

Continuation sheet

United States Department of the Interior National Park Service

National Register of Historic Places Inventory—Nomination Form

For NPS use only received date entered Page 1

front wall and arched over the stream. Hangars were suspended from the arch and were connected to the ties that supported the floor. A beam was located where the arch crossed the floor. The arches, hangars, and ties became a unified structure when the concrete was poured. The beams were separated from the floor slab by slideable wear plates. The rise and fall of the arch due to longitudinal expansion and contraction could cause the beam to move beneath the ends of the floor. The floor could also expand and contract causing it to move over the beams. The wear plates facilitated such movement. The construction of the short articulated hanger closest to the point where the arch passed through the floor allowed it to move independently also, compensating for movement of the arch. As the other hangars were further from this arch/floor crossing point, and were longer, the arch movement was more readily absorbed and articulation of these members was not necessary.

Item number

7

In the "tied" or "bottom chord" rainbow arch, the arches were connected to the top of the piers with use of cast steel rocker shoes. One of these shoes was engineered to allow for expansion and contraction of the structure and roadway. All this design lacked the massive abutment to asborb or resist horizontal thrust, a bottom chord or tie was added to the arch to fill this function.

The Marsh arch is actually a steel bridge with a concrete coating. Bridge plans reveal the schedule of the concrete placement after the metal framework had been erected. The footings, abutments and/or piers were the first to be concreted. These were followed by the hangers, the arch ribs, and the beams. Expansion plates were placed on the beams in preparation for receiving the floor. Finally, the intermediate ties, floor slab, wall copings and rail were poured. Once the floor centering was struck the intermediate hangars were concreted. Because the hangars had to be under full dead load when they were concreted, the floor centering was struck no less than 10 days or more than 21 after the rest of the concrete was placed. The handrail was the last portion of the bridge to be concreted.

Through the years most of the bridges have been altered in some minor way. Some have been painted, some are covered with graffiti. The decking has been replaced on most of the bridges and some overhead struts that connected one arch to the other have been removed.

NPS Form 10-900-a (3-82)			OMB No. 1024-0018 Exp. 10-31-84
United States Department of the Int National Park Service	terior		For NPS use only
National Register of His	storic Plac	es	received
Inventory-Nomination	Form		date entered
Clarification of selection process for Continuation sheet	Rainbow (Marsh) Item number	Arch 7	Bridge thematic nomination. Page 2

Selecting bridges for inclusion in a thematic National Register nomination is an involved process. Not only must one consider the listing criteria provided by the National Register, but it would be foolish not to take safety and practical concerns into consideration as well. A state's road system will not accomodate itself to the hundreds of old and possibly historic bridges known to exist throughout the state. The bridges must somehow be accomodated to stricter safety codes, heavier vehicles, more traffic, and new standards for roadbeds. Sometimes a roadway will be straightened with the result that a bridge is abandoned in place. This bridge may be maintained by a municipality or a concerned citizen, or be allowed to slowly deteriorate.

More often than not, old bridges found throughout Kansas are on roads that must be brought up to state or federal standards as new projects or maintenance is carried out. Usually this means that a bridge is not wide enough or that its sufficiency rating is not adequate. The result is that the bridge must be replaced.

In the past, hundreds of bridge projects were allowed to proceed in Kansas because the significance of various types of bridges was not known, and money was not available for a statewide survey and analysis. This problem was solved when the Kansas Department of Transportation agreed to undertake a survey of all older bridges throughout the state and to pay a private contractor to do the detailed research and analysis required for the nomination of bridges of each type.

The first thematic bridge nomination submitted by the Kansas Historic Preservation Department as a result of this survey was for Rainbow (Marsh) Arches. It was stated in that nomination that the bridges included were chosen on the basis of their likelihood to survive. This was not the only criteria. Within that group the bridges had to represent the two types of Marsh Arches as well as single and multiple spans of those types. They had to have a high level of integrity.

It has seemed in the past that the National Register has been reluctant to list deteriorated structures that are threatened by imminent destruction unless listing would encourage their preservation. Listing those bridges in Kansas that do not meet modern safety codes and road requirements would not encourage their preservation but would cause a severe rift between two state agencies that are currently striving to work together on a very delicate situation. It is hoped in the future that a large percentage of each bridge class will be nominated, but in the meantime we must settle for saving at least some of the bridges rather that none.

Submitted April 6, 1983.

8. Significance

Period prehistoric 1400–1499 1500–1599 1600–1699 1700–1799 1800–1899 1900–	Areas of Significance—C archeology-prehistoric archeology-historic agriculture architecture art commerce communications	heck and justify below community planning conservation economics education engineering exploration/settlement industry invention	Iandscape architecture Iaw ' Iiterature Iiterature Iitary music Philosophy Politics/government	e religion science sculpture social/ humanitarian theater transportation other (specify)
Specific dates	,	Builder/Architect		

Statement of Significance (in one paragraph)

The Marsh arch is an attractive and well-engineered bridge such as one does not see built anymore in this day of strict utilitarianism. In the history of bridge engineering, the Marsh arch does not represent any great technological break-through but is rather one of the many ways in which reinforced concrete was used in the early 20th century, and fits into the mainstream of bridge design for that period.

Bridges were for centuries combinations of artistic expression and engineering expertise. Although the architectural and artistic aspects of bridge-building seem to have been forgotten in the last few decades, as late as the 1930's the combination of aesthetics with technology in utilitatian structures was viewed as the goal toward which engineers and architects alike should strive. As Wilbur J. Watson, a respected engineer, wrote in 1926, "It is highly desirable that utilitatian structures, such as bridges, should be pleasing to the eye as it is practicable to make them, and that there should be greater collaboration between the Architect and the Engineer, with a realization on the part of each that science without art is apt to be unattractive, and art without science inefficient." The Marsh arch bridges in Kansas are a result of this combination of engineering and architecture. They are products of an era when aesthetics were still as important as utilitatianism.

Carl Condit wrote of concrete bridges that by 1910 "the main line of evolution was moving away from massive construction, with echoes of the masonry tradition, toward the flattened parabolic curves of narrow ribs, the slender spandrel posts, and the minimal piers that scientific reinforcing was to make possible." One finds all of these characteristics present in the Marsh arch.

The earliest known Marsh arch in Kansas was built in 1917, the latest in 1934. Construction of the arches reached a peak in the late 1920's and declined after 1930. Those chosen for nomination span the period from 1923 to 1932.

THIS STATEMENT REFLECTS CURRENT KNOWLEDGE AND IS SUBJECT TO AMENDMENT.

· · · · ·

9. Major Bibliographical References

	Condit, Carl W Steinman, Davi Publicatior Watson, Wilbur	N. <u>American Build</u> id B. & Sara Ruth ns Inc., 1941, rpt r J. <u>A Decade of I</u>	ing Watson. Bridges & t 1957. Bridges, 1926-1936.	Their builders. NY: Dover Cleveland: J.H. Jansen, 1937.
10.	Geograp	hical Data	See Individual No	omination Forms
Acreage Quadran UT M Ref	of nominated proper igle name erences	rty		Quadrangle scale
	Easting	Northing		Northing
Verbal	boundary descript	tion and justification	[3] a M.C. at Kow Dow Model + 4	
List all	states and counti	es for properties ove	county	ty boundaries
	N/A			45
			county	code
organiza	e Nora Pat tion Kansas St	Small, Architectu ate Historical So t Tenth	ral Historian cietyHPD date	hone 913 296-3251
city or to			state	Kanana 66612
12.	State Hi	storic Pres	servation Of	fficer Certification
The eval	uated significance of	f this property within the	e state is:	
	national	_X_ state	local	
As the do 665), I he accordin State His	esignated State Histo ereby nominate this p g to the criteria and storic Preservation O	oric Preservation Office property for inclusion in procedures set forth by	r for the National Historic the National Register and the National Park Service	Preservation Act of 1966 (Public Law 89– d certify that it has been evaluated e.
title _{Ex}	Director & St	ate Historic Rres	ervation Officer	date January 4, 1983
For N	PS use only ereby certify that this	s property is included in	ہ the National Register ک	date 3/10/83
1 Keep	er of the National R	eaister		

Chief of Registration

.

United States Department of the Interior National Park Service

10. Blacksmith Creek Bridge

National Register of Historic Places Inventory—Nomination Form

					*
For NPS use	o aniy				
received					
date entere	d				
P	age	1	4	1	

ntinuation sheet	Item number	r	Page 141
	Multiple Resour Thematic G	rce Area roup	dnr-11
Name <u>Rainbow Arc</u> State <u>Kansas</u>	ch (Marsh Arch) Bridges of Ka	nsas Themat	ic Resources
Nomination/Type of	Review		Date/Signature
⁶ 1. Cedar Creek Bri	idge National Register	Keeper	3/10/83 XulunsByun
² 2. Brush Creek Bri	Uncored in 6 Idge National Register	Attest Keeper	3/10/83 Almabyen
✤3. Neosho River Br	Entered in idge Estimal Register	Attest Keeper	3/au/8 3 Delous Byen
4. Conroe Bridge	Bolizense Boosener. Bolizense Boosener	Attest f Keeper	3/cu/83 XulourByer
3. Mine Creek Brid	lge Intered in the	Attest fKeeper	3/10/83 Alloustym
6. Soden's Grove H	Bridge Committed all the and other	Attest Keeper-	Janan Me Chelland
7. Creamery Bridge	Entere d in the National Regi ster	Attest Keeper	3/10/83 Helmespyer
8. Pottawatomie Cr	eek Bridge matica in the National Register	Attest f Keeper	3/col83 Alous Byen
9. Dewlen-Spohnhau	uer Bridge Mational Register	Attest f Keeper	3/10/83 Xbelong Sym
		Attest	

Entered in the Intered in the Interest freeper 3/10/83 Keloungsym United States Department of the Interior National Park Service

National Register of Historic Places Continuation Sheet

Section number _____ Page _____

Rainbow Arch (Marsh Arch) Bridges of Kansas MPS

11. Mack, John, Bridge

Antonia in the Thistophic Accusing

1/22/92