UNITED STATES DEPARTMENT OF THE INTERIOR NATIONAL PARK SERVICE

NATIONAL REGISTER OF HISTORIC PLACES INVENTORY -- NOMINATION FORM

101		

RECEIVED

DATE ENTERED

SEE INSTRUCTIONS IN HOW TO COMPLETE NATIONAL REGISTER FORMS TYPE ALL ENTRIES -- COMPLETE APPLICABLE SECTIONS

	Preader Peactor #1			
AND/OR COMMON Experimental	Preader Deactor #1			
Experimental	Breeuer Reactor #1			
	1 Breeder Reactor #1	•••		
LOCATION				
STREET & NUMBER	SE1/4, of NE 1/4, of	SW 1/4, Section 9		
T2N, R9E	Boise Meridian		NOT FOR PUBLICATION	
CITY, TOWN	-		CUNGRESSIONAL DISTRI	СТ
Arco	XX	VICINITY OF	2nd	CODE
state Idaho		CODE 16	Butte	023
CLASSIFIC/	ATION			
CATEGORY	OWNERSHIP	STATUS	PRESI	ENTUSE
DISTRICT	X_PUBLIC	OCCUPIED	AGRICULTURE	XMUSEUM
BUILDING(S)	PRIVATE		COMMERCIAL	PARK
STRUCTURE	ВОТН	WORK IN PROGRESS	-EDUCATIONAL	PRIVATE RESIDENC
SITE XX	PUBLIC ACQUISITION	ACCESSIBLE	ENTERTAINMENT	RELIGIOUS
XX OBJECT	IN PROCESS	XYES: RESTRICTED	X_GOVERNMENT	SCIENTIFIC
	BEING CONSIDERED	YES: UNRESTRICTED	INDUSTRIAL	
•		NO	MILITARY -	OTHER:
NAME	PROPERTY Contac Office Department of E		t. 1317	
STREET & NUMBER	(Interpretation	of the site is by	National Park Se	rvice staff.
550 Second Str		f the Moon National		
CITY, TOWN			STATE	
Idaho Falls		VICINITY OF	Idaho	83401
LOCATION	OF LEGAL DESCR	IPTION		
COURTHOUSE. REGISTRY OF DEEDS, ET	^{rc.} Butte County C			
STREET & NUMBER	Burre county c			
CITY. TOWN			STATE	
	TATION IN EXIST	NG SURVEYS		
REPRESEN'			ric Iandmark Plat	-
TITLE	tal Breeder Reactor	11. National Hietor	ידרי דיצארוראוזסדר עד דקו	-
TITLE	tal Breeder Reactor	······································	ATE X COLUMN	
TITLE Experiment DATE DEPOSITORY FOR		FEDERALST	TATE X_COUNTY _LOCAL	
TITLE Experiment DATE DEPOSITORY FOR	tal Breeder Reactor	FEDERALST	TATE X_COUNTYLOCAL	

7 DESCRIPTION

CONDITION		CHECK ONE	CHECK ONE		
XX	DETERIORATED	XXUNALTERED	_XORIGINAL	SITE	
GOOD	RUINS	ALTERED	MOVED	DATE	
FAIR	UNEXPOSED	(decommissionedinactive)			

DESCRIBE THE PRESENT AND ORIGINAL (IF KNOWN) PHYSICAL APPEARANCE The Idaho National Engineering Laboratory, which was formerly the National Reactor Testing Station established in 1949 by the Atomic Energy Commission (now administered by the Energy Research and Development Administration), is a complex of nuclear facilities distributed over 894 square miles of desert land in southeastern Idaho. This desolate site was initially chosen because of its isolation, its large supply of underground water and its earthquake-free history. Here the largest concentration of experimental breeder-reactors in the world have been built, including reactors for safety research, materials testing, electric power, and naval propulsion.

The EBR-I area, situated in the southwest part of the Idaho National Engineering Lab, comprised at its largest, the Experimental Breeder Reactor No. 1, the Argonne Fast Source Reactor, BORAX-V, and the Zero Power Reactor No. 3. Construction work by the AEC at the Station began in this area in May 1949 with the drilling of the EBR-I well. The EBR-I, the first major facility built at the testing station, was completed in Arpil 1951, at a total cost of approximately \$2,700,000.

All of the buildings presently located at the EBR-1 site were in existence in 1964 when EBR-1 was decommissioned. However, only the EBR-I building was directly associated with the operation of the EBR-I reactor. The building, a buff-colored rectangular brick structure with a one-story north section and a two-story south section is located on the west side of the small complex and is the largest building there.

The building was essentially constructed around the reactor and the interior is split into three levels with special working rooms and equipment designed and built into the structure especially for the handling of this reactor and its products. Most of the equipment presently located within the building is historic--it was used during the operation of the EBR-I. Since the building is open to the public, various safety precautions have been taken, and some materials probably have been removed.

During its operational lifetime EBR-1 was fueled with three cores of uranium 235, each of a somewhat different physical construction, and finally with a core of plutonium--the first power reactor ever to be so fueled. EBR-I operation at full power is about 1 megawatt (one million watts). The critical mass on December 21, 1951, when the reactor was brought to full power was 52 kilograms of U-235 (114 lbs.) and the core of fissionable material was about the size of a football.

The reactor consists of three principal parts: the core, an inner blanket of uranium surrounding the core, and a denser outer blanket. The outer aircooled breeding blanket is made up of keystone-shaped natural uranium bricks which, when assembled, form a cup that may be moved up to surround the coreinner blanket assembly or dropped down to shut off the reaction.



PERIOD

AREAS OF SIGNIFICANCE -- CHECK AND JUSTIFY BELOW

- ___ARCHEOLOGY-PREHISTORIC ___COMMUNITY PLANNING ___PREHISTORIC __CONSERVATION ___1400-1499 ___ARCHEOLOGY-HISTORIC ___ECONOMICS ___AGRICULTURE ___EDUCATION __1600-1699 ___ARCHITECTURE ___ENGINEERING ___1700-1799 ___ART ___EXPLORATION/SETTLEMENT __COMMERCE ___1800-1899 <u>X 1900-</u> __INDUSTRY __COMMUNICATIONS __INVENTION
 - INING __LANDSCAPE ARCHITECTURE __LAW __LITERATURE __MILITARY __MUSIC TLEMENT __PHILOSOPHY __POLITICS/GOVERNMENT
- ___RELIGION
- ___SCULPTURE
- __SOCIAL/HUMANITARIAN
- ___THEATER
- ___TRANSPORTATION
- __OTHER (SPECIFY)

SPECIFIC DATES 1950-1964 (in operation) BUILDER/ARCHITECT

STATEMENT OF SIGNIFICANCE

The Experimental Breeder Reactor No. 1 of the Idaho National Engineering Lab demonstrated that a nuclear reactor, designed to operate in the high-energy neutron range, is capable of breeding (creating more fuel than its operation consumes) and also of achieving ecomonically competitive nuclear power.

This reactor, was the first reactor built in the Atomic Energy Commission's program to derive electric power for civilian use from atomic energy. On December 20, 1951, the EBR-I produced the first usable amounts of electricity created by nuclear means. The reactor is also noted for having been the first to achieve a self-sustaining chain reaction using plutonium instead of uranium as the major component in the fuel, in July 1963. The EBR-I was the first reactor used to demonstrate the feasibility of using liquid metal (sodium potassium) at high temperatures as a reactor coolant.

EBR-I sustained initial criticality in 1951 and was decommissioned early in 1964 for lack of further assignments.

The concept of a breeder reactor was known to the scientists working on the United States' wartime atomic energy program in the early 1940s. Experiments indicated that breeding nuclear fuel would be possible in a properly designed reactor. However at that time there was neither time nor resources to undertake such a project.

After the war, the newly established Atomic Energy Commission directed some of their agency's efforts to developing peaceful uses of the atom. The large amounts of uranium located in the 1950s were then unknown and uranium was in very short supply. Consequently the first prototype power reactor built was an attempt to prove the theory of fuel breeding.

EBR-I construction began late in 1949 at the new National Reactor Testing Station in Idaho. Early in 1951, a few months before the EBR-I building was completed, nine staff members from the AEC's Argonne National Laboratory in Illinois, arrived to install the reactor which they had designed at a laboratory near Chicago.

9 MAJOR BIBLIOGRAPHICAL REFERENCES

Report of the U.S. Atomic Energy Commission historian proposing national historic landmark sites associated with atomic energy. Historic Sites Survey files 1965.

Information book and pamphlets prepared by National Reactor Testing Station, U.S. Atomic Energy Commission, Idaho Falls, Idaho. (copies in file)

	10 GEOGRAPHICAL DATA ACREAGE OF NOMINATED PROPERTY 0.9508 acres UTM REFERENCES	
-	A 1 2 3 3 7 8 8 0 4 8 1 9 3 5 0 E ZONE EASTING NORTHING C 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	ZONE EASTING NORTHING
1	That portion of the SE 1/4, NE 1/4, SW 1/4, Boise Meridian, better described as follows	Section 9, T2N, R29E, of the
ŀ	Beginning at a lava stone marking the South Township 2 North, Range 29 East of the Boise Butte, State of Idaho, and running West 129.	Meridian, County of
]	side of said Section 9; thence North 1,316.7 marking the South East Corner of the Propert BEGINNING; thence North 72 [°] 10'11'' West 156.0 thence North 1.7 [°] 49'49'' East 265.50 feet to a 72 [°] 10'11'' East 156.00 feet to a brass cap; t West 265.50 feet to a brass cap, the TRUE PC	'l feet to a brass cap y, the TRUE POINT of 00 feet to a brass cap; 1 brass cap; thence South 2 hence South 17°49'49''
	11 FORM PREPARED BY	
	NAME / TITLE	
-	Blanche Higgins Schroer, Landmark Review	Project DATE
	Historic Sites Survey - National Park Ser	
•	STREET & NUMBER	TELEPHONE
	1100 L Street NW.	
	CITY OR TOWN	STATE
	Washington	D.C
	12 STATE HISTORIC PRESERVATION OF	FICER CERTIFICATION
	THE EVALUATED SIGNIFICANCE OF THIS P	ROPERTY WITHIN THE STATE IS:
STURIC S),	NATIONAL STATE	LOCAL
(NATIONAL HISTO LANDMARKS),	As the designated State Historic Preservation Officer for the National hereby nominate this property for inclusion in the National Register criteria and procedures set forth by the National Park Service.	
NDI	FEDERAL REPRESENTATIVE SIGNATURE	LANDMARKS)
ATLC LA	TITLE	DATE
		DATE 4/16/84
	ATTEST: KEEPER OF THE NATIONAL REGISTER	DATE

Form No. 10-300a (Rev. 10-74)

UNITED STATES DEPARTMENT OF THE INTERIOR NATIONAL PARK SERVICE

NATIONAL REGISTER OF HISTORIC PLACES INVENTORY -- NOMINATION FORM

FOR NPS USE ONLY RECEIVED DATE ENTERED

Experimental Breeder Reactor #1

CONTINUATION SHEET	ITEM NUMBER	7	PAGE	2	

Both the core and inner blanket consist of subassemblies, hexagonal in cross-section, filled with cylindrical rods of small diameter. The metallic fuel material is 7.5 inches of uranium enriched in the isotope U-235, with a section of natural uranium blanket above and below it.

Heat generated in the reactor core is transferred to the sodium-potassium coolant in the primary system, which becomes intensely radioactive in the high neutron flux. Heat is then transferred to a second sodium-potassium system, which does not become radio-active, and the secondary heat is used to manufacture steam in a bank of steam generators. Thus, the possibility of contact of radioactive coolant with water, which could be reactive in nature, is avoided. The steam produces operates through a conventional turbine-generator system to reproduce electricity.

The buildings located to the east of EBR-I, although built there prior to 1964 when EBR-I was decommissioned, were not associated with its operation. They were built for use by other reactors between 1955 and 1959. The EBR-I building, and the guard shack to the northeast, although still maintained by DOE, were open to the public as a museum and interpreted by the National Park Service during the summer of 1975.

NATIONAL REGISTER OF HISTORIC PLACES INVENTORY -- NOMINATION FORM

Experimental Breeder Reactor #1

CONTINUATION SHEET

ITEM NUMBER 8 PAGE 2

In May of 1951 the first attempt to operate the new reactor was unsuccessful, since it was determined there was not sufficient fuel in the core. The next three months were spent acquiring additional uranium and refabricating larger fuel rods. Then, on August 24, Dr. Walter Zinn and his Argonne staff brought EBR-I to criticality (a controlled, self-sustained reaction) with a core about the size of a football.* For the next several months the reactor was placed on low power operation while the scientists observed their new invention.


December 20, 1951, the first historic EBR-I experiment began. The reactor was started and the power gradually increased over a period of several hours. At 1:50 p.m. the first electricity ever generated from a nuclear reaction began flowing from the EBR-I turbine generator and four light bulbs were lit by its power. The next day the experiment was repeated and the reactor generated enough electricity to power the EBR-I building.

EBR-I's chief purpose was to determine whether theoretical calculations on fuel breeding could be realized: that more nuclear fuel could be created in a reactor than it consumed while operating. Less than a year after EBR-I generated its first electricity, Argonne scientists calculated that the reactor could indeed breed fuel. In 1953 a laboratory analysis indicated that EBR-I was producing one new atom of a nuclear fuel for each atom consumed.

With fuel breeding a proven fact, Argonne scientists began to design cores that would increase the breeding ratio so that one reactor could not only sustain its own operation but also produce surplus fuel for additional reactors. Three such improved cores were developed over the next ten years. The last of them--called Mark IV-- produces 1.27 new atoms of fuel for each atom consumed.

Since these earliest EBR-I experiments, scientists and engineers at what is now called the Idaho National Engineering Laboratory and elsewhere haveworked to scale up and improve technology pioneered in the relatively small EBR-I power plant. A larger version, EBR-II began operating at the Idaho testing station in 1964. EBR-II has operated safely for more than ten years and has generated enough electricity to supply a city of 35,000 for two years. EBR-II is still basically an experimental model reactor, providing information for development of fuels and composition for even larger breeder reactors.

*Although the core is equivalent in approximate size to a football, its shape and size more nearly match a two-pound coffee can.



NATIONAL REGISTER OF HISTORIC PLACES INVENTORY -- NOMINATION FORM

FOR NPS USE ONLY RECEIVED DATE ENTERED

Experimental Breeder Reactor #1

CONTINUATION SHEET	ITEM NUMBER 8	PAGE 3	

EBR-I was indeed a critical accomplishment in atomic energy research which now has established a power reactor concept utilizing a source of energy more than 2,000 times greater than the world's supply of fossil fuels.

IDAHO FALLS

