

PH035-1440

UNITED STATES DEPARTMENT OF THE INTERIOR  
NATIONAL PARK SERVICE

# DATA SHEET

## NATIONAL REGISTER OF HISTORIC PLACES INVENTORY -- NOMINATION FORM

FOR NPS USE ONLY  
RECEIVED FEB 24 1977  
DATE ENTERED SEP 15 1977

SEE INSTRUCTIONS IN HOW TO COMPLETE NATIONAL REGISTER FORMS  
TYPE ALL ENTRIES -- COMPLETE APPLICABLE SECTIONS

### 1 NAME

HISTORIC  Susitna River Bridge (AHRs SITE NO. TLM-006)

AND/OR COMMON  
Gold Creek Bridge

### 2 LOCATION

STREET & NUMBER  
ARR Mile 264.1

CITY, TOWN  
Gold Creek

VICINITY OF

CONGRESSIONAL DISTRICT  
At Large

STATE  
Alaska

CODE  
02

COUNTY  
Yukon-Koyukuk Dov. CODE  
290

### 3 CLASSIFICATION

CATEGORY	OWNERSHIP	STATUS	PRESENT USE
<input type="checkbox"/> DISTRICT	<input checked="" type="checkbox"/> PUBLIC	<input checked="" type="checkbox"/> OCCUPIED	<input type="checkbox"/> AGRICULTURE <input type="checkbox"/> MUSEUM
<input type="checkbox"/> BUILDING(S)	<input type="checkbox"/> PRIVATE	<input type="checkbox"/> UNOCCUPIED	<input type="checkbox"/> COMMERCIAL <input type="checkbox"/> PARK
<input checked="" type="checkbox"/> STRUCTURE	<input type="checkbox"/> BOTH	<input type="checkbox"/> WORK IN PROGRESS	<input type="checkbox"/> EDUCATIONAL <input type="checkbox"/> PRIVATE RESIDENCE
<input type="checkbox"/> SITE	<b>PUBLIC ACQUISITION</b>	<b>ACCESSIBLE</b>	<input type="checkbox"/> ENTERTAINMENT <input type="checkbox"/> RELIGIOUS
<input type="checkbox"/> OBJECT	<input type="checkbox"/> IN PROCESS	<input type="checkbox"/> YES: RESTRICTED	<input type="checkbox"/> GOVERNMENT <input type="checkbox"/> SCIENTIFIC
	<input type="checkbox"/> BEING CONSIDERED	<input checked="" type="checkbox"/> YES: UNRESTRICTED	<input type="checkbox"/> INDUSTRIAL <input checked="" type="checkbox"/> TRANSPORTATION
		<input type="checkbox"/> NO	<input type="checkbox"/> MILITARY <input type="checkbox"/> OTHER:

### 4 OWNER OF PROPERTY

NAME  
Alaska Railroad  
U.S. Department of Transportation (907) 265-2411

STREET & NUMBER  
Pouch 7-2111

CITY, TOWN  
Anchorage

VICINITY OF

STATE  
Alaska 99501

### 5 LOCATION OF LEGAL DESCRIPTION

COURTHOUSE REGISTRY OF DEEDS, ETC.  
Alaska Railroad  
U.S. Department of Transportation (907) 265-2411

STREET & NUMBER  
Pouch 7-2111

CITY, TOWN  
Anchorage

STATE  
Alaska 99501

### 6 REPRESENTATION IN EXISTING SURVEYS

TITLE  
Alaska Heritage Resources Survey (AHRs)

DATE  
April 8, 1975

FEDERAL  STATE  COUNTY  LOCAL

DEPOSITORY FOR SURVEY RECORDS  
Alaska Division of Parks, 323 E. 4th Avenue

CITY, TOWN  
Anchorage

STATE  
Alaska 99501

# 7 DESCRIPTION

CONDITION		CHECK ONE	CHECK ONE
<input checked="" type="checkbox"/> EXCELLENT	<input type="checkbox"/> DETERIORATED	<input type="checkbox"/> UNALTERED	<input checked="" type="checkbox"/> ORIGINAL SITE
<input type="checkbox"/> GOOD	<input type="checkbox"/> RUINS	<input checked="" type="checkbox"/> ALTERED	<input type="checkbox"/> MOVED      DATE _____
<input type="checkbox"/> FAIR	<input type="checkbox"/> UNEXPOSED		

## DESCRIBE THE PRESENT AND ORIGINAL (IF KNOWN) PHYSICAL APPEARANCE

This bridge is at Mile 264.1 on the Alaska Railroad, where the right-of-way crosses the Susitna River at the head of navigation on that river. As one faces north, toward the right hand side of the bridge, the river approaches from the east, while on the left it proceeds in a generally southerly direction to the point where it empties into Cook Inlet.

The bridge design embodied a quarter-mile of track over its bridge and trestlework, with the principal section a 504-foot through-truss span over the main river channel. The quarter mile of track was divided into seven distinct parts. Traveling from south to north, there was, first, 392 feet of approach trestlework. This was succeeded by bridge spans of 70, 121, 504, 121, and 70 feet respectively. Then, at the north end, a short 28 feet of trestle, as the road passed from the river onto the bank. From time to time the sections of the bridge have been upgraded so that they now are all of steel construction, in succession, a 42-foot trestle, 70-foot thru girder, 70-foot thru girder, 504-foot truss, 70-foot thru girder, and 42-foot trestle.

The main span was of all-steel construction. However, timber was used on all approach spans, due to the high price of bridge steel at the time and the need for economy. The main piers were designed and built to sustain 200-foot steel approach spans, with the idea that at some future time such spans could be installed in place of the original combinations of timber construction.

Work on the piers was begun May 22, 1920. The final steel was erected on February 2, 1921, and the first train crossed over on February 6, 1921. In 1935, the wooden trestles in the north approach were replaced by seventy-foot steel plate girder spans, and additional steel replacements were installed and piers shored up during the 1950's and 1960's. Successive up-gradings of the structural fabric and members has adhered to the principals of the original design.

### Summary

Dates of construction: 1920-1921 (504' Span)  
Manufacturer: American Bridge Company, Gary, Indiana  
Engineer: Col. Frederick Mears, USA, Chief Engineer  
          Walter E. Angier, C.E., Consulting Engineer  
          F.A. Hanson, Construction Engineer  
          W.J.H. Fogelstrom, Bridge Engineer  
Association with Railroad: Alaska Railroad  
Substructure: Concrete and Steel  
Material of Abutments and Piers: Concrete  
Superstructure: Steel  
Type of Truss: Through-truss

# 8 SIGNIFICANCE

PERIOD	AREAS OF SIGNIFICANCE -- CHECK AND JUSTIFY BELOW			
<input type="checkbox"/> PREHISTORIC	<input type="checkbox"/> ARCHEOLOGY-PREHISTORIC	<input type="checkbox"/> COMMUNITY PLANNING	<input type="checkbox"/> LANDSCAPE ARCHITECTURE	<input type="checkbox"/> RELIGION
<input type="checkbox"/> 1400-1499	<input type="checkbox"/> ARCHEOLOGY-HISTORIC	<input type="checkbox"/> CONSERVATION	<input type="checkbox"/> LAW	<input type="checkbox"/> SCIENCE
<input type="checkbox"/> 1500-1599	<input type="checkbox"/> AGRICULTURE	<input type="checkbox"/> ECONOMICS	<input type="checkbox"/> LITERATURE	<input type="checkbox"/> SCULPTURE
<input type="checkbox"/> 1600-1699	<input type="checkbox"/> ARCHITECTURE	<input type="checkbox"/> EDUCATION	<input type="checkbox"/> MILITARY	<input type="checkbox"/> SOCIAL/HUMANITARIAN
<input type="checkbox"/> 1700-1799	<input type="checkbox"/> ART	<input checked="" type="checkbox"/> ENGINEERING	<input type="checkbox"/> MUSIC	<input type="checkbox"/> THEATER
<input type="checkbox"/> 1800-1899	<input type="checkbox"/> COMMERCE	<input type="checkbox"/> EXPLORATION/SETTLEMENT	<input type="checkbox"/> PHILOSOPHY	<input type="checkbox"/> TRANSPORTATION
<input checked="" type="checkbox"/> 1900-	<input type="checkbox"/> COMMUNICATIONS	<input type="checkbox"/> INDUSTRY	<input type="checkbox"/> POLITICS/GOVERNMENT	<input type="checkbox"/> OTHER (SPECIFY)
		<input type="checkbox"/> INVENTION		

SPECIFIC DATES	1920-1921 (504' Span)	BUILDER/ARCHITECT	Col. Frederick Mears, Chief Engineer Walter E. Angier, C.E., Consulting Engineer F.A. Hanson, Construction Engineer W.J.H. Fogelstrom, Bridge Engineer
----------------	-----------------------	-------------------	--

STATEMENT OF SIGNIFICANCE

The successful completion of this structure marked completion of the first of a series of major bridges required for construction of the Alaska Railroad between the Tanana Valley and a warm-water port on the south-central coast. Construction of the foundation piers for erection of the bridge presented difficult and unforeseeable technical problems in Arctic construction, never before encountered during a major construction project. The solutions decided upon and put into practice in the field were innovations that became standard procedure in Arctic engineering and construction technology. These techniques were utilized in construction of the remaining major bridges of the Alaska Railroad, and have been reinvented during construction of the Trans-Alaska Oil Pipeline from Prudhoe Bay to Valdez.

Historical Narrative:

The planners of the Alaska Railroad surveyed alternate routes from Anchorage north to Fairbanks so as to choose the most desirable routing both for original construction and for long term maintenance of the line. Passing north from the Matanuska Valley there was no way that the railroad could avoid some route through the Alaska Mountain Range, a northern prolongation of the Rocky Mountain System. There are many streams and valleys on the flanks of that range, while slopes go on up to the heights of Mt. McKinley and Mt. Foraker.

For many miles the route selected followed the Susitna River, clinging to its eastern bank, until the crossing was made, bridging the river 264.1 rail miles north of Seward, where the first of the major clear span steel bridges was constructed on the line north of Anchorage.

The engineers attempted to ascertain all possible facts, so that allowances could be made for unforeseen problems when they arose. Standard pre-construction studies were conducted and results and measurements recorded, so that the engineers would have all available information and data at their fingertips to anticipate problems that the Alaska winters and spring break-ups would probably bring.

The railroad planners took into account the effects of the wind on the bridge structure, as it would be affected unladen and with a train crossing load. For study of the foundation required, test borings were put down 60 and 70 feet into the bed of the river, showing underlying strata consisting of compact sand, gravel, and big boulders.

# 9 MAJOR BIBLIOGRAPHICAL REFERENCES

See Continuation Sheet

## 10 GEOGRAPHICAL DATA

ACREAGE OF NOMINATED PROPERTY less than 1 acre

UTM REFERENCES

A	0,6	3,6,2	5,7,5	6,9	6,2	4,5,0	B			
	ZONE	EASTING	NORTHING	ZONE	EASTING	NORTHING				
C				D						

VERBAL BOUNDARY DESCRIPTION

Not Applicable

LIST ALL STATES AND COUNTIES FOR PROPERTIES OVERLAPPING STATE OR COUNTY BOUNDARIES

STATE	CODE	COUNTY	CODE
STATE	CODE	COUNTY	CODE

## 11 FORM PREPARED BY

NAME / TITLE

Alfred Mongin, Architectural Historian

ORGANIZATION

Alaska Division of Parks

DATE

December 14, 1976

STREET & NUMBER

323 East 4th Avenue

TELEPHONE

(907) 274-4679

CITY OR TOWN

Anchorage

STATE

Alaska 99501

## 12 STATE HISTORIC PRESERVATION OFFICER CERTIFICATION

THE EVALUATED SIGNIFICANCE OF THIS PROPERTY WITHIN THE STATE IS:

NATIONAL

STATE

LOCAL

As the designated State Historic Preservation Officer for the National Historic Preservation Act of 1966 (Public Law 89-665), I hereby nominate this property for inclusion in the National Register and certify that it has been evaluated according to the criteria and procedures set forth by the National Park Service.

STATE HISTORIC PRESERVATION OFFICER SIGNATURE

*Russell W. Cahill*

TITLE SHPO

DATE 2/8/1977

FOR NPS USE ONLY

I HEREBY CERTIFY THAT THIS PROPERTY IS INCLUDED IN THE NATIONAL REGISTER

DIRECTOR, OFFICE OF ARCHAEOLOGY AND HISTORIC PRESERVATION	KEEPER OF THE NATIONAL REGISTER
ATTEST: <i>Charles H. ...</i>	DATE <u>2/7/77</u>
KEEPER OF THE NATIONAL REGISTER	

UNITED STATES DEPARTMENT OF THE INTERIOR  
NATIONAL PARK SERVICE

**NATIONAL REGISTER OF HISTORIC PLACES  
INVENTORY -- NOMINATION FORM**

FOR NPS USE ONLY	
RECEIVED	FEB 24 1977
DATE ENTERED	SEP 15 1977

Susitna River Bridge (AHRS SITE NO. TLM-006)

CONTINUATION SHEET

ITEM NUMBER 8 PAGE 1 of 3

The subsurface situation was judged to be of such a kind that the sinking of piles beneath the foundation layers of the piers would be unnecessary. One of the problems considered most difficult was the effect of river ice on the bridge piers.

There is, naturally, plenty of ice in Alaska, especially in the winter time. A large volume comes down the Susitna River and swirls past the bridge site during spring break-up. The planners believed that the ice break-up in the spring occurred before the ice had softened. Great pieces of solid ice swung down the river, jamming themselves into islands, bars and shore, as the river negotiated its turns and twists. The ice piled up and restrained the river. The water level rose and produced increased pressure against the ice jams. After a time, the ice might yield and then rush on to get into another jam farther downstream. The engineers questioned what would happen to bridge piers exposed to jams and rushes. They appeared to have given little attention to the possibility of using timber piers. Concrete, it seems, was thought hardly certain to be equal to the job of withstanding perfectly the harsh scouring action of an ice jam against the pier. Such action would not be confined to high water, but to surfaces all the way down to river bottom.

Concrete piers were decided upon. Obviously the belief was that they would be equal to any force, if they were sufficiently massive. Steel-rod reinforcing of structural concrete had been introduced less than ten years earlier, but that technique appears to have not been considered for use here.

Consideration was given to spanning the main channel of the river by two center spans, each 250 feet long. The two span concept was considered in competition with a single 500 foot span. The former would have required not only three piers, but one would have been near the center of the river channel, in a position of maximum danger from ice buffeting. The cost was less for construction of the single span, and that was the design selected.

The end of steel tracks being laid was still a score of miles to the south when work was started toward pier construction for the Susitna River Bridge on May 22, 1920. A temporary trestle was put across the river parallel to the bridge site, and track was laid on it, facilitating movement of freight onward and delivery of construction materials to the north bank of the river. By September track construction advanced north to the bridge site.

In September 1920 the south pier was completed and work on the north pier begun when the south pier suffered a partial failure. The failure was at first attributed to poor materials. This first conclusion proved inaccurate.

UNITED STATES DEPARTMENT OF THE INTERIOR  
NATIONAL PARK SERVICE

**NATIONAL REGISTER OF HISTORIC PLACES  
INVENTORY -- NOMINATION FORM**

FOR NPS USE ONLY	
RECEIVED	FEB 24 1977
DATE ENTERED	SEP 15 1977

CONTINUATION SHEET

ITEM NUMBER 8

PAGE 2 of 3

A method of dry construction had been employed for construction of the south bridge pier. The wall consisted of Wakefield piles.\* These piles, when properly driven into the river bed, created a wooden diaphragm everywhere interlocked. In pouring the concrete for the piers, within these cofferdams, difficulty was experienced from more than one direction. At the bridge site, there was a gravel bank, with intermingled sand. Though the sand was deficient in relative amounts that was something that could be corrected. Nevertheless, there occurred a partial failure of one of the piers. The failure was at first ascribed to the presence of humus in the aggregate; then to a combination of poor quality of cement, the presence of humus, and to the low temperature for setting the concrete, the latter most dangerous to successful setting and curing of the material.

The root problem, however, was one unique to the character of the sub-river-bottom strata. The cofferdam presented a water-free area, which put the river bed, consisting of porous material, under a 22-foot head of water. This meant an upward pressure over the bottom surface of at least 9 1/2 pounds per square inch, from the fluids in the porous sub-strata. It was found to be practically impossible to successfully place concrete against this ambient sub-strata pressure.

By November the river temperature was down almost to the freezing point. The river bottom area to be covered by concrete was large. Failure loomed as a distinct possibility. The traditional river pier construction method, using piping or buckets to place the concrete under water--much as had been done successfully for the Brooklyn Bridge piers and the foundations for the "Million Dollar Bridge" on the Copper River Railroad--was considered and was discarded as impracticable and unworkable. It then was determined to take a fresh approach toward solving the concrete pouring problem.

---

\* The Wakefield pile was made by spiking three planks of equal width together. The outer planks were set exactly opposite each other, the center one displaced perhaps two or three inches, though kept parallel. The unit would then have a tongue of one edge and a groove of identical size on the other. By driving such units one after the other, in a circle, with the tongue of the new pile in the groove of the pile last driven, a continuous wall was created that was virtually watertight.

The interlocking steel sheet pile was already driving the wooden pile out of service. The steel substitute could be made tighter and be driven to much greater advantage because of its superior strength and the knife-like edge on the bottom. However, the engineers used the Wakefield pile at this crossing in Alaska, possibly because timber was at hand and relatively cheap.

---

UNITED STATES DEPARTMENT OF THE INTERIOR  
NATIONAL PARK SERVICE

**NATIONAL REGISTER OF HISTORIC PLACES  
INVENTORY -- NOMINATION FORM**

FOR NPS USE ONLY	
RECEIVED	FEB 24 1977
DATE ENTERED	SEP 15 1977

Susitna River Bridge (AHRS SITE NO. TLM-006)

CONTINUATION SHEET

ITEM NUMBER 8 PAGE 3 of 3

As the river water temperature lowered toward the freezing point, the subsurface strata froze, eliminating the ambient pressure from sub-surface-strata water in the river bed. The space enclosed by the cofferdams was warmed by means of steam coils. The sand and gravel mix was heated by steam coils, and heated water was used for mixing the concrete, which was poured hot. The concrete for repouring the south pier was poured while the outside air varied from 2 degrees below zero to 48 degrees above. When the north pier was poured the air temperature readings varied from 12 degrees below zero to 34 degrees above. The procedure worked. This technique of pouring hot concrete during sub-zero weather is still in general use in Artic construction. A corollary technique of freezing large dam formations for stability was employed ten years later during major dam construction in the American west. Whether that resulted from this stabilizing technique is conjectural, but would be a logical development.

As pier construction was successfully completed, erection of the main span was carried forward. Riveting of the superstructure was being accomplished on one day when the temperature in the morning was 42 degrees below zero, and rose to a high of 12 degrees above zero that afternoon. The first train crossed the bridge on February 6, 1921, and all major construction was completed ten days later, on February 16.

The piers for the other major bridges on the railroad north of here were all set at the same season of the year, following the same technique. The Hurricane Gulch Bridge had no piers set into the river below it, so was constructed primarily during the summer season. Following the example of construction of the Susitna River Bridge, the Riley Creek Bridge was completed in February 1922, the Tanana River Bridge in February 1923, and the Nenana River (temporary) Bridge completed in April 1922, with the rebuilt (steel) bridge completed in May 1925.

The engineers who recognized and solved this problem deserve recognition for their major contribution to the technology of Artic construction. In addition, the problems of logistics were enormous, seemingly insuperable. Advance engineering surveys had to be made in this remote place. The only access in winter was by dog team and, during the summer, by the long river route and on foot or by pack train, while fighting the terrible Arctic mosquitos. There were no roads, only paths and trails, and the airplane was still a novelty for daredevils, in the interior of Alaska.

The bridge superstructure was fabricated in a mill at Gary, Indiana, shipped by rail like a huge Tinker Toy, to Seattle, by ship to Anchorage, and by rail to the end of steel at the construction site, where it was reconstructed by a team of riggers sent, from Gary, by the manufacturer, The American Bridge Company.

UNITED STATES DEPARTMENT OF THE INTERIOR  
NATIONAL PARK SERVICE

FOR NPS USE ONLY	
RECEIVED	FEB 24 1977
DATE ENTERED	SEP 15 1977

**NATIONAL REGISTER OF HISTORIC PLACES  
INVENTORY -- NOMINATION FORM**

Susitna River Bridge (AHRs SITE NO. TLM-006)

CONTINUATION SHEET

ITEM NUMBER 9 PAGE 1 of 1

Alaska Railroad, The: Probing the Interior. Anchorage: Office of Statewide Cultural Programs, Alaska Division of Parks, History and Archaeology, Miscellaneous Publications, No. 15, October 1975.

"Government Railroad in Alaska Nearing Completion," Scientific American, January 1922, p. 29 ff.

Mears, Col. Frederick, Papers, University of Alaska Archives, Rasmuson Library, Fairbanks, Alaska.

Mears, Col. Frederick, "Report of Col. F. Mears, Chairman of the Alaskan Engineering Commission Relative to Construction and Operation of the Government Railroad in Alaska," Annual Report of the Secretary of the Interior 1921, Appendix D, August 27, 1921.

Mears, Col. Frederick, "The Alaska Railroad," Western Society of Engineers Journal, Volume 26, September 1921, pp. 323-325.

"Memoir of Walter Eugene Angier," American Society of Civil Engineers Transactions, Volume 93, 1926, pp. 1762-1763.

[O'Neel, A.C., Editor], "Copper River and Northwestern Railway, Copper River Bridge Near Miles Glacier, Engineers Report 1910." [1916, Anchorage, Alaska Engineering Commission Report.] Col. Frederick Mears Papers, University of Alaska Archives.

Prince, Bernadine Le May, The Alaska Railroad in Pictures 1914-1964. Anchorage, Ken Wray's Print Shop, 1964.

"Prominent Engineer Arrives in Anchorage," Alaska Railroad Record, Volume IV, Number 24, April 20, 1920, p. 191.

Riggs, Thomas, Jr., "The Government Railroad in Alaska -- What Two Years and Limited Funds Have Accomplished," Engineering Record, Volume 73, Number 19, pp. 600-604.

"Walter Eugene Angier," Who Was Who in America, Volume I, 1897-1942. Chicago, A.N. Marquis Co., 1943, 1962.